

---

# qbittorrent-api

*Release 2020.6.4*

Jul 27, 2020



---

## Contents

---

<b>1</b>	<b>Introduction</b>	<b>1</b>
	<b>Python Module Index</b>	<b>41</b>
	<b>Index</b>	<b>43</b>



Python client implementation for qBittorrent Web API.

Currently supports up to qBittorrent [v4.2.5](#) (Web API v2.5.1) released on April 24, 2020.

The full qBittorrent Web API documentation is available on their [wiki](#).

## 1.1 Features

- The entire qBittorrent Web API is implemented.
- qBittorrent version checking for an endpoint's existence/features is automatically handled.
- All Python versions are supported.
- If the authentication cookie expires, a new one is automatically requested in line with any API call.

## 1.2 Installation

- **Install via pip from [PyPI](#):**

```
– pip install qbittorrent-api
```

- **Install specific release:**

```
– pip install git+https://github.com/rmartin16/qbittorrent-api.git@v2020.6.4#egg=qbittorrent-api
```

- **Install direct from master:**

```
– pip install git+https://github.com/rmartin16/qbittorrent-api.git#egg=qbittorrent-api
```

- Ensure urllib3, requests, and attrdict are installed. (These are installed automatically using the methods above.)
- Enable WebUI in qBittorrent: Tools -> Preferences -> Web UI
- If the Web API will be exposed to the Internet, follow the [recommendations](#).

## 1.3 Getting Started

```
import qbittorrentapi

# instantiate a Client using the appropriate WebUI configuration
qbt_client = qbittorrentapi.Client(host='localhost:8080', username='admin', password=
    ↪ 'adminadmin')

# the Client will automatically acquire/maintain a logged in state in line with any
    ↪ request.
# therefore, this is not necessary; however, you may want to test the provided login
    ↪ credentials.
try:
    qbt_client.auth_log_in()
except qbittorrentapi.LoginFailed as e:
    print(e)

# display qBittorrent info
print(f'qBittorrent: {qbt_client.app.version}')
print(f'qBittorrent Web API: {qbt_client.app.web_api_version}')
for k,v in qbt_client.app.build_info.items(): print(f'{k}: {v}')

# retrieve and show all torrents
for torrent in qbt_client.torrents_info():
    print(f'{torrent.hash[-6:]}: {torrent.name} ({torrent.state})')

# pause all torrents
qbt_client.torrents.pause.all()
```

## 1.4 Usage

First, the Web API endpoints are organized in to eight namespaces.

- Authentication (auth)
- Application (app)
- Log (log)
- Sync (sync)
- Transfer (transfer)
- Torrent Management (torrents)
- RSS (rss)
- Search (search)

Second, this client has two modes of interaction with the qBittorrent Web API.

Each Web API endpoint is implemented one-to-one as a method of the instantiated client.

```
import qbittorrentapi
qbt_client = qbittorrentapi.Client(host='localhost:8080', username='admin', password=
↳ 'adminadmin')
qbt_client.app_version()
qbt_client.rss_rules()
qbt_client.torrents_info()
qbt_client.torrents_resume(torrent_hashes='...')
# and so on
```

However, a more robust interface to the endpoints is available via each namespace. This is intended to provide a more seamless and intuitive interface to the Web API.

```
import qbittorrentapi
qbt_client = qbittorrentapi.Client(host='localhost:8080', username='admin', password=
↳ 'adminadmin')
# changing a preference
is_dht_enabled = qbt_client.app.preferences.dht
qbt_client.app.preferences = dict(dht=not is_dht_enabled)
# stopping all torrents
qbt_client.torrents.pause.all()
# retrieve different views of the log
qbt_client.log.main.warning()
qbt_client.log.main.normal()
```

Finally, some of the objects returned by the client support methods of their own. This is most pronounced for torrents themselves.

```
import qbittorrentapi
qbt_client = qbittorrentapi.Client(host='localhost:8080', username='admin', password=
↳ 'adminadmin')

for torrent in qbt_client.torrents.info.active():
    torrent.set_location(location='/home/user/torrents/')
    torrent.reannounce()
    torrent.upload_limit = -1
```

### 1.4.1 Introduction

Python client implementation for qBittorrent Web API.

Currently supports up to qBittorrent v4.2.5 (Web API v2.5.1) released on April 24, 2020.

The full qBittorrent Web API documentation is available on their [wiki](#).

#### Features

- The entire qBittorrent Web API is implemented.
- qBittorrent version checking for an endpoint's existence/features is automatically handled.
- All Python versions are supported.
- If the authentication cookie expires, a new one is automatically requested in line with any API call.

## Installation

- **Install via pip from PyPI:**

- `pip install qbittorrent-api`

- **Install specific release:**

- `pip install git+https://github.com/rmartin16/qbittorrent-api.git@v2020.6.4#egg=qbittorrent-api`

- **Install direct from master:**

- `pip install git+https://github.com/rmartin16/qbittorrent-api.git#egg=qbittorrent-api`

- Ensure urllib3, requests, and attrdict are installed. (These are installed automatically using the methods above.)
- Enable WebUI in qBittorrent: Tools -> Preferences -> Web UI
- If the Web API will be exposed to the Internet, follow the [recommendations](#).

## Getting Started

```
import qbittorrentapi

# instantiate a Client using the appropriate WebUI configuration
qbt_client = qbittorrentapi.Client(host='localhost:8080', username='admin', password=
↳ 'adminadmin')

# the Client will automatically acquire/maintain a logged in state in line with any
↳ request.
# therefore, this is not necessary; however, you may want to test the provided login
↳ credentials.
try:
    qbt_client.auth_log_in()
except qbittorrentapi.LoginFailed as e:
    print(e)

# display qBittorrent info
print(f'qBittorrent: {qbt_client.app.version}')
print(f'qBittorrent Web API: {qbt_client.app.web_api_version}')
for k,v in qbt_client.app.build_info.items(): print(f'{k}: {v}')

# retrieve and show all torrents
for torrent in qbt_client.torrents_info():
    print(f'{torrent.hash[-6:]}: {torrent.name} ({torrent.state})')

# pause all torrents
qbt_client.torrents.pause.all()
```

## Usage

First, the Web API endpoints are organized in to eight namespaces.

- Authentication (auth)
- Application (app)



- Log (log)
- Sync (sync)
- Transfer (transfer)
- Torrent Management (torrents)
- RSS (rss)
- Search (search)

Second, this client has two modes of interaction with the qBittorrent Web API.

Each Web API endpoint is implemented one-to-one as a method of the instantiated client.

```
import qbittorrentapi
qbt_client = qbittorrentapi.Client(host='localhost:8080', username='admin', password=
↳ 'adminadmin')
qbt_client.app_version()
qbt_client.rss_rules()
qbt_client.torrents_info()
qbt_client.torrents_resume(torrent_hashes='...')
# and so on
```

However, a more robust interface to the endpoints is available via each namespace. This is intended to provide a more seamless and intuitive interface to the Web API.

```
import qbittorrentapi
qbt_client = qbittorrentapi.Client(host='localhost:8080', username='admin', password=
↳ 'adminadmin')
# changing a preference
is_dht_enabled = qbt_client.app.preferences.dht
qbt_client.app.preferences = dict(dht=not is_dht_enabled)
# stopping all torrents
qbt_client.torrents.pause.all()
# retrieve different views of the log
qbt_client.log.main.warning()
qbt_client.log.main.normal()
```

Finally, some of the objects returned by the client support methods of their own. This is most pronounced for torrents themselves.

```
import qbittorrentapi
qbt_client = qbittorrentapi.Client(host='localhost:8080', username='admin', password=
↳ 'adminadmin')

for torrent in qbt_client.torrents.info.active():
    torrent.set_location(location='/home/user/torrents/')
    torrent.reannounce()
    torrent.upload_limit = -1
```

## 1.4.2 Behavior & Configuration

### Untrusted WebUI Certificate

- qBittorrent allows you to configure HTTPS with an untrusted certificate; this commonly includes self-signed certificates.

- When using such a certificate, instantiate `Client` with `VERIFY_WEBUI_CERTIFICATE=False` or set environment variable `PYTHON_QBITTORRENTAPI_DO_NOT_VERIFY_WEBUI_CERTIFICATE` to a non-null value.
- Failure to do this for will cause connections to qBittorrent to fail.
- As a word of caution, doing this actually does turn off certificate verification. Therefore, for instance, potential man-in-the-middle attacks will not be detected and reported (since the error is suppressed). However, the connection will remain encrypted.

## Host, Username and Password

- These can be provided when instantiating `Client` or calling `qbt_client.auth_log_in(username='...', password='...')`.
- Alternatively, set environment variables `PYTHON_QBITTORRENTAPI_HOST`, `PYTHON_QBITTORRENTAPI_USERNAME` and `PYTHON_QBITTORRENTAPI_PASSWORD`.

## Unimplemented API Endpoints

- Since the qBittorrent Web API has evolved over time, some endpoints may not be available from the qBittorrent host.
- By default, if a call is made to endpoint that doesn't exist for the version of the qBittorrent host (e.g., the Search endpoints were introduced in Web API v2.1.1), there's a debug logger output and `None` is returned.
- To raise `NotImplementedError` instead, instantiate `Client` with `RAISE_NOTIMPLEMENTEDERROR_FOR_UNIMPLEMENTED`

## Disable Logging Debug Output

- Instantiate `Client` with `DISABLE_LOGGING_DEBUG_OUTPUT=True` or manually disable logging for the relevant packages:
  - `logging.getLogger('qbittorrentapi').setLevel(logging.INFO)`
  - `logging.getLogger('requests').setLevel(logging.INFO)`
  - `logging.getLogger('urllib3').setLevel(logging.INFO)`

### 1.4.3 Performance

By default, complex objects are returned from some endpoints. These objects allow for accessing the response's items as attributes and include methods for contextually relevant actions (such as `start()` and `stop()` for a torrent, for example).

This comes at the cost of performance, though. Generally, this cost isn't large; however, some endpoints, such as `torrents_files()`, may need to convert a large payload and the cost can be significant.

This client can be configured to always return only the simple JSON if desired. Simply set `SIMPLE_RESPONSES=True` when instantiating the client.

```
qbt_client = qbittorrentapi.Client(host='localhost:8080', username='admin', password=
↪ 'adminadmin', SIMPLE_RESPONSES=True)
```

Alternatively, `SIMPLE_RESPONSES` can be set to `True` to return the simple JSON only for an individual method call.

```
qbt_client.torrents.files(torrent_hash='...', SIMPLE_RESPONSES=True)
```

## 1.4.4 Exceptions

**exception** `qbittorrentapi.exceptions.APIError`

Bases: `Exception`

Base error for all exceptions from this Client.

**exception** `qbittorrentapi.exceptions.FileError`

Bases: `OSError`, `qbittorrentapi.exceptions.APIError`

Base class for all exceptions for file handling.

**exception** `qbittorrentapi.exceptions.TorrentFileError`

Bases: `qbittorrentapi.exceptions.FileError`

Base class for all exceptions for torrent files.

**exception** `qbittorrentapi.exceptions.TorrentFileNotFoundError`

Bases: `qbittorrentapi.exceptions.TorrentFileError`

Specified torrent file does not appear to exist.

**exception** `qbittorrentapi.exceptions.TorrentFilePermissionError`

Bases: `qbittorrentapi.exceptions.TorrentFileError`

Permission was denied to read the specified torrent file.

**exception** `qbittorrentapi.exceptions.APIConnectionError(*args, **kwargs)`

Bases: `requests.exceptions.RequestException`, `qbittorrentapi.exceptions.APIError`

Base class for all communications errors including HTTP errors.

**exception** `qbittorrentapi.exceptions.LoginFailed(*args, **kwargs)`

Bases: `qbittorrentapi.exceptions.APIConnectionError`

This can technically be raised with any request since log in may be attempted for any request and could fail.

**exception** `qbittorrentapi.exceptions.HTTPError(*args, **kwargs)`

Bases: `requests.exceptions.HTTPError`, `qbittorrentapi.exceptions.APIConnectionError`

Base error for all HTTP errors. All errors following a successful connection to qBittorrent are returned as HTTP statuses.

**exception** `qbittorrentapi.exceptions.HTTP4XXError(*args, **kwargs)`

Bases: `qbittorrentapi.exceptions.HTTPError`

Base error for all HTTP 4XX statuses.

**exception** `qbittorrentapi.exceptions.HTTP5XXError(*args, **kwargs)`

Bases: `qbittorrentapi.exceptions.HTTPError`

Base error for all HTTP 5XX statuses.

**exception** `qbittorrentapi.exceptions.HTTP400Error(*args, **kwargs)`

Bases: `qbittorrentapi.exceptions.HTTP4XXError`

HTTP 400 Status

**exception** `qbittorrentapi.exceptions.HTTP401Error(*args, **kwargs)`  
Bases: `qbittorrentapi.exceptions.HTTP4XXError`  
HTTP 401 Status

**exception** `qbittorrentapi.exceptions.HTTP403Error(*args, **kwargs)`  
Bases: `qbittorrentapi.exceptions.HTTP4XXError`  
HTTP 403 Status

**exception** `qbittorrentapi.exceptions.HTTP404Error(*args, **kwargs)`  
Bases: `qbittorrentapi.exceptions.HTTP4XXError`  
HTTP 404 Status

**exception** `qbittorrentapi.exceptions.HTTP409Error(*args, **kwargs)`  
Bases: `qbittorrentapi.exceptions.HTTP4XXError`  
HTTP 409 Status

**exception** `qbittorrentapi.exceptions.HTTP415Error(*args, **kwargs)`  
Bases: `qbittorrentapi.exceptions.HTTP4XXError`  
HTTP 415 Status

**exception** `qbittorrentapi.exceptions.HTTP500Error(*args, **kwargs)`  
Bases: `qbittorrentapi.exceptions.HTTP5XXError`  
HTTP 500 Status

**exception** `qbittorrentapi.exceptions.MissingRequiredParameters400Error(*args, **kwargs)`  
Bases: `qbittorrentapi.exceptions.HTTP400Error`  
Endpoint call is missing one or more required parameters.

**exception** `qbittorrentapi.exceptions.InvalidRequest400Error(*args, **kwargs)`  
Bases: `qbittorrentapi.exceptions.HTTP400Error`  
One or more endpoint arguments are malformed.

**exception** `qbittorrentapi.exceptions.Unauthorized401Error(*args, **kwargs)`  
Bases: `qbittorrentapi.exceptions.HTTP401Error`  
Primarily reserved for XSS and host header issues.

**exception** `qbittorrentapi.exceptions.Forbidden403Error(*args, **kwargs)`  
Bases: `qbittorrentapi.exceptions.HTTP403Error`  
Not logged in, IP has been banned, or calling an API method that isn't public.

**exception** `qbittorrentapi.exceptions.NotFound404Error(*args, **kwargs)`  
Bases: `qbittorrentapi.exceptions.HTTP404Error`  
This should mean qBittorrent couldn't find a torrent for the torrent hash.

**exception** `qbittorrentapi.exceptions.Conflict409Error(*args, **kwargs)`  
Bases: `qbittorrentapi.exceptions.HTTP409Error`  
Returned if arguments don't make sense specific to the endpoint.

**exception** `qbittorrentapi.exceptions.UnsupportedMediaType415Error(*args, **kwargs)`  
Bases: `qbittorrentapi.exceptions.HTTP415Error`  
torrents/add endpoint will return this for invalid URL(s) or files.

**exception** `qbittorrentapi.exceptions.InternalServerError500Error` (*\*args*,  
*\*\*kwargs*)

Bases: `qbittorrentapi.exceptions.HTTP500Error`

Returned if qBittorrent craps on itself while processing the request. . .

## 1.4.5 API Reference

### Application

**class** `qbittorrentapi.AppAPIMixin` (*host=""*, *port=None*, *username=None*, *password=None*,  
*\*\*kwargs*)

Implementation of all Application API methods

**app\_buildInfo** (*\*\*kwargs*)

Retrieve build info. (alias: `app_buildInfo`)

**Returns** Dictionary of build info. Each piece of info is an attribute. Properties: <https://github.com/qbittorrent/qBittorrent/wiki/Web-API-Documentation#get-build-info>

**app\_build\_info** (*\*\*kwargs*)

Retrieve build info. (alias: `app_buildInfo`)

**Returns** Dictionary of build info. Each piece of info is an attribute. Properties: <https://github.com/qbittorrent/qBittorrent/wiki/Web-API-Documentation#get-build-info>

**app\_defaultSavePath** (*\*\*kwargs*)

Retrieves the default path for where torrents are saved. (alias: `app_defaultSavePath`)

**Returns** string

**app\_default\_save\_path** (*\*\*kwargs*)

Retrieves the default path for where torrents are saved. (alias: `app_defaultSavePath`)

**Returns** string

**app\_preferences** (*\*\*kwargs*)

Retrieve qBittorrent application preferences.

**Returns** Dictionary of preferences. Each preference is an attribute. Properties: <https://github.com/qbittorrent/qBittorrent/wiki/Web-API-Documentation#get-application-preferences>

**app\_setPreferences** (*prefs=None*, *\*\*kwargs*)

Set one or more preferences in qBittorrent application. (alias: `app_setPreferences`)

**Parameters** `prefs` – dictionary of preferences to set

**Returns** None

**app\_set\_preferences** (*prefs=None*, *\*\*kwargs*)

Set one or more preferences in qBittorrent application. (alias: `app_setPreferences`)

**Parameters** `prefs` – dictionary of preferences to set

**Returns** None

**app\_shutdown** (*\*\*kwargs*)

Shutdown qBittorrent.

**app\_version** (*\*\*kwargs*)

Retrieve application version

**Returns** string

**app\_web\_api\_version** (\*\*kwargs)  
Retrieve web API version. (alias: app\_webapiVersion)

**Returns** string

**app\_webapiVersion** (\*\*kwargs)  
Retrieve web API version. (alias: app\_webapiVersion)

**Returns** string

**application**  
Allows for transparent interaction with Application endpoints. (alias: app)  
  
See Application class for usage. :return: Application object

**class** qbittorrentapi.**Application** (\*args, \*\*kwargs)  
Allows interaction with “Application” API endpoints.

**Usage:**

```
>>> from qbittorrentapi import Client
>>> client = Client(host='localhost:8080', username='admin', password=
↳ 'adminadmin')
>>> # this are all the same attributes that are available as named in the
>>> # endpoints or the more pythonic names in Client (with or without 'app_'
↳ prepended)
>>> webapiVersion = client.application.webapiVersion
>>> web_api_version = client.application.web_api_version
>>> app_web_api_version = client.application.app_web_api_version
>>> # access and set preferences as attributes
>>> is_dht_enabled = client.application.preferences.dht
>>> # supports sending a just subset of preferences to update
>>> client.application.preferences = dict(dht=(not is_dht_enabled))
>>> prefs = client.application.preferences
>>> prefs['web_ui_clickjacking_protection_enabled'] = True
>>> client.app.preferences = prefs
>>>
>>> client.application.shutdown()
```

**buildInfo**

**build\_info**

**defaultSavePath**

**default\_save\_path**

**preferences**

**setPreferences** (prefs=None, \*\*kwargs)

**set\_preferences** (prefs=None, \*\*kwargs)

**shutdown** ()

**version**

**web\_api\_version**

**webapiVersion**

## Authentication

**class** qbittorrentapi.**Request** (*host=""*, *port=None*, *username=None*, *password=None*, *\*\*kwargs*)  
Facilitates HTTP requests to qBittorrent

**auth\_log\_in** (*username=None*, *password=None*)  
Log in to qBittorrent host.

**Exceptions:** LoginFailed if credentials failed to log in Forbidden403Error if user is banned... or not logged in

### Parameters

- **username** – user name for qBittorrent client
- **password** – password for qBittorrent client

**Returns** None

**auth\_log\_out** (*\*\*kwargs*)  
End session with qBittorrent

## Client

**class** qbittorrentapi.**Client** (*host=""*, *port=None*, *username=None*, *password=None*, *\*\*kwargs*)  
Initialize API for qBittorrent client.

Host must be specified. Username and password can be specified at login. A call to `auth_log_in` is not explicitly required if username and password are provided during Client construction.

### Parameters

- **host** – hostname for qBittorrent Web API (e.g. `[http[s]://]localhost[:8080]`)
- **port** – port number for qBittorrent Web API (note: only used if host does not contain a port)
- **username** – user name for qBittorrent client
- **password** – password for qBittorrent client
- **SIMPLE\_RESPONSES** – By default, complex objects are returned from some endpoints. These objects will allow for accessing responses' items as attributes and include methods for contextually relevant actions. This comes at the cost of performance. Generally, this cost isn't large; however, some endpoints, such as `torrents_files()` method, may need to convert a large payload. Set this to True to return the simple JSON back. Alternatively, set this to True only for an individual method call. For instance, when requesting the files for a torrent: `client.torrents_files(hash='...', SIMPLE_RESPONSES=True)`.
- **VERIFY\_WEBUI\_CERTIFICATE** – Set to False to skip verify certificate for HTTPS connections; for instance, if the connection is using a self-signed certificate. Not setting this to False for self-signed certs will cause a `APIConnectionError` exception to be raised.
- **RAISE\_UNIMPLEMENTEDERROR\_FOR\_UNIMPLEMENTED\_API\_ENDPOINTS** – Some Endpoints may not be implemented in older versions of qBittorrent. Setting this to True will raise a `UnimplementedError` instead of just returning None.
- **DISABLE\_LOGGING\_DEBUG\_OUTPUT** – Turn off debug output from logging for this package as well as Requests & urllib3.

## Log

**class** qbittorrentapi.**LogAPIMixin** (*host=""*, *port=None*, *username=None*, *password=None*,  
  *\*\*kwargs*)

Implementation of all Log API methods

**log\_main** (*normal=None*, *info=None*, *warning=None*, *critical=None*, *last\_known\_id=None*,  
                  *\*\*kwargs*)

Retrieve the qBittorrent log entries. Iterate over returned object.

### Parameters

- **normal** – False to exclude ‘normal’ entries
- **info** – False to exclude ‘info’ entries
- **warning** – False to exclude ‘warning’ entries
- **critical** – False to exclude ‘critical’ entries
- **last\_known\_id** – only entries with an ID greater than this value will be returned

**Returns** List of log entries.

**log\_peers** (*last\_known\_id=None*, *\*\*kwargs*)

Retrieve qBittorrent peer log.

**Parameters** **last\_known\_id** – only entries with an ID greater than this value will be returned

**Returns** list of log entries in a List

**class** qbittorrentapi.**Log** (*client*)

Allows interaction with “Log” API endpoints.

**Usage:**

```
>>> from qbittorrentapi import Client
>>> client = Client(host='localhost:8080', username='admin', password=
↳ 'adminadmin')
>>> # this is all the same attributes that are available as named in the
>>> # endpoints or the more pythonic names in Client (with or without 'log_'
↳ prepended)
>>> log_list = client.log.main()
>>> peers_list = client.log.peers(hash='...')
>>> # can also filter log down with additional attributes
>>> log_info = client.log.main.info(last_known_id='...')
>>> log_warning = client.log.main.warning(last_known_id='...')
```

**peers** (*last\_known\_id=None*, *\*\*kwargs*)

## RSS

**class** qbittorrentapi.**RSSAPIMixin** (*host=""*, *port=None*, *username=None*, *password=None*,  
  *\*\*kwargs*)

Implementation of all RSS API methods

**rss\_addFeed** (*url=None*, *item\_path=None*, *\*\*kwargs*)

Add new RSS feed. Folders in path must already exist. (alias: `rss_addFeed`)

**Exceptions:** Conflict409Error

### Parameters



- **url** – URL of RSS feed (e.g <http://thepiratebay.org/rss/top100/200>)
- **item\_path** – Name and/or path for new feed (e.g. FolderSubfolderFeedName)

**Returns** None

**rss\_addFolder** (*folder\_path=None, \*\*kwargs*)

Add a RSS folder. Any intermediate folders in path must already exist. (alias: rss\_addFolder)

**Exceptions:** Conflict409Error

**Parameters** **folder\_path** – path to new folder (e.g. LinuxISOs)

**Returns** None

**rss\_add\_feed** (*url=None, item\_path=None, \*\*kwargs*)

Add new RSS feed. Folders in path must already exist. (alias: rss\_addFeed)

**Exceptions:** Conflict409Error

**Parameters**

- **url** – URL of RSS feed (e.g <http://thepiratebay.org/rss/top100/200>)
- **item\_path** – Name and/or path for new feed (e.g. FolderSubfolderFeedName)

**Returns** None

**rss\_add\_folder** (*folder\_path=None, \*\*kwargs*)

Add a RSS folder. Any intermediate folders in path must already exist. (alias: rss\_addFolder)

**Exceptions:** Conflict409Error

**Parameters** **folder\_path** – path to new folder (e.g. LinuxISOs)

**Returns** None

**rss\_items** (*include\_feed\_data=None, \*\*kwargs*)

Retrieve RSS items and optionally feed data.

**Parameters** **include\_feed\_data** – True or false to include feed data

**Returns** dictionary of RSS items

**rss\_markAsRead** (*item\_path=None, article\_id=None, \*\*kwargs*)

Mark RSS article as read. If article ID is not provider, the entire feed is marked as read. (alias: rss\_markAsRead)

**Exceptions:** NotFound404Error

**Parameters**

- **item\_path** – path to item to be refreshed (e.g. FolderSubfolderItemName)
- **article\_id** – article ID from rss\_items()

**Returns** None

**rss\_mark\_as\_read** (*item\_path=None, article\_id=None, \*\*kwargs*)

Mark RSS article as read. If article ID is not provider, the entire feed is marked as read. (alias: rss\_markAsRead)

**Exceptions:** NotFound404Error

**Parameters**

- **item\_path** – path to item to be refreshed (e.g. FolderSubfolderItemName)
- **article\_id** – article ID from rss\_items()

**Returns** None**rss\_matchingArticles** (*rule\_name=None, \*\*kwargs*)

Fetch all articles matching a rule. (alias: rss\_matchingArticles)

Exceptions:

**Parameters** **rule\_name** – Name of rule to return matching articles

:return

**rss\_matching\_articles** (*rule\_name=None, \*\*kwargs*)

Fetch all articles matching a rule. (alias: rss\_matchingArticles)

Exceptions:

**Parameters** **rule\_name** – Name of rule to return matching articles

:return

**rss\_moveItem** (*orig\_item\_path=None, new\_item\_path=None, \*\*kwargs*)

Move/rename a RSS item (folder, feed, etc). (alias: rss\_moveItem)

**Exceptions:** Conflict409Error**Parameters**

- **orig\_item\_path** – path to item to be removed (e.g. FolderSubfolderItemName)
- **new\_item\_path** – path to item to be removed (e.g. FolderSubfolderItemName)

**Returns** None**rss\_move\_item** (*orig\_item\_path=None, new\_item\_path=None, \*\*kwargs*)

Move/rename a RSS item (folder, feed, etc). (alias: rss\_moveItem)

**Exceptions:** Conflict409Error**Parameters**

- **orig\_item\_path** – path to item to be removed (e.g. FolderSubfolderItemName)
- **new\_item\_path** – path to item to be removed (e.g. FolderSubfolderItemName)

**Returns** None**rss\_refreshItem** (*item\_path=None, \*\*kwargs*)

Trigger a refresh for a RSS item (alias: rss\_refreshItem)

**Parameters** **item\_path** – path to item to be refreshed (e.g. FolderSubfolderItemName)**Returns** None**rss\_refresh\_item** (*item\_path=None, \*\*kwargs*)

Trigger a refresh for a RSS item (alias: rss\_refreshItem)

**Parameters** **item\_path** – path to item to be refreshed (e.g. FolderSubfolderItemName)**Returns** None

**rss\_removeItem** (*item\_path=None, \*\*kwargs*)

Remove a RSS item (folder, feed, etc). (alias: rss\_removeItem)

NOTE: Removing a folder also removes everything in it.

**Exceptions:** Conflict409Error

**Parameters** **item\_path** – path to item to be removed (e.g. FolderSubfolderItemName)

**Returns** None

**rss\_removeRule** (*rule\_name=None, \*\*kwargs*)

Delete a RSS auto-downloading rule. (alias: rss\_removeRule)

**Parameters** **rule\_name** – Name of rule to delete

**Returns** None

**rss\_remove\_item** (*item\_path=None, \*\*kwargs*)

Remove a RSS item (folder, feed, etc). (alias: rss\_removeItem)

NOTE: Removing a folder also removes everything in it.

**Exceptions:** Conflict409Error

**Parameters** **item\_path** – path to item to be removed (e.g. FolderSubfolderItemName)

**Returns** None

**rss\_remove\_rule** (*rule\_name=None, \*\*kwargs*)

Delete a RSS auto-downloading rule. (alias: rss\_removeRule)

**Parameters** **rule\_name** – Name of rule to delete

**Returns** None

**rss\_renameRule** (*orig\_rule\_name=None, new\_rule\_name=None, \*\*kwargs*)

Rename a RSS auto-download rule. (alias: rss\_renameRule)

**Parameters**

- **orig\_rule\_name** – current name of rule
- **new\_rule\_name** – new name for rule

**Returns** None

**rss\_rename\_rule** (*orig\_rule\_name=None, new\_rule\_name=None, \*\*kwargs*)

Rename a RSS auto-download rule. (alias: rss\_renameRule)

**Parameters**

- **orig\_rule\_name** – current name of rule
- **new\_rule\_name** – new name for rule

**Returns** None

**rss\_rules** (*\*\*kwargs*)

Retrieve RSS auto-download rule definitions.

**Returns** None

**rss\_setRule** (*rule\_name=None, rule\_def=None, \*\*kwargs*)

Create a new RSS auto-downloading rule. (alias: rss\_setRule)

**Parameters**

- **rule\_name** – name for new rule
- **rule\_def** – dictionary with rule fields Properties: <https://github.com/qbittorrent/qBittorrent/wiki/Web-API-Documentation#set-auto-downloading-rule>

**Returns** None

**rss\_set\_rule** (*rule\_name=None, rule\_def=None, \*\*kwargs*)  
Create a new RSS auto-downloading rule. (alias: `rss_setRule`)

**Parameters**

- **rule\_name** – name for new rule
- **rule\_def** – dictionary with rule fields Properties: <https://github.com/qbittorrent/qBittorrent/wiki/Web-API-Documentation#set-auto-downloading-rule>

**Returns** None

**class** qbittorrentapi.**RSS** (*client*)  
Allows interaction with “RSS” API endpoints.

**Usage:**

```
>>> from qbittorrentapi import Client
>>> client = Client(host='localhost:8080', username='admin', password=
↳ 'adminadmin')
>>> # this is all the same attributes that are available as named in the
>>> # endpoints or the more pythonic names in Client (with or without 'log_'
↳ prepended)
>>> rss_rules = client.rss.rules
>>> client.rss.addFolder(folder_path="TPB")
>>> client.rss.addFeed(url='...', item_path="TPB\Top100")
>>> client.rss.remove_item(item_path="TPB") # deletes TPB and Top100
>>> client.rss.set_rule(rule_name="...", rule_def={...})
>>> client.rss.items.with_data
>>> client.rss.items.without_data
```

**addFeed** (*url=None, item\_path=None, \*\*kwargs*)

**addFolder** (*folder\_path=None, \*\*kwargs*)

**add\_feed** (*url=None, item\_path=None, \*\*kwargs*)

**add\_folder** (*folder\_path=None, \*\*kwargs*)

**markAsRead** (*item\_path=None, article\_id=None, \*\*kwargs*)

**mark\_as\_read** (*item\_path=None, article\_id=None, \*\*kwargs*)

**matchingArticles** (*rule\_name=None, \*\*kwargs*)

**matching\_articles** (*rule\_name=None, \*\*kwargs*)

**moveItem** (*orig\_item\_path=None, new\_item\_path=None, \*\*kwargs*)

**move\_item** (*orig\_item\_path=None, new\_item\_path=None, \*\*kwargs*)

**refreshItem** (*item\_path=None*)

**refresh\_item** (*item\_path=None*)

**removeItem** (*item\_path=None, \*\*kwargs*)

**removeRule** (*rule\_name=None, \*\*kwargs*)

```

remove_item (item_path=None, **kwargs)
remove_rule (rule_name=None, **kwargs)
renameRule (orig_rule_name=None, new_rule_name=None, **kwargs)
rename_rule (orig_rule_name=None, new_rule_name=None, **kwargs)
rules
setRule (rule_name=None, rule_def=None, **kwargs)
set_rule (rule_name=None, rule_def=None, **kwargs)

```

## Search

```

class qbittorrentapi.SearchAPIMixin (host="", port=None, username=None, password=None,
                                     **kwargs)

```

Implementation for all Search API methods

```

search_categories (plugin_name=None, **kwargs)

```

Retrieve categories for search.

**Parameters** **plugin\_name** – Limit categories returned by plugin(s) (supports ‘all’ and ‘enabled’)

**Returns** list of categories

```

search_delete (search_id=None, **kwargs)

```

Delete a search job.

**ExceptionsL** NotFound404Error

**Parameters** **search\_id** – ID of search to delete

**Returns** None

```

search_enablePlugin (plugins=None, enable=None, **kwargs)

```

Enable or disable search plugin(s). (alias: search\_enablePlugin)

**Parameters**

- **plugins** – list of plugin names
- **enable** – True or False

**Returns** None

```

search_enable_plugin (plugins=None, enable=None, **kwargs)

```

Enable or disable search plugin(s). (alias: search\_enablePlugin)

**Parameters**

- **plugins** – list of plugin names
- **enable** – True or False

**Returns** None

```

search_installPlugin (sources=None, **kwargs)

```

Install search plugins from either URL or file. (alias: search\_installPlugin)

**Parameters** **sources** – list of URLs or filepaths

**Returns** None

**search\_install\_plugin** (*sources=None, \*\*kwargs*)

Install search plugins from either URL or file. (alias: search\_installPlugin)

**Parameters** **sources** – list of URLs or filepaths

**Returns** None

**search\_plugins** (*\*\*kwargs*)

Retrieve details of search plugins.

**Returns** List of plugins. **Properties:** <https://github.com/qbittorrent/qBittorrent/wiki/Web-API-Documentation#get-search-plugins>

**search\_results** (*search\_id=None, limit=None, offset=None, \*\*kwargs*)

Retrieve the results for the search.

**Exceptions** NotFound404Error Conflict409Error

**Parameters**

- **search\_id** – ID of search job
- **limit** – number of results to return
- **offset** – where to start returning results

**Returns** Dictionary of results **Properties:** <https://github.com/qbittorrent/qBittorrent/wiki/Web-API-Documentation#get-search-results>

**search\_start** (*pattern=None, plugins=None, category=None, \*\*kwargs*)

Start a search. Python must be installed. Host may limit number of concurrent searches.

**Exceptions:** Conflict409Error

**Parameters**

- **pattern** – term to search for
- **plugins** – list of plugins to use for searching (supports ‘all’ and ‘enabled’)
- **category** – categories to limit search; dependent on plugins. (supports ‘all’)

**Returns** search job

**search\_status** (*search\_id=None, \*\*kwargs*)

Retrieve status of one or all searches.

**Exceptions:** NotFound404Error

**Parameters** **search\_id** – ID of search to get status; leave empty for status of all jobs

**Returns** dictionary of searches **Properties:** <https://github.com/qbittorrent/qBittorrent/wiki/Web-API-Documentation#get-search-status>

**search\_stop** (*search\_id=None, \*\*kwargs*)

Stop a running search.

**Exceptions:** NotFound404Error

**Parameters** **search\_id** – ID of search job to stop

**Returns** None

**search\_uninstallPlugin** (*names=None, \*\*kwargs*)  
Uninstall search plugins. (alias: search\_uninstallPlugin)

**Parameters** **names** – names of plugins to uninstall

**Returns** None

**search\_uninstall\_plugin** (*names=None, \*\*kwargs*)  
Uninstall search plugins. (alias: search\_uninstallPlugin)

**Parameters** **names** – names of plugins to uninstall

**Returns** None

**search\_updatePlugins** (*\*\*kwargs*)  
Auto update search plugins. (alias: search\_updatePlugins)

**Returns** None

**search\_update\_plugins** (*\*\*kwargs*)  
Auto update search plugins. (alias: search\_updatePlugins)

**Returns** None

**class** qbittorrentapi.**Search** (*\*args, \*\*kwargs*)  
Allows interaction with “Search” API endpoints.

**Usage:**

```
>>> from qbittorrentapi import Client
>>> client = Client(host='localhost:8080', username='admin', password=
↳ 'adminadmin')
>>> # this is all the same attributes that are available as named in the
>>> # endpoints or the more pythonic names in Client (with or without
↳ 'search_' prepended)
>>> # initiate searches and retrieve results
>>> search_job = client.search.start(pattern='Ubuntu', plugins='all',
↳ category='all')
>>> status = search_job.status()
>>> results = search_job.result()
>>> search_job.delete()
>>> # inspect and manage plugins
>>> plugins = client.search.plugins
>>> cats = client.search.categories(plugin_name='...')
>>> client.search.install_plugin(sources='...')
>>> client.search.update_plugins()
```

**categories** (*plugin\_name=None, \*\*kwargs*)

**delete** (*search\_id=None, \*\*kwargs*)

**enablePlugin** (*plugins=None, enable=None, \*\*kwargs*)

**enable\_plugin** (*plugins=None, enable=None, \*\*kwargs*)

**installPlugin** (*sources=None, \*\*kwargs*)

**install\_plugin** (*sources=None, \*\*kwargs*)

**plugins**

**results** (*search\_id=None, limit=None, offset=None, \*\*kwargs*)

**start** (*pattern=None, plugins=None, category=None, \*\*kwargs*)

**status** (*search\_id=None, \*\*kwargs*)

```
stop (search_id=None, **kwargs)
uninstallPlugin (sources=None, **kwargs)
uninstall_plugin (sources=None, **kwargs)
updatePlugins (**kwargs)
update_plugins (**kwargs)
```

## Sync

```
class qbittorrentapi.SyncAPIMixin (host="", port=None, username=None, password=None,
                                   **kwargs)
```

Implementation of all Sync API Methods

```
sync_maindata (rid=0, **kwargs)
```

Retrieves sync data.

**Parameters** `rid` – response ID

**Returns** dictionary response Properties: <https://github.com/qbittorrent/qBittorrent/wiki/Web-API-Documentation#get-main-data>

```
sync_torrentPeers (torrent_hash=None, rid=0, **kwargs)
```

Retrieves torrent sync data. (alias: `sync_torrentPeers`)

**Exceptions:** `NotFound404Error`

### Parameters

- **torrent\_hash** – hash for torrent
- **rid** – response ID

**Returns** Dictionary of torrent sync data. Properties: <https://github.com/qbittorrent/qBittorrent/wiki/Web-API-Documentation#get-torrent-peers-data>

```
sync_torrent_peers (torrent_hash=None, rid=0, **kwargs)
```

Retrieves torrent sync data. (alias: `sync_torrentPeers`)

**Exceptions:** `NotFound404Error`

### Parameters

- **torrent\_hash** – hash for torrent
- **rid** – response ID

**Returns** Dictionary of torrent sync data. Properties: <https://github.com/qbittorrent/qBittorrent/wiki/Web-API-Documentation#get-torrent-peers-data>

```
class qbittorrentapi.Sync (client)
```

Allows interaction with the “Sync” API endpoints.

### Usage:

```
>>> from qbittorrentapi import Client
>>> client = Client(host='localhost:8080', username='admin', password=
↳ 'adminadmin')
>>> # this are all the same attributes that are available as named in the
>>> # endpoints or the more pythonic names in Client (with or without 'sync_
↳ 'prepended)
```

(continues on next page)



(continued from previous page)

```

>>> maindata = client.sync.maindata(rid="...")
>>> # for use when continuously calling maindata for changes in torrents
>>> # this will automatically request the changes since the last call
>>> md = client.sync.maindata.delta()
>>> #
>>> torrentPeers= client.sync.torrentPeers(hash="...", rid='...')
>>> torrent_peers = client.sync.torrent_peers(hash="...", rid='...')

```

## Torrents

**class** qbittorrentapi.**TorrentsAPIMixin** (*host="", port=None, username=None, password=None, \*\*kwargs*)

Implementation of all Torrents API methods

### **torrent\_categories**

Allows for transparent interaction with Torrent Categories endpoints.

See `Torrent_Categories` class for usage. :return: `Torrent Categories` object

### **torrent\_tags**

Allows for transparent interaction with Torrent Tags endpoints.

See `Torrent_Tags` class for usage. :return: `Torrent Tags` object

**torrents\_add** (*urls=None, torrent\_files=None, save\_path=None, cookie=None, category=None, is\_skip\_checking=None, is\_paused=None, is\_root\_folder=None, rename=None, upload\_limit=None, download\_limit=None, use\_auto\_torrent\_management=None, is\_sequential\_download=None, is\_first\_last\_piece\_priority=None, \*\*kwargs*)

Add one or more torrents by URLs and/or torrent files.

**Exceptions:** `UnsupportedMediaType415Error` if file is not a valid torrent file `TorrentFileNotFoundError` if a torrent file doesn't exist `TorrentFilePermissionError` if read permission is denied to torrent file

### **Parameters**

- **urls** – List of URLs (<http://>, <https://>, magnet: and bc://bt/)
- **torrent\_files** – list of torrent files
- **save\_path** – location to save the torrent data
- **cookie** – cookie to retrieve torrents by URL
- **category** – category to assign to torrent(s)
- **is\_skip\_checking** – skip hash checking
- **is\_paused** – True to start torrent(s) paused
- **is\_root\_folder** – True or False to create root folder
- **rename** – new name for torrent(s)
- **upload\_limit** – upload limit in bytes/second
- **download\_limit** – download limit in bytes/second
- **use\_auto\_torrent\_management** – True or False to use automatic torrent management
- **is\_sequential\_download** – True or False for sequential download

- **is\_first\_last\_piece\_priority** – True or False for first and last piece download priority

**Returns** “Ok.” for success and “Fails.” for failure

**torrents\_addPeers** (*peers=None, torrent\_hashes=None, \*\*kwargs*)

Add one or more peers to one or more torrents. (alias: `torrents_addPeers`)

**Exceptions:** `InvalidRequest400Error` for invalid peers

**Parameters**

- **peers** – one or more peers to add. each peer should take the form ‘host:port’
- **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.

**Returns** dictionary - {<hash>: {‘added’: #, ‘failed’: #}}

**torrents\_addTags** (*tags=None, torrent\_hashes=None, \*\*kwargs*)

Add one or more tags to one or more torrents. (alias: `torrents_addTags`) Note: Tags that do not exist will be created on-the-fly.

**Parameters**

- **tags** – tag name or list of tags
- **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.

**Returns** None

**torrents\_addTrackers** (*torrent\_hash=None, urls=None, \*\*kwargs*)

Add trackers to a torrent. (alias: `torrents_addTrackers`)

**Exceptions:** `NotFound404Error`

**Parameters**

- **torrent\_hash** – hash for torrent
- **urls** – tracker urls to add to torrent

**Returns** None

**torrents\_add\_peers** (*peers=None, torrent\_hashes=None, \*\*kwargs*)

Add one or more peers to one or more torrents. (alias: `torrents_addPeers`)

**Exceptions:** `InvalidRequest400Error` for invalid peers

**Parameters**

- **peers** – one or more peers to add. each peer should take the form ‘host:port’
- **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.

**Returns** dictionary - {<hash>: {‘added’: #, ‘failed’: #}}

**torrents\_add\_tags** (*tags=None, torrent\_hashes=None, \*\*kwargs*)

Add one or more tags to one or more torrents. (alias: `torrents_addTags`) Note: Tags that do not exist will be created on-the-fly.

**Parameters**

- **tags** – tag name or list of tags

- **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.

**Returns** None

**torrents\_add\_trackers** (*torrent\_hash=None, urls=None, \*\*kwargs*)

Add trackers to a torrent. (alias: torrents\_addTrackers)

**Exceptions:** NotFound404Error

**Parameters**

- **torrent\_hash** – hash for torrent
- **urls** – tracker urls to add to torrent

**Returns** None

**torrents\_bottomPrio** (*torrent\_hashes=None, \*\*kwargs*)

Set torrent as highest priority. Torrent Queuing must be enabled. (alias: torrents\_bottomPrio)

**Exceptions:** Conflict409

**Parameters** **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.

**Returns** None

**torrents\_bottom\_priority** (*torrent\_hashes=None, \*\*kwargs*)

Set torrent as highest priority. Torrent Queuing must be enabled. (alias: torrents\_bottomPrio)

**Exceptions:** Conflict409

**Parameters** **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.

**Returns** None

**torrents\_categories** (*\*\*kwargs*)

Retrieve all category definitions

Note: torrents/categories is not available until v2.1.0 :return: dictionary of categories

**torrents\_createCategory** (*name=None, save\_path=None, \*\*kwargs*)

Create a new torrent category. (alias: torrents\_createCategory)

Note: save\_path is not available until web API version 2.1.0

**Exceptions:** Conflict409 if category name is not valid or unable to create

**Parameters**

- **name** – name for new category
- **save\_path** – location to save torrents for this category

**Returns** None

**torrents\_createTags** (*tags=None, \*\*kwargs*)

Create one or more tags. (alias: torrents\_createTags)

**Parameters** **tags** – tag name or list of tags

**Returns** None

**torrents\_create\_category** (*name=None, save\_path=None, \*\*kwargs*)

Create a new torrent category. (alias: `torrents_createCategory`)

Note: `save_path` is not available until web API version 2.1.0

**Exceptions:** Conflict409 if category name is not valid or unable to create

**Parameters**

- **name** – name for new category
- **save\_path** – location to save torrents for this category

**Returns** None

**torrents\_create\_tags** (*tags=None, \*\*kwargs*)

Create one or more tags. (alias: `torrents_createTags`)

**Parameters** **tags** – tag name or list of tags

**Returns** None

**torrents\_decreasePrio** (*torrent\_hashes=None, \*\*kwargs*)

Decrease the priority of a torrent. Torrent Queuing must be enabled. (alias: `torrents_decreasePrio`)

**Exceptions:** Conflict409

**Parameters** **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.

**Returns** None

**torrents\_decrease\_priority** (*torrent\_hashes=None, \*\*kwargs*)

Decrease the priority of a torrent. Torrent Queuing must be enabled. (alias: `torrents_decreasePrio`)

**Exceptions:** Conflict409

**Parameters** **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.

**Returns** None

**torrents\_delete** (*delete\_files=None, torrent\_hashes=None, \*\*kwargs*)

Remove a torrent from qBittorrent and optionally delete its files.

**Parameters**

- **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.
- **delete\_files** – True to delete the torrent’s files

**Returns** None

**torrents\_deleteTags** (*tags=None, \*\*kwargs*)

Delete one or more tags. (alias: `torrents_deleteTags`)

**Parameters** **tags** – tag name or list of tags

**Returns** None

**torrents\_delete\_tags** (*tags=None, \*\*kwargs*)

Delete one or more tags. (alias: `torrents_deleteTags`)

**Parameters** **tags** – tag name or list of tags

**Returns** None

**torrents\_downloadLimit** (*torrent\_hashes=None, \*\*kwargs*)

Retrieve the download limit for one or more torrents. (alias: `torrents_downloadLimit`)

**Returns** dictionary {hash: limit} (-1 represents no limit)

**torrents\_download\_limit** (*torrent\_hashes=None, \*\*kwargs*)

Retrieve the download limit for one or more torrents. (alias: `torrents_downloadLimit`)

**Returns** dictionary {hash: limit} (-1 represents no limit)

**torrents\_editCategory** (*name=None, save\_path=None, \*\*kwargs*)

Edit an existing category. (alias: `torrents_editCategory`)

Note: `torrents/editCategory` not available until web API version 2.1.0

**Exceptions:** Conflict409

**Parameters**

- **name** – category to edit
- **save\_path** – new location to save files for this category

**Returns** None

**torrents\_editTracker** (*torrent\_hash=None, original\_url=None, new\_url=None, \*\*kwargs*)

Replace a torrent's tracker with a different one. (alias: `torrents_editTrackers`)

**Exceptions:** InvalidRequest400 NotFound404Error Conflict409Error

**Parameters**

- **torrent\_hash** – hash for torrent
- **original\_url** – URL for existing tracker
- **new\_url** – new URL to replace

**Returns** None

**torrents\_edit\_category** (*name=None, save\_path=None, \*\*kwargs*)

Edit an existing category. (alias: `torrents_editCategory`)

Note: `torrents/editCategory` not available until web API version 2.1.0

**Exceptions:** Conflict409

**Parameters**

- **name** – category to edit
- **save\_path** – new location to save files for this category

**Returns** None

**torrents\_edit\_tracker** (*torrent\_hash=None, original\_url=None, new\_url=None, \*\*kwargs*)

Replace a torrent's tracker with a different one. (alias: `torrents_editTrackers`)

**Exceptions:** InvalidRequest400 NotFound404Error Conflict409Error

**Parameters**

- **torrent\_hash** – hash for torrent

- **original\_url** – URL for existing tracker
- **new\_url** – new URL to replace

**Returns** None

**torrents\_filePrio** (*torrent\_hash=None, file\_ids=None, priority=None, \*\*kwargs*)

Set priority for one or more files. (alias: `torrents_filePrio`)

**Exceptions:** `InvalidRequest400` if priority is invalid or at least one file ID is not an integer `NotFound404Error` `Conflict409` if torrent metadata has not finished downloading or at least one file was not found

**Parameters**

- **torrent\_hash** – hash for torrent
- **file\_ids** – single file ID or a list. See
- **priority** – priority for file(s) Properties: <https://github.com/qbittorrent/qBittorrent/wiki/Web-API-Documentation#set-file-priority>

**Returns**

**torrents\_file\_priority** (*torrent\_hash=None, file\_ids=None, priority=None, \*\*kwargs*)

Set priority for one or more files. (alias: `torrents_filePrio`)

**Exceptions:** `InvalidRequest400` if priority is invalid or at least one file ID is not an integer `NotFound404Error` `Conflict409` if torrent metadata has not finished downloading or at least one file was not found

**Parameters**

- **torrent\_hash** – hash for torrent
- **file\_ids** – single file ID or a list. See
- **priority** – priority for file(s) Properties: <https://github.com/qbittorrent/qBittorrent/wiki/Web-API-Documentation#set-file-priority>

**Returns**

**torrents\_files** (*torrent\_hash=None, \*\*kwargs*)

Retrieve individual torrent's files.

**Exceptions:** `NotFound404Error`

**Parameters** **torrent\_hash** – hash for torrent

**Returns** List of torrent's files Properties: <https://github.com/qbittorrent/qBittorrent/wiki/Web-API-Documentation#get-torrent-contents>

**torrents\_increasePrio** (*torrent\_hashes=None, \*\*kwargs*)

Increase the priority of a torrent. Torrent Queuing must be enabled. (alias: `torrents_increasePrio`)

**Exceptions:** `Conflict409`

**Parameters** **torrent\_hashes** – single torrent hash or list of torrent hashes. Or 'all' for all torrents.

**Returns** None

**torrents\_increase\_priority** (*torrent\_hashes=None, \*\*kwargs*)

Increase the priority of a torrent. Torrent Queuing must be enabled. (alias: `torrents_increasePrio`)

**Exceptions:** Conflict409

**Parameters** **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.

**Returns** None

**torrents\_info** (*status\_filter=None, category=None, sort=None, reverse=None, limit=None, offset=None, torrent\_hashes=None, \*\*kwargs*)

Retrieves list of info for torrents. Note: hashes is available starting web API version 2.0.1

**Parameters**

- **status\_filter** – Filter list by all, downloading, completed, paused, active, inactive, resumed stalled, stalled\_uploading and stalled\_downloading added in Web API v2.4.1
- **category** – Filter list by category
- **sort** – Sort list by any property returned
- **reverse** – Reverse sorting
- **limit** – Limit length of list
- **offset** – Start of list (if < 0, offset from end of list)
- **torrent\_hashes** – Filter list by hash (separate multiple hashes with a ‘|’)

**Returns** List of torrents Properties: <https://github.com/qbittorrent/qBittorrent/wiki/Web-API-Documentation#get-torrent-list>

**torrents\_pause** (*torrent\_hashes=None, \*\*kwargs*)

Pause one or more torrents in qBittorrent.

**Parameters** **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.

**Returns** None

**torrents\_pieceHashes** (*torrent\_hash=None, \*\*kwargs*)

Retrieve individual torrent’s pieces’ hashes. (alias: `torrents_pieceHashes`)

**Exceptions:** NotFound404Error

**Parameters** **torrent\_hash** – hash for torrent

**Returns** List of torrent’s pieces’ hashes

**torrents\_pieceStates** (*torrent\_hash=None, \*\*kwargs*)

Retrieve individual torrent’s pieces’ states. (alias: `torrents_pieceStates`)

**Exceptions:** NotFound404Error

**Parameters** **torrent\_hash** – hash for torrent

**Returns** list of torrent’s pieces’ states

**torrents\_piece\_hashes** (*torrent\_hash=None, \*\*kwargs*)

Retrieve individual torrent’s pieces’ hashes. (alias: `torrents_pieceHashes`)

**Exceptions:** NotFound404Error

**Parameters** `torrent_hash` – hash for torrent

**Returns** List of torrent's pieces' hashes

**torrents\_piece\_states** (*torrent\_hash=None, \*\*kwargs*)

Retrieve individual torrent's pieces' states. (alias: `torrents_pieceStates`)

**Exceptions:** `NotFound404Error`

**Parameters** `torrent_hash` – hash for torrent

**Returns** list of torrent's pieces' states

**torrents\_properties** (*torrent\_hash=None, \*\*kwargs*)

Retrieve individual torrent's properties.

**Exceptions:** `NotFound404Error`

**Parameters** `torrent_hash` – hash for torrent

**Returns** Dictionary of torrent properties Properties: <https://github.com/qbittorrent/qBittorrent/wiki/Web-API-Documentation#get-torrent-generic-properties>

**torrents\_reannounce** (*torrent\_hashes=None, \*\*kwargs*)

Reannounce a torrent.

Note: `torrents/reannounce` not available web API version 2.0.2

**Parameters** `torrent_hashes` – single torrent hash or list of torrent hashes. Or 'all' for all torrents.

**Returns** `None`

**torrents\_recheck** (*torrent\_hashes=None, \*\*kwargs*)

Recheck a torrent in qBittorrent.

**Parameters** `torrent_hashes` – single torrent hash or list of torrent hashes. Or 'all' for all torrents.

**Returns** `None`

**torrents\_removeCategories** (*categories=None, \*\*kwargs*)

Delete one or more categories. (alias: `torrents_removeCategories`)

**Parameters** `categories` – categories to delete

**Returns** `None`

**torrents\_removeTags** (*tags=None, torrent\_hashes=None, \*\*kwargs*)

Add one or more tags to one or more torrents. (alias: `torrents_removeTags`)

**Parameters**

- **tags** – tag name or list of tags
- **torrent\_hashes** – single torrent hash or list of torrent hashes. Or 'all' for all torrents.

**Returns** `None`

**torrents\_removeTrackers** (*torrent\_hash=None, urls=None, \*\*kwargs*)

Remove trackers from a torrent. (alias: `torrents_removeTrackers`)

**Exceptions:** `NotFound404Error` `Conflict409Error`



**Parameters**

- **torrent\_hash** – hash for torrent
- **urls** – tracker urls to removed from torrent

**Returns** None**torrents\_remove\_categories** (*categories=None, \*\*kwargs*)Delete one or more categories. (alias: `torrents_removeCategories`)**Parameters** **categories** – categories to delete**Returns** None**torrents\_remove\_tags** (*tags=None, torrent\_hashes=None, \*\*kwargs*)Add one or more tags to one or more torrents. (alias: `torrents_removeTags`)**Parameters**

- **tags** – tag name or list of tags
- **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.

**Returns** None**torrents\_remove\_trackers** (*torrent\_hash=None, urls=None, \*\*kwargs*)Remove trackers from a torrent. (alias: `torrents_removeTrackers`)**Exceptions:** `NotFound404Error` `Conflict409Error`**Parameters**

- **torrent\_hash** – hash for torrent
- **urls** – tracker urls to removed from torrent

**Returns** None**torrents\_rename** (*torrent\_hash=None, new\_torrent\_name=None, \*\*kwargs*)

Rename a torrent.

**Exceptions:** `NotFound404Error`**Parameters**

- **torrent\_hash** – hash for torrent
- **new\_torrent\_name** – new name for torrent

**Returns** None**torrents\_renameFile** (*torrent\_hash=None, file\_id=None, new\_file\_name=None, \*\*kwargs*)

Rename a torrent file.

**Exceptions:** `MissingRequiredParameters400Error` `NotFound404Error` `Conflict409Error`**Parameters**

- **torrent\_hash** – hash for torrent
- **file\_id** – id for file
- **new\_file\_name** – new name for file

**Returns** None

**torrents\_rename\_file** (*torrent\_hash=None, file\_id=None, new\_file\_name=None, \*\*kwargs*)  
Rename a torrent file.

**Exceptions:** MissingRequiredParameters400Error NotFound404Error Conflict409Error

**Parameters**

- **torrent\_hash** – hash for torrent
- **file\_id** – id for file
- **new\_file\_name** – new name for file

**Returns** None

**torrents\_resume** (*torrent\_hashes=None, \*\*kwargs*)  
Resume one or more torrents in qBittorrent.

**Parameters** **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.

**Returns** None

**torrents\_setAutoManagement** (*enable=None, torrent\_hashes=None, \*\*kwargs*)  
Enable or disable automatic torrent management for one or more torrents. (alias: `torrents_setAutoManagement`)

**Parameters**

- **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.
- **enable** – True or False

**Returns** None

**torrents\_setCategory** (*category=None, torrent\_hashes=None, \*\*kwargs*)  
Set a category for one or more torrents. (alias: `torrents_setCategory`)

**Exceptions:** Conflict409 for bad category

**Parameters**

- **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.
- **category** – category to assign to torrent

**Returns** None

**torrents\_setDownloadLimit** (*limit=None, torrent\_hashes=None, \*\*kwargs*)  
Set the download limit for one or more torrents. (alias: `torrents_setDownloadLimit`)

**Parameters**

- **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.
- **limit** – bytes/second (-1 sets the limit to infinity)

**Returns** None

**torrents\_setForceStart** (*enable=None, torrent\_hashes=None, \*\*kwargs*)  
Force start one or more torrents. (alias: `torrents_setForceStart`)

**Parameters**

- **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.

- **enable** – True or False (False makes this equivalent to `torrents_resume()`)

**Returns** None

**torrents\_setLocation** (*location=None, torrent\_hashes=None, \*\*kwargs*)

Set location for torrents's files. (alias: `torrents_setLocation`)

**Exceptions:** `Forbidden403Error` if the user doesn't have permissions to write to the location `Conflict409` if the directory cannot be created at the location

**Parameters**

- **torrent\_hashes** – single torrent hash or list of torrent hashes. Or 'all' for all torrents.
- **location** – disk location to move torrent's files

**Returns** None

**torrents\_setShareLimits** (*ratio\_limit=None, seeding\_time\_limit=None, torrent\_hashes=None, \*\*kwargs*)

Set share limits for one or more torrents.

**Parameters**

- **torrent\_hashes** – single torrent hash or list of torrent hashes. Or 'all' for all torrents.
- **ratio\_limit** – max ratio to seed a torrent. (-2 means use the global value and -1 is no limit)
- **seeding\_time\_limit** – minutes (-2 means use the global value and -1 is no limit)

**Returns** None

**torrents\_setSuperSeeding** (*enable=None, torrent\_hashes=None, \*\*kwargs*)

Set one or more torrents as super seeding. (alias: `torrents_setSuperSeeding`)

**Parameters**

- **torrent\_hashes** – single torrent hash or list of torrent hashes. Or 'all' for all torrents.
- **enable** – True or False

**Returns**

**torrents\_setUploadLimit** (*limit=None, torrent\_hashes=None, \*\*kwargs*)

Set the upload limit for one or more torrents. (alias: `torrents_setUploadLimit`)

**Parameters**

- **torrent\_hashes** – single torrent hash or list of torrent hashes. Or 'all' for all torrents.
- **limit** – bytes/second (-1 sets the limit to infinity)

**Returns** None

**torrents\_set\_auto\_management** (*enable=None, torrent\_hashes=None, \*\*kwargs*)

Enable or disable automatic torrent management for one or more torrents. (alias: `torrents_setAutoManagement`)

**Parameters**

- **torrent\_hashes** – single torrent hash or list of torrent hashes. Or 'all' for all torrents.
- **enable** – True or False

**Returns** None

**torrents\_set\_category** (*category=None, torrent\_hashes=None, \*\*kwargs*)

Set a category for one or more torrents. (alias: `torrents_setCategory`)

**Exceptions:** Conflict409 for bad category

**Parameters**

- **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.
- **category** – category to assign to torrent

**Returns** None

**torrents\_set\_download\_limit** (*limit=None, torrent\_hashes=None, \*\*kwargs*)

Set the download limit for one or more torrents. (alias: `torrents_setDownloadLimit`)

**Parameters**

- **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.
- **limit** – bytes/second (-1 sets the limit to infinity)

**Returns** None

**torrents\_set\_force\_start** (*enable=None, torrent\_hashes=None, \*\*kwargs*)

Force start one or more torrents. (alias: `torrents_setForceStart`)

**Parameters**

- **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.
- **enable** – True or False (False makes this equivalent to `torrents_resume()`)

**Returns** None

**torrents\_set\_location** (*location=None, torrent\_hashes=None, \*\*kwargs*)

Set location for torrents’s files. (alias: `torrents_setLocation`)

**Exceptions:** Forbidden403Error if the user doesn’t have permissions to write to the location Conflict409 if the directory cannot be created at the location

**Parameters**

- **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.
- **location** – disk location to move torrent’s files

**Returns** None

**torrents\_set\_share\_limits** (*ratio\_limit=None, seeding\_time\_limit=None, torrent\_hashes=None, \*\*kwargs*)

Set share limits for one or more torrents.

**Parameters**

- **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.
- **ratio\_limit** – max ratio to seed a torrent. (-2 means use the global value and -1 is no limit)
- **seeding\_time\_limit** – minutes (-2 means use the global value and -1 is no limit)

**Returns** None

**torrents\_set\_super\_seeding** (*enable=None, torrent\_hashes=None, \*\*kwargs*)

Set one or more torrents as super seeding. (alias: `torrents_setSuperSeeding`)

**Parameters**

- **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.
- **enable** – True or False

**Returns**

**torrents\_set\_upload\_limit** (*limit=None, torrent\_hashes=None, \*\*kwargs*)

Set the upload limit for one or more torrents. (alias: `torrents_setUploadLimit`)

**Parameters**

- **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.
- **limit** – bytes/second (-1 sets the limit to infinity)

**Returns** None

**torrents\_tags** (*\*\*kwargs*)

Retrieve all tag definitions.

**Returns** list of tags

**torrents\_toggleFirstLastPiecePrio** (*torrent\_hashes=None, \*\*kwargs*)

Toggle priority of first/last piece downloading. (alias: `torrents_toggleFirstLastPiecePrio`)

**Parameters** **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.

**Returns** None

**torrents\_toggleSequentialDownload** (*torrent\_hashes=None, \*\*kwargs*)

Toggle sequential download for one or more torrents. (alias: `torrents_toggleSequentialDownload`)

**Parameters** **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.

**Returns** None

**torrents\_toggle\_first\_last\_piece\_priority** (*torrent\_hashes=None, \*\*kwargs*)

Toggle priority of first/last piece downloading. (alias: `torrents_toggleFirstLastPiecePrio`)

**Parameters** **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.

**Returns** None

**torrents\_toggle\_sequential\_download** (*torrent\_hashes=None, \*\*kwargs*)

Toggle sequential download for one or more torrents. (alias: `torrents_toggleSequentialDownload`)

**Parameters** **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.

**Returns** None

**torrents\_topPrio** (*torrent\_hashes=None, \*\*kwargs*)

Set torrent as highest priority. Torrent Queuing must be enabled. (alias: `torrents_topPrio`)

**Exceptions:** Conflict409

**Parameters** **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.

**Returns** None

**torrents\_top\_priority** (*torrent\_hashes=None, \*\*kwargs*)

Set torrent as highest priority. Torrent Queuing must be enabled. (alias: `torrents_topPrio`)

**Exceptions:** Conflict409

**Parameters** **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.

**Returns** None

**torrents\_trackers** (*torrent\_hash=None, \*\*kwargs*)

Retrieve individual torrent’s trackers.

**Exceptions:** NotFound404Error

**Parameters** **torrent\_hash** – hash for torrent

**Returns** List of torrent’s trackers Properties: <https://github.com/qbittorrent/qBittorrent/wiki/Web-API-Documentation#get-torrent-trackers>

**torrents\_uploadLimit** (*torrent\_hashes=None, \*\*kwargs*)

Retrieve the upload limit for one or more torrents. (alias: `torrents_uploadLimit`)

**Parameters** **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.

**Returns** dictionary of limits

**torrents\_upload\_limit** (*torrent\_hashes=None, \*\*kwargs*)

Retrieve the upload limit for one or more torrents. (alias: `torrents_uploadLimit`)

**Parameters** **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.

**Returns** dictionary of limits

**torrents\_webseeds** (*torrent\_hash=None, \*\*kwargs*)

Retrieve individual torrent’s web seeds.

**Exceptions:** NotFound404Error

**Parameters** **torrent\_hash** – hash for torrent

**Returns** List of torrent’s web seeds Properties: <https://github.com/qbittorrent/qBittorrent/wiki/Web-API-Documentation#get-torrent-web-seeds>

**class** qbittorrentapi.**Torrents** (*client*)

Allows interaction with the “Torrents” API endpoints.

**Usage:**

```
>>> from qbittorrentapi import Client
>>> client = Client(host='localhost:8080', username='admin', password=
↳ 'adminadmin')
>>> # this are all the same attributes that are available as named in the
>>> # endpoints or the more pythonic names in Client (with or without
↳ 'torrents_' prepended)
>>> torrent_list = client.torrents.info()
>>> torrent_list_active = client.torrents.info.active()
>>> torrent_list_active_partial = client.torrents.info.active(limit=100,
↳ offset=200)
```

(continues on next page)

(continued from previous page)

```

>>> torrent_list_downloading = client.torrents.info.downloading()
>>> # torrent looping
>>> for torrent in client.torrents.info.completed()
>>> # all torrents endpoints with a 'hashes' parameters support all method to
    ↪ apply action to all torrents
>>> client.torrents.pause.all()
>>> client.torrents.resume.all()
>>> # or specify the individual hashes
>>> client.torrents.downloadLimit(torrent_hashes=['...', '...'])

```

**add** (urls=None, torrent\_files=None, save\_path=None, cookie=None, category=None, is\_skip\_checking=None, is\_paused=None, is\_root\_folder=None, rename=None, upload\_limit=None, download\_limit=None, use\_auto\_torrent\_management=None, is\_sequential\_download=None, is\_first\_last\_piece\_priority=None, \*\*kwargs)

**class** qbittorrentapi.TorrentDictionary (data, client)

Allows interaction with individual torrents via the “Torrents” API endpoints.

**Usage:**

```

>>> from qbittorrentapi import Client
>>> client = Client(host='localhost:8080', username='admin', password=
    ↪ 'adminadmin')
>>> # this are all the same attributes that are available as named in the
>>> # endpoints or the more pythonic names in Client (with or without
    ↪ 'transfer_' prepended)
>>> torrent = client.torrents.info()[0]
>>> hash = torrent.info.hash
>>> # Attributes without inputs and a return value are properties
>>> properties = torrent.properties
>>> trackers = torrent.trackers
>>> files = torrent.files
>>> # Action methods
>>> torrent.edit_tracker(original_url="...", new_url="...")
>>> torrent.remove_trackers(urls='http://127.0.0.2/')
>>> torrent.rename(new_torrent_name="...")
>>> torrent.resume()
>>> torrent.pause()
>>> torrent.recheck()
>>> torrent.torrents_top_priority()
>>> torrent.setLocation(location='/home/user/torrents/')
>>> torrent.setCategory(category='video')

```

**addTags** (tags=None, \*\*kwargs)

**addTrackers** (urls=None, \*\*kwargs)

**add\_tags** (tags=None, \*\*kwargs)

**add\_trackers** (urls=None, \*\*kwargs)

**bottomPrio** (\*\*kwargs)

**bottom\_priority** (\*\*kwargs)

**decreasePrio** (\*\*kwargs)

**decrease\_priority** (\*\*kwargs)

**delete** (delete\_files=None, \*\*kwargs)

**downloadLimit**  
**download\_limit**  
**editTracker** (*orig\_url=None, new\_url=None, \*\*kwargs*)  
**edit\_tracker** (*orig\_url=None, new\_url=None, \*\*kwargs*)  
**filePriority** (*file\_ids=None, priority=None, \*\*kwargs*)  
**file\_priority** (*file\_ids=None, priority=None, \*\*kwargs*)  
**files**  
**increasePrio** (*\*\*kwargs*)  
**increase\_priority** (*\*\*kwargs*)  
**info**  
**pause** (*\*\*kwargs*)  
**pieceHashes**  
**pieceStates**  
**piece\_hashes**  
**piece\_states**  
**properties**  
**reannounce** (*\*\*kwargs*)  
**recheck** (*\*\*kwargs*)  
**removeTags** (*tags=None, \*\*kwargs*)  
**removeTrackers** (*urls=None, \*\*kwargs*)  
**remove\_tags** (*tags=None, \*\*kwargs*)  
**remove\_trackers** (*urls=None, \*\*kwargs*)  
**rename** (*new\_name=None, \*\*kwargs*)  
**renameFile** (*file\_id=None, new\_file\_name=None, \*\*kwargs*)  
**rename\_file** (*file\_id=None, new\_file\_name=None, \*\*kwargs*)  
**resume** (*\*\*kwargs*)  
**setAutoManagement** (*enable=None, \*\*kwargs*)  
**setCategory** (*category=None, \*\*kwargs*)  
**setDownloadLimit** (*limit=None, \*\*kwargs*)  
**setForceStart** (*enable=None, \*\*kwargs*)  
**setLocation** (*location=None, \*\*kwargs*)  
**setShareLimits** (*ratio\_limit=None, seeding\_time\_limit=None, \*\*kwargs*)  
**setSuperSeeding** (*enable=None, \*\*kwargs*)  
**setUploadLimit** (*limit=None, \*\*kwargs*)  
**set\_auto\_management** (*enable=None, \*\*kwargs*)  
**set\_category** (*category=None, \*\*kwargs*)



```

set_download_limit (limit=None, **kwargs)
set_force_start (enable=None, **kwargs)
set_location (location=None, **kwargs)
set_share_limits (ratio_limit=None, seeding_time_limit=None, **kwargs)
set_super_seeding (enable=None, **kwargs)
set_upload_limit (limit=None, **kwargs)
sync_local ()
    Update local cache of torrent info.
toggleFirstLastPiecePrio (**kwargs)
toggleSequentialDownload (**kwargs)
toggle_first_last_piece_priority (**kwargs)
toggle_sequential_download (**kwargs)
topPrio (**kwargs)
top_priority (**kwargs)
trackers
uploadLimit
upload_limit
webseeds

```

## Transfer

```

class qbittorrentapi.TransferAPIMixin (host="", port=None, username=None, pass-
                                         word=None, **kwargs)

```

Implementation of all Transfer API methods

```

transfer_banPeers (peers=None, **kwargs)

```

Ban one or more peers. (alias: `transfer_banPeers`)

**Parameters** **peers** – one or more peers to ban. each peer should take the form ‘host:port’

**Returns** None

```

transfer_ban_peers (peers=None, **kwargs)

```

Ban one or more peers. (alias: `transfer_banPeers`)

**Parameters** **peers** – one or more peers to ban. each peer should take the form ‘host:port’

**Returns** None

```

transfer_downloadLimit (**kwargs)

```

Retrieves download limit. 0 is unlimited. (alias: `transfer_downloadLimit`)

**Returns** integer

```

transfer_download_limit (**kwargs)

```

Retrieves download limit. 0 is unlimited. (alias: `transfer_downloadLimit`)

**Returns** integer

```

transfer_info (**kwargs)

```

Retrieves the global transfer info usually found in qBittorrent status bar.

**Returns** dictionary of status items Properties: <https://github.com/qbittorrent/qBittorrent/wiki/Web-API-Documentation#get-global-transfer-info>

**transfer\_setDownloadLimit** (*limit=None, \*\*kwargs*)

Set the global download limit in bytes/second. (alias: transfer\_setDownloadLimit)

**Parameters** **limit** – download limit in bytes/second (0 or -1 for no limit)

**Returns** None

**transfer\_setUploadLimit** (*limit=None, \*\*kwargs*)

Set the global download limit in bytes/second. (alias: transfer\_setUploadLimit)

**Parameters** **limit** – upload limit in bytes/second (0 or -1 for no limit)

**Returns** None

**transfer\_set\_download\_limit** (*limit=None, \*\*kwargs*)

Set the global download limit in bytes/second. (alias: transfer\_setDownloadLimit)

**Parameters** **limit** – download limit in bytes/second (0 or -1 for no limit)

**Returns** None

**transfer\_set\_upload\_limit** (*limit=None, \*\*kwargs*)

Set the global download limit in bytes/second. (alias: transfer\_setUploadLimit)

**Parameters** **limit** – upload limit in bytes/second (0 or -1 for no limit)

**Returns** None

**transfer\_speedLimitsMode** (*\*\*kwargs*)

Retrieves whether alternative speed limits are enabled. (alias: transfer\_speedLimitMode)

**Returns** '1' if alternative speed limits are currently enabled, '0' otherwise

**transfer\_speed\_limits\_mode** (*\*\*kwargs*)

Retrieves whether alternative speed limits are enabled. (alias: transfer\_speedLimitMode)

**Returns** '1' if alternative speed limits are currently enabled, '0' otherwise

**transfer\_toggleSpeedLimitsMode** (*intended\_state=None, \*\*kwargs*)

Sets whether alternative speed limits are enabled. (alias: transfer\_toggleSpeedLimitsMode)

**Parameters** **intended\_state** – True to enable alt speed and False to disable. Leaving None will toggle the current state.

**Returns** None

**transfer\_toggle\_speed\_limits\_mode** (*intended\_state=None, \*\*kwargs*)

Sets whether alternative speed limits are enabled. (alias: transfer\_toggleSpeedLimitsMode)

**Parameters** **intended\_state** – True to enable alt speed and False to disable. Leaving None will toggle the current state.

**Returns** None

**transfer\_uploadLimit** (*\*\*kwargs*)

Retrieves upload limit. 0 is unlimited. (alias: transfer\_uploadLimit)

**Returns** integer

**transfer\_upload\_limit** (*\*\*kwargs*)

Retrieves upload limit. 0 is unlimited. (alias: transfer\_uploadLimit)

**Returns** integer

**class** qbittorrentapi.**Transfer**(\*args, \*\*kwargs)

Allows interaction with the “Transfer” API endpoints.

Usage:

```
>>> from qbittorrentapi import Client
>>> client = Client(host='localhost:8080', username='admin', password=
↳ 'adminadmin')
>>> # this are all the same attributes that are available as named in the
>>> # endpoints or the more pythonic names in Client (with or without
↳ 'transfer_' prepended)
>>> transfer_info = client.transfer.info
>>> # access and set download/upload limits as attributes
>>> dl_limit = client.transfer.download_limit
>>> # this updates qBittorrent in real-time
>>> client.transfer.download_limit = 1024000
>>> # update speed limits mode to alternate or not
>>> client.transfer.speedLimitsMode = True
```

**banPeers** (peers=None, \*\*kwargs)

**ban\_peers** (peers=None, \*\*kwargs)

**downloadLimit**

**download\_limit**

**info**

**setDownloadLimit** (limit=None, \*\*kwargs)

**setUploadLimit** (limit=None, \*\*kwargs)

**set\_download\_limit** (limit=None, \*\*kwargs)

**set\_upload\_limit** (limit=None, \*\*kwargs)

**speedLimitsMode**

**speed\_limits\_mode**

**toggleSpeedLimitsMode** (intended\_state=None, \*\*kwargs)

**toggle\_speed\_limits\_mode** (intended\_state=None, \*\*kwargs)

**uploadLimit**

**upload\_limit**



### q

`qbittorrentapi`, [37](#)

`qbittorrentapi.exceptions`, [7](#)



## A

add() (*qbittorrentapi.Torrents method*), 35  
 add\_feed() (*qbittorrentapi.RSS method*), 16  
 add\_folder() (*qbittorrentapi.RSS method*), 16  
 add\_tags() (*qbittorrentapi.TorrentDictionary method*), 35  
 add\_trackers() (*qbittorrentapi.TorrentDictionary method*), 35  
 addFeed() (*qbittorrentapi.RSS method*), 16  
 addFolder() (*qbittorrentapi.RSS method*), 16  
 addTags() (*qbittorrentapi.TorrentDictionary method*), 35  
 addTrackers() (*qbittorrentapi.TorrentDictionary method*), 35  
 APIConnectionError, 7  
 APIError, 7  
 app\_build\_info() (*qbittorrentapi.AppAPIMixin method*), 9  
 app\_buildInfo() (*qbittorrentapi.AppAPIMixin method*), 9  
 app\_default\_save\_path() (*qbittorrentapi.AppAPIMixin method*), 9  
 app\_defaultSavePath() (*qbittorrentapi.AppAPIMixin method*), 9  
 app\_preferences() (*qbittorrentapi.AppAPIMixin method*), 9  
 app\_set\_preferences() (*qbittorrentapi.AppAPIMixin method*), 9  
 app\_setPreferences() (*qbittorrentapi.AppAPIMixin method*), 9  
 app\_shutdown() (*qbittorrentapi.AppAPIMixin method*), 9  
 app\_version() (*qbittorrentapi.AppAPIMixin method*), 9  
 app\_web\_api\_version() (*qbittorrentapi.AppAPIMixin method*), 9  
 app\_webapiVersion() (*qbittorrentapi.AppAPIMixin method*), 10  
 AppAPIMixin (class in *qbittorrentapi*), 9

Application (class in *qbittorrentapi*), 10  
 application (*qbittorrentapi.AppAPIMixin attribute*), 10  
 auth\_log\_in() (*qbittorrentapi.Request method*), 11  
 auth\_log\_out() (*qbittorrentapi.Request method*), 11

## B

ban\_peers() (*qbittorrentapi.Transfer method*), 39  
 banPeers() (*qbittorrentapi.Transfer method*), 39  
 bottom\_priority() (*qbittorrentapi.TorrentDictionary method*), 35  
 bottomPrio() (*qbittorrentapi.TorrentDictionary method*), 35  
 build\_info (*qbittorrentapi.Application attribute*), 10  
 buildInfo (*qbittorrentapi.Application attribute*), 10

## C

categories() (*qbittorrentapi.Search method*), 19  
 Client (class in *qbittorrentapi*), 11  
 Conflict409Error, 8

## D

decrease\_priority() (*qbittorrentapi.TorrentDictionary method*), 35  
 decreasePrio() (*qbittorrentapi.TorrentDictionary method*), 35  
 default\_save\_path (*qbittorrentapi.Application attribute*), 10  
 defaultSavePath (*qbittorrentapi.Application attribute*), 10  
 delete() (*qbittorrentapi.Search method*), 19  
 delete() (*qbittorrentapi.TorrentDictionary method*), 35  
 download\_limit (*qbittorrentapi.TorrentDictionary attribute*), 36  
 download\_limit (*qbittorrentapi.Transfer attribute*), 39  
 downloadLimit (*qbittorrentapi.TorrentDictionary attribute*), 35

downloadLimit (*qbittorrentapi.Transfer attribute*), 39

## E

edit\_tracker() (*qbittorrentapi.TorrentDictionary method*), 36

editTracker() (*qbittorrentapi.TorrentDictionary method*), 36

enable\_plugin() (*qbittorrentapi.Search method*), 19

enablePlugin() (*qbittorrentapi.Search method*), 19

## F

file\_priority() (*qbittorrentapi.TorrentDictionary method*), 36

FileError, 7

filePriority() (*qbittorrentapi.TorrentDictionary method*), 36

files (*qbittorrentapi.TorrentDictionary attribute*), 36

Forbidden403Error, 8

## H

HTTP400Error, 7

HTTP401Error, 7

HTTP403Error, 8

HTTP404Error, 8

HTTP409Error, 8

HTTP415Error, 8

HTTP4XXError, 7

HTTP500Error, 8

HTTP5XXError, 7

HTTPError, 7

## I

increase\_priority() (*qbittorrentapi.TorrentDictionary method*), 36

increasePrio() (*qbittorrentapi.TorrentDictionary method*), 36

info (*qbittorrentapi.TorrentDictionary attribute*), 36

info (*qbittorrentapi.Transfer attribute*), 39

install\_plugin() (*qbittorrentapi.Search method*), 19

installPlugin() (*qbittorrentapi.Search method*), 19

InternalServerError500Error, 8

InvalidRequest400Error, 8

## L

Log (*class in qbittorrentapi*), 12

log\_main() (*qbittorrentapi.LogAPIMixin method*), 12

log\_peers() (*qbittorrentapi.LogAPIMixin method*), 12

LogAPIMixin (*class in qbittorrentapi*), 12

LoginFailed, 7

## M

mark\_as\_read() (*qbittorrentapi.RSS method*), 16

markAsRead() (*qbittorrentapi.RSS method*), 16

matching\_articles() (*qbittorrentapi.RSS method*), 16

matchingArticles() (*qbittorrentapi.RSS method*), 16

MissingRequiredParameters400Error, 8

move\_item() (*qbittorrentapi.RSS method*), 16

moveItem() (*qbittorrentapi.RSS method*), 16

## N

NotFound404Error, 8

## P

pause() (*qbittorrentapi.TorrentDictionary method*), 36

peers() (*qbittorrentapi.Log method*), 12

piece\_hashes (*qbittorrentapi.TorrentDictionary attribute*), 36

piece\_states (*qbittorrentapi.TorrentDictionary attribute*), 36

pieceHashes (*qbittorrentapi.TorrentDictionary attribute*), 36

pieceStates (*qbittorrentapi.TorrentDictionary attribute*), 36

plugins (*qbittorrentapi.Search attribute*), 19

preferences (*qbittorrentapi.Application attribute*), 10

properties (*qbittorrentapi.TorrentDictionary attribute*), 36

## Q

qbittorrentapi (*module*), 9, 11, 12, 17, 20, 21, 37

qbittorrentapi.exceptions (*module*), 7

## R

reannounce() (*qbittorrentapi.TorrentDictionary method*), 36

recheck() (*qbittorrentapi.TorrentDictionary method*), 36

refresh\_item() (*qbittorrentapi.RSS method*), 16

refreshItem() (*qbittorrentapi.RSS method*), 16

remove\_item() (*qbittorrentapi.RSS method*), 17

remove\_rule() (*qbittorrentapi.RSS method*), 17

remove\_tags() (*qbittorrentapi.TorrentDictionary method*), 36

remove\_trackers() (*qbittorrentapi.TorrentDictionary method*), 36

removeItem() (*qbittorrentapi.RSS method*), 16

removeRule() (*qbittorrentapi.RSS method*), 16

removeTags() (*qbittorrentapi.TorrentDictionary method*), 36

removeTrackers() (*qbittorrentapi.TorrentDictionary method*), 36



[rename\(\)](#) (*qbittorrentapi.TorrentDictionary* method), [36](#)  
[rename\\_file\(\)](#) (*qbittorrentapi.TorrentDictionary* method), [36](#)  
[rename\\_rule\(\)](#) (*qbittorrentapi.RSS* method), [17](#)  
[renameFile\(\)](#) (*qbittorrentapi.TorrentDictionary* method), [36](#)  
[renameRule\(\)](#) (*qbittorrentapi.RSS* method), [17](#)  
[Request](#) (class in *qbittorrentapi*), [11](#)  
[results\(\)](#) (*qbittorrentapi.Search* method), [19](#)  
[resume\(\)](#) (*qbittorrentapi.TorrentDictionary* method), [36](#)  
[RSS](#) (class in *qbittorrentapi*), [16](#)  
[rss\\_add\\_feed\(\)](#) (*qbittorrentapi.RSSAPIMixin* method), [13](#)  
[rss\\_add\\_folder\(\)](#) (*qbittorrentapi.RSSAPIMixin* method), [13](#)  
[rss\\_addFeed\(\)](#) (*qbittorrentapi.RSSAPIMixin* method), [12](#)  
[rss\\_addFolder\(\)](#) (*qbittorrentapi.RSSAPIMixin* method), [13](#)  
[rss\\_items\(\)](#) (*qbittorrentapi.RSSAPIMixin* method), [13](#)  
[rss\\_mark\\_as\\_read\(\)](#) (*qbittorrentapi.RSSAPIMixin* method), [13](#)  
[rss\\_markAsRead\(\)](#) (*qbittorrentapi.RSSAPIMixin* method), [13](#)  
[rss\\_matching\\_articles\(\)](#) (*qbittorrentapi.RSSAPIMixin* method), [14](#)  
[rss\\_matchingArticles\(\)](#) (*qbittorrentapi.RSSAPIMixin* method), [14](#)  
[rss\\_move\\_item\(\)](#) (*qbittorrentapi.RSSAPIMixin* method), [14](#)  
[rss\\_moveItem\(\)](#) (*qbittorrentapi.RSSAPIMixin* method), [14](#)  
[rss\\_refresh\\_item\(\)](#) (*qbittorrentapi.RSSAPIMixin* method), [14](#)  
[rss\\_refreshItem\(\)](#) (*qbittorrentapi.RSSAPIMixin* method), [14](#)  
[rss\\_remove\\_item\(\)](#) (*qbittorrentapi.RSSAPIMixin* method), [15](#)  
[rss\\_remove\\_rule\(\)](#) (*qbittorrentapi.RSSAPIMixin* method), [15](#)  
[rss\\_removeItem\(\)](#) (*qbittorrentapi.RSSAPIMixin* method), [14](#)  
[rss\\_removeRule\(\)](#) (*qbittorrentapi.RSSAPIMixin* method), [15](#)  
[rss\\_rename\\_rule\(\)](#) (*qbittorrentapi.RSSAPIMixin* method), [15](#)  
[rss\\_renameRule\(\)](#) (*qbittorrentapi.RSSAPIMixin* method), [15](#)  
[rss\\_rules\(\)](#) (*qbittorrentapi.RSSAPIMixin* method), [15](#)  
[rss\\_set\\_rule\(\)](#) (*qbittorrentapi.RSSAPIMixin* method), [16](#)  
[rss\\_setRule\(\)](#) (*qbittorrentapi.RSSAPIMixin* method), [15](#)  
[RSSAPIMixin](#) (class in *qbittorrentapi*), [12](#)  
[rules](#) (*qbittorrentapi.RSS* attribute), [17](#)

## S

[Search](#) (class in *qbittorrentapi*), [19](#)  
[search\\_categories\(\)](#) (*qbittorrentapi.SearchAPIMixin* method), [17](#)  
[search\\_delete\(\)](#) (*qbittorrentapi.SearchAPIMixin* method), [17](#)  
[search\\_enable\\_plugin\(\)](#) (*qbittorrentapi.SearchAPIMixin* method), [17](#)  
[search\\_enablePlugin\(\)](#) (*qbittorrentapi.SearchAPIMixin* method), [17](#)  
[search\\_install\\_plugin\(\)](#) (*qbittorrentapi.SearchAPIMixin* method), [17](#)  
[search\\_installPlugin\(\)](#) (*qbittorrentapi.SearchAPIMixin* method), [17](#)  
[search\\_plugins\(\)](#) (*qbittorrentapi.SearchAPIMixin* method), [18](#)  
[search\\_results\(\)](#) (*qbittorrentapi.SearchAPIMixin* method), [18](#)  
[search\\_start\(\)](#) (*qbittorrentapi.SearchAPIMixin* method), [18](#)  
[search\\_status\(\)](#) (*qbittorrentapi.SearchAPIMixin* method), [18](#)  
[search\\_stop\(\)](#) (*qbittorrentapi.SearchAPIMixin* method), [18](#)  
[search\\_uninstall\\_plugin\(\)](#) (*qbittorrentapi.SearchAPIMixin* method), [19](#)  
[search\\_uninstallPlugin\(\)](#) (*qbittorrentapi.SearchAPIMixin* method), [18](#)  
[search\\_update\\_plugins\(\)](#) (*qbittorrentapi.SearchAPIMixin* method), [19](#)  
[search\\_updatePlugins\(\)](#) (*qbittorrentapi.SearchAPIMixin* method), [19](#)  
[SearchAPIMixin](#) (class in *qbittorrentapi*), [17](#)  
[set\\_auto\\_management\(\)](#) (*qbittorrentapi.TorrentDictionary* method), [36](#)  
[set\\_category\(\)](#) (*qbittorrentapi.TorrentDictionary* method), [36](#)  
[set\\_download\\_limit\(\)](#) (*qbittorrentapi.TorrentDictionary* method), [36](#)  
[set\\_download\\_limit\(\)](#) (*qbittorrentapi.Transfer* method), [39](#)  
[set\\_force\\_start\(\)](#) (*qbittorrentapi.TorrentDictionary* method), [37](#)  
[set\\_location\(\)](#) (*qbittorrentapi.TorrentDictionary* method), [37](#)  
[set\\_preferences\(\)](#) (*qbittorrentapi.Application* method), [10](#)  
[set\\_rule\(\)](#) (*qbittorrentapi.RSS* method), [17](#)

set\_share\_limits() (*qbittorrentapi.TorrentDictionary method*), 37  
 set\_super\_seeding() (*qbittorrentapi.TorrentDictionary method*), 37  
 set\_upload\_limit() (*qbittorrentapi.TorrentDictionary method*), 37  
 set\_upload\_limit() (*qbittorrentapi.Transfer method*), 39  
 setAutoManagement() (*qbittorrentapi.TorrentDictionary method*), 36  
 setCategory() (*qbittorrentapi.TorrentDictionary method*), 36  
 setDownloadLimit() (*qbittorrentapi.TorrentDictionary method*), 36  
 setDownloadLimit() (*qbittorrentapi.Transfer method*), 39  
 setForceStart() (*qbittorrentapi.TorrentDictionary method*), 36  
 setLocation() (*qbittorrentapi.TorrentDictionary method*), 36  
 setPreferences() (*qbittorrentapi.Application method*), 10  
 setRule() (*qbittorrentapi.RSS method*), 17  
 setShareLimits() (*qbittorrentapi.TorrentDictionary method*), 36  
 setSuperSeeding() (*qbittorrentapi.TorrentDictionary method*), 36  
 setUploadLimit() (*qbittorrentapi.TorrentDictionary method*), 36  
 setUploadLimit() (*qbittorrentapi.Transfer method*), 39  
 shutdown() (*qbittorrentapi.Application method*), 10  
 speed\_limits\_mode (*qbittorrentapi.Transfer attribute*), 39  
 speedLimitsMode (*qbittorrentapi.Transfer attribute*), 39  
 start() (*qbittorrentapi.Search method*), 19  
 status() (*qbittorrentapi.Search method*), 19  
 stop() (*qbittorrentapi.Search method*), 20  
 Sync (*class in qbittorrentapi*), 20  
 sync\_local() (*qbittorrentapi.TorrentDictionary method*), 37  
 sync\_maindata() (*qbittorrentapi.SyncAPIMixin method*), 20  
 sync\_torrent\_peers() (*qbittorrentapi.SyncAPIMixin method*), 20  
 sync\_torrentPeers() (*qbittorrentapi.SyncAPIMixin method*), 20  
 SyncAPIMixin (*class in qbittorrentapi*), 20

**T**

toggle\_first\_last\_piece\_priority() (*qbittorrentapi.TorrentDictionary method*), 37  
 toggle\_sequential\_download() (*qbittorrentapi.TorrentDictionary method*), 37  
 toggle\_speed\_limits\_mode() (*qbittorrentapi.Transfer method*), 39  
 toggleFirstLastPiecePrio() (*qbittorrentapi.TorrentDictionary method*), 37  
 toggleSequentialDownload() (*qbittorrentapi.TorrentDictionary method*), 37  
 toggleSpeedLimitsMode() (*qbittorrentapi.Transfer method*), 39  
 top\_priority() (*qbittorrentapi.TorrentDictionary method*), 37  
 topPrio() (*qbittorrentapi.TorrentDictionary method*), 37  
 torrent\_categories (*qbittorrentapi.TorrentsAPIMixin attribute*), 21  
 torrent\_tags (*qbittorrentapi.TorrentsAPIMixin attribute*), 21  
 TorrentDictionary (*class in qbittorrentapi*), 35  
 TorrentFileError, 7  
 TorrentFileNotFoundError, 7  
 TorrentFilePermissionError, 7  
 Torrents (*class in qbittorrentapi*), 34  
 torrents\_add() (*qbittorrentapi.TorrentsAPIMixin method*), 21  
 torrents\_add\_peers() (*qbittorrentapi.TorrentsAPIMixin method*), 22  
 torrents\_add\_tags() (*qbittorrentapi.TorrentsAPIMixin method*), 22  
 torrents\_add\_trackers() (*qbittorrentapi.TorrentsAPIMixin method*), 23  
 torrents\_addPeers() (*qbittorrentapi.TorrentsAPIMixin method*), 22  
 torrents\_addTags() (*qbittorrentapi.TorrentsAPIMixin method*), 22  
 torrents\_addTrackers() (*qbittorrentapi.TorrentsAPIMixin method*), 22  
 torrents\_bottom\_priority() (*qbittorrentapi.TorrentsAPIMixin method*), 23  
 torrents\_bottomPrio() (*qbittorrentapi.TorrentsAPIMixin method*), 23  
 torrents\_categories() (*qbittorrentapi.TorrentsAPIMixin method*), 23  
 torrents\_create\_category() (*qbittorrentapi.TorrentsAPIMixin method*), 23  
 torrents\_create\_tags() (*qbittorrentapi.TorrentsAPIMixin method*), 24  
 torrents\_createCategory() (*qbittorrentapi.TorrentsAPIMixin method*), 23  
 torrents\_createTags() (*qbittorrentapi.TorrentsAPIMixin method*), 23  
 torrents\_decrease\_priority() (*qbittorrentapi.TorrentsAPIMixin method*), 24  
 torrents\_decreasePrio() (*qbittorrentapi.TorrentsAPIMixin method*), 24

<i>rentapi.TorrentsAPIMixin method</i> ), 24	<i>rentapi.TorrentsAPIMixin method</i> ), 28
<i>torrents_delete()</i> ( <i>qbittorrentapi.TorrentsAPIMixin method</i> ), 24	<i>torrents_removeTags()</i> ( <i>qbittorrentapi.TorrentsAPIMixin method</i> ), 28
<i>torrents_delete_tags()</i> ( <i>qbittorrentapi.TorrentsAPIMixin method</i> ), 24	<i>torrents_removeTrackers()</i> ( <i>qbittorrentapi.TorrentsAPIMixin method</i> ), 28
<i>torrents_deleteTags()</i> ( <i>qbittorrentapi.TorrentsAPIMixin method</i> ), 24	<i>torrents_rename()</i> ( <i>qbittorrentapi.TorrentsAPIMixin method</i> ), 29
<i>torrents_download_limit()</i> ( <i>qbittorrentapi.TorrentsAPIMixin method</i> ), 25	<i>torrents_rename_file()</i> ( <i>qbittorrentapi.TorrentsAPIMixin method</i> ), 30
<i>torrents_downloadLimit()</i> ( <i>qbittorrentapi.TorrentsAPIMixin method</i> ), 25	<i>torrents_renameFile()</i> ( <i>qbittorrentapi.TorrentsAPIMixin method</i> ), 29
<i>torrents_edit_category()</i> ( <i>qbittorrentapi.TorrentsAPIMixin method</i> ), 25	<i>torrents_resume()</i> ( <i>qbittorrentapi.TorrentsAPIMixin method</i> ), 30
<i>torrents_edit_tracker()</i> ( <i>qbittorrentapi.TorrentsAPIMixin method</i> ), 25	<i>torrents_set_auto_management()</i> ( <i>qbittorrentapi.TorrentsAPIMixin method</i> ), 31
<i>torrents_editCategory()</i> ( <i>qbittorrentapi.TorrentsAPIMixin method</i> ), 25	<i>torrents_set_category()</i> ( <i>qbittorrentapi.TorrentsAPIMixin method</i> ), 31
<i>torrents_editTracker()</i> ( <i>qbittorrentapi.TorrentsAPIMixin method</i> ), 25	<i>torrents_set_download_limit()</i> ( <i>qbittorrentapi.TorrentsAPIMixin method</i> ), 32
<i>torrents_file_priority()</i> ( <i>qbittorrentapi.TorrentsAPIMixin method</i> ), 26	<i>torrents_set_force_start()</i> ( <i>qbittorrentapi.TorrentsAPIMixin method</i> ), 32
<i>torrents_filePrio()</i> ( <i>qbittorrentapi.TorrentsAPIMixin method</i> ), 26	<i>torrents_set_location()</i> ( <i>qbittorrentapi.TorrentsAPIMixin method</i> ), 32
<i>torrents_files()</i> ( <i>qbittorrentapi.TorrentsAPIMixin method</i> ), 26	<i>torrents_set_share_limits()</i> ( <i>qbittorrentapi.TorrentsAPIMixin method</i> ), 32
<i>torrents_increase_priority()</i> ( <i>qbittorrentapi.TorrentsAPIMixin method</i> ), 26	<i>torrents_set_super_seeding()</i> ( <i>qbittorrentapi.TorrentsAPIMixin method</i> ), 32
<i>torrents_increasePrio()</i> ( <i>qbittorrentapi.TorrentsAPIMixin method</i> ), 26	<i>torrents_set_upload_limit()</i> ( <i>qbittorrentapi.TorrentsAPIMixin method</i> ), 33
<i>torrents_info()</i> ( <i>qbittorrentapi.TorrentsAPIMixin method</i> ), 27	<i>torrents_setAutoManagement()</i> ( <i>qbittorrentapi.TorrentsAPIMixin method</i> ), 30
<i>torrents_pause()</i> ( <i>qbittorrentapi.TorrentsAPIMixin method</i> ), 27	<i>torrents_setCategory()</i> ( <i>qbittorrentapi.TorrentsAPIMixin method</i> ), 30
<i>torrents_piece_hashes()</i> ( <i>qbittorrentapi.TorrentsAPIMixin method</i> ), 27	<i>torrents_setDownloadLimit()</i> ( <i>qbittorrentapi.TorrentsAPIMixin method</i> ), 30
<i>torrents_piece_states()</i> ( <i>qbittorrentapi.TorrentsAPIMixin method</i> ), 28	<i>torrents_setForceStart()</i> ( <i>qbittorrentapi.TorrentsAPIMixin method</i> ), 30
<i>torrents_pieceHashes()</i> ( <i>qbittorrentapi.TorrentsAPIMixin method</i> ), 27	<i>torrents_setLocation()</i> ( <i>qbittorrentapi.TorrentsAPIMixin method</i> ), 31
<i>torrents_pieceStates()</i> ( <i>qbittorrentapi.TorrentsAPIMixin method</i> ), 27	<i>torrents_setShareLimits()</i> ( <i>qbittorrentapi.TorrentsAPIMixin method</i> ), 31
<i>torrents_properties()</i> ( <i>qbittorrentapi.TorrentsAPIMixin method</i> ), 28	<i>torrents_setSuperSeeding()</i> ( <i>qbittorrentapi.TorrentsAPIMixin method</i> ), 31
<i>torrents_reannounce()</i> ( <i>qbittorrentapi.TorrentsAPIMixin method</i> ), 28	<i>torrents_setUploadLimit()</i> ( <i>qbittorrentapi.TorrentsAPIMixin method</i> ), 31
<i>torrents_recheck()</i> ( <i>qbittorrentapi.TorrentsAPIMixin method</i> ), 28	<i>torrents_tags()</i> ( <i>qbittorrentapi.TorrentsAPIMixin method</i> ), 33
<i>torrents_remove_categories()</i> ( <i>qbittorrentapi.TorrentsAPIMixin method</i> ), 29	<i>torrents_toggle_first_last_piece_priority()</i> ( <i>qbittorrentapi.TorrentsAPIMixin method</i> ), 33
<i>torrents_remove_tags()</i> ( <i>qbittorrentapi.TorrentsAPIMixin method</i> ), 29	<i>torrents_toggle_sequential_download()</i> ( <i>qbittorrentapi.TorrentsAPIMixin method</i> ), 33
<i>torrents_remove_trackers()</i> ( <i>qbittorrentapi.TorrentsAPIMixin method</i> ), 29	<i>torrents_toggleFirstLastPiecePrio()</i> ( <i>qbittorrentapi.TorrentsAPIMixin method</i> ), 33
<i>torrents_removeCategories()</i> ( <i>qbittorrentapi.TorrentsAPIMixin method</i> ), 29	<i>torrents_toggleSequentialDownload()</i> ( <i>qbittorrentapi.TorrentsAPIMixin method</i> ), 33

*(qbittorrentapi.TorrentsAPIMixin method)*, 33  
*torrents\_top\_priority()* (*qbittorrentapi.TorrentsAPIMixin method*), 33  
*torrents\_topPrio()* (*qbittorrentapi.TorrentsAPIMixin method*), 33  
*torrents\_trackers()* (*qbittorrentapi.TorrentsAPIMixin method*), 34  
*torrents\_upload\_limit()* (*qbittorrentapi.TorrentsAPIMixin method*), 34  
*torrents\_uploadLimit()* (*qbittorrentapi.TorrentsAPIMixin method*), 34  
*torrents\_webseeds()* (*qbittorrentapi.TorrentsAPIMixin method*), 34  
*TorrentsAPIMixin* (class in *qbittorrentapi*), 21  
*trackers* (*qbittorrentapi.TorrentDictionary* attribute), 37  
*Transfer* (class in *qbittorrentapi*), 38  
*transfer\_ban\_peers()* (*qbittorrentapi.TransferAPIMixin method*), 37  
*transfer\_banPeers()* (*qbittorrentapi.TransferAPIMixin method*), 37  
*transfer\_download\_limit()* (*qbittorrentapi.TransferAPIMixin method*), 37  
*transfer\_downloadLimit()* (*qbittorrentapi.TransferAPIMixin method*), 37  
*transfer\_info()* (*qbittorrentapi.TransferAPIMixin method*), 37  
*transfer\_set\_download\_limit()* (*qbittorrentapi.TransferAPIMixin method*), 38  
*transfer\_set\_upload\_limit()* (*qbittorrentapi.TransferAPIMixin method*), 38  
*transfer\_setDownloadLimit()* (*qbittorrentapi.TransferAPIMixin method*), 38  
*transfer\_setUploadLimit()* (*qbittorrentapi.TransferAPIMixin method*), 38  
*transfer\_speed\_limits\_mode()* (*qbittorrentapi.TransferAPIMixin method*), 38  
*transfer\_speedLimitsMode()* (*qbittorrentapi.TransferAPIMixin method*), 38  
*transfer\_toggle\_speed\_limits\_mode()* (*qbittorrentapi.TransferAPIMixin method*), 38  
*transfer\_toggleSpeedLimitsMode()* (*qbittorrentapi.TransferAPIMixin method*), 38  
*transfer\_upload\_limit()* (*qbittorrentapi.TransferAPIMixin method*), 38  
*transfer\_uploadLimit()* (*qbittorrentapi.TransferAPIMixin method*), 38  
*TransferAPIMixin* (class in *qbittorrentapi*), 37

## U

*Unauthorized401Error*, 8  
*uninstall\_plugin()* (*qbittorrentapi.Search method*), 20

*uninstallPlugin()* (*qbittorrentapi.Search method*), 20  
*UnsupportedMediaType415Error*, 8  
*update\_plugins()* (*qbittorrentapi.Search method*), 20  
*updatePlugins()* (*qbittorrentapi.Search method*), 20  
*upload\_limit* (*qbittorrentapi.TorrentDictionary* attribute), 37  
*upload\_limit* (*qbittorrentapi.Transfer* attribute), 39  
*uploadLimit* (*qbittorrentapi.TorrentDictionary* attribute), 37  
*uploadLimit* (*qbittorrentapi.Transfer* attribute), 39

## V

*version* (*qbittorrentapi.Application* attribute), 10

## W

*web\_api\_version* (*qbittorrentapi.Application* attribute), 10  
*webapiVersion* (*qbittorrentapi.Application* attribute), 10  
*webseeds* (*qbittorrentapi.TorrentDictionary* attribute), 37