

---

**qbittorrent-api**

***Release 2020.6.4***

**Aug 14, 2020**



---

## Contents

---

<b>1</b>	<b>Introduction</b>	<b>1</b>
<b>Python Module Index</b>		<b>41</b>
<b>Index</b>		<b>43</b>



# CHAPTER 1

---

## Introduction

---

Python client implementation for qBittorrent Web API.

Currently supports up to qBittorrent [v4.2.5](#) (Web API v2.5.1) released on April 24, 2020.

The full qBittorrent Web API documentation is available on their [wiki](#).

### 1.1 Features

- The entire qBittorrent Web API is implemented.
- qBittorrent version checking for an endpoint's existence/features is automatically handled.
- All Python versions are supported.
- If the authentication cookie expires, a new one is automatically requested in line with any API call.

### 1.2 Installation

- **Install via pip from PyPI:**

- `pip install qbittorrent-api`

- **Install specific release:**

- `pip install git+https://github.com/rmartin16/qbittorrent-api.git@v2020.6.4#egg=qbittorrent-api`

- **Install direct from master:**

- `pip install git+https://github.com/rmartin16/qbittorrent-api.git#egg=qbittorrent-api`

- Ensure urllib3, requests, and attrdict are installed. (These are installed automatically using the methods above.)
- Enable WebUI in qBittorrent: Tools -> Preferences -> Web UI
- If the Web API will be exposed to the Internet, follow the [recommendations](#).

## 1.3 Getting Started

```
import qbittorrentapi

# instantiate a Client using the appropriate WebUI configuration
qbt_client = qbittorrentapi.Client(host='localhost:8080', username='admin', password=
    'adminadmin')

# the Client will automatically acquire/maintain a logged in state in line with any
# request.
# therefore, this is not necessary; however, you many want to test the provided login_
# credentials.
try:
    qbt_client.auth_log_in()
except qbittorrentapi.LoginFailed as e:
    print(e)

# display qBittorrent info
print(f'qBittorrent: {qbt_client.app.version}')
print(f'qBittorrent Web API: {qbt_client.app.web_api_version}')
for k,v in qbt_client.app.build_info.items(): print(f'{k}: {v}')

# retrieve and show all torrents
for torrent in qbt_client.torrents_info():
    print(f'{torrent.hash[-6:]}: {torrent.name} ({torrent.state})')

# pause all torrents
qbt_client.torrents.pause.all()
```

## 1.4 Usage

First, the Web API endpoints are organized in to eight namespaces.

- Authentication (auth)
- Application (app)
- Log (log)
- Sync (sync)
- Transfer (transfer)
- Torrent Management (torrents)
- RSS (rss)
- Search (search)

Second, this client has two modes of interaction with the qBittorrent Web API.

Each Web API endpoint is implemented one-to-one as a method of the instantiated client.

```
import qbittorrentapi
qbt_client = qbittorrentapi.Client(host='localhost:8080', username='admin', password=
    ↪'adminadmin')
qbt_client.app_version()
qbt_client.rss_rules()
qbt_client.torrents_info()
qbt_client.torrents_resume(torrent_hashes='... ')
# and so on
```

However, a more robust interface to the endpoints is available via each namespace. This is intended to provide a more seamless and intuitive interface to the Web API.

```
import qbittorrentapi
qbt_client = qbittorrentapi.Client(host='localhost:8080', username='admin', password=
    ↪'adminadmin')
# changing a preference
is_dht_enabled = qbt_client.app.preferences.dht
qbt_client.app.preferences = dict(dht=not is_dht_enabled)
# stopping all torrents
qbt_client.torrents.pause.all()
# retrieve different views of the log
qbt_client.log.main.warning()
qbt_client.log.main.normal()
```

Finally, some of the objects returned by the client support methods of their own. This is most pronounced for torrents themselves.

```
import qbittorrentapi
qbt_client = qbittorrentapi.Client(host='localhost:8080', username='admin', password=
    ↪'adminadmin')

for torrent in qbt_client.torrents.info.active():
    torrent.set_location(location='/home/user/torrents/')
    torrent.reannounce()
    torrent.upload_limit = -1
```

### 1.4.1 Introduction

Python client implementation for qBittorrent Web API.

Currently supports up to qBittorrent v4.2.5 (Web API v2.5.1) released on April 24, 2020.

The full qBittorrent Web API documentation is available on their [wiki](#).

### Features

- The entire qBittorrent Web API is implemented.
- qBittorrent version checking for an endpoint's existence/features is automatically handled.
- All Python versions are supported.
- If the authentication cookie expires, a new one is automatically requested in line with any API call.

## Installation

- **Install via pip from PyPI:**

```
- pip install qbittorrent-api
```

- **Install specific release:**

```
- pip install git+https://github.com/rmartin16/qbittorrent-api.  
git@v2020.6.4#egg=qbittorrent-api
```

- **Install direct from master:**

```
- pip install git+https://github.com/rmartin16/qbittorrent-api.  
git#egg=qbittorrent-api
```

- Ensure urllib3, requests, and attrdict are installed. (These are installed automatically using the methods above.)
- Enable WebUI in qBittorrent: Tools -> Preferences -> Web UI
- If the Web API will be exposed to the Internet, follow the [recommendations](#).

## Getting Started

```
import qbittorrentapi

# instantiate a Client using the appropriate WebUI configuration
qbt_client = qbittorrentapi.Client(host='localhost:8080', username='admin', password=
    'adminadmin')

# the Client will automatically acquire/maintain a logged in state in line with any_
# request.
# therefore, this is not necessary; however, you many want to test the provided login_
# credentials.
try:
    qbt_client.auth_log_in()
except qbittorrentapi.LoginFailed as e:
    print(e)

# display qBittorrent info
print(f'qBittorrent: {qbt_client.app.version}')
print(f'qBittorrent Web API: {qbt_client.app.web_api_version}')
for k,v in qbt_client.app.build_info.items(): print(f'{k}: {v}')

# retrieve and show all torrents
for torrent in qbt_client.torrents_info():
    print(f'{torrent.hash[-6:]}: {torrent.name} ({torrent.state})')

# pause all torrents
qbt_client.torrents.pause.all()
```

## Usage

First, the Web API endpoints are organized in to eight namespaces.

- Authentication (auth)
- Application (app)

- Log (log)
- Sync (sync)
- Transfer (transfer)
- Torrent Management (torrents)
- RSS (rss)
- Search (search)

Second, this client has two modes of interaction with the qBittorrent Web API.

Each Web API endpoint is implemented one-to-one as a method of the instantiated client.

```
import qbittorrentapi
qbt_client = qbittorrentapi.Client(host='localhost:8080', username='admin', password=
    'adminadmin')
qbt_client.app_version()
qbt_client.rss_rules()
qbt_client.torrents_info()
qbt_client.torrents_resume(torrent_hashes='... ')
# and so on
```

However, a more robust interface to the endpoints is available via each namespace. This is intended to provide a more seamless and intuitive interface to the Web API.

```
import qbittorrentapi
qbt_client = qbittorrentapi.Client(host='localhost:8080', username='admin', password=
    'adminadmin')
# changing a preference
is_dht_enabled = qbt_client.app.preferences.dht
qbt_client.app.preferences = dict(dht=not is_dht_enabled)
# stopping all torrents
qbt_client.torrents.pause.all()
# retrieve different views of the log
qbt_client.log.main.warning()
qbt_client.log.main.normal()
```

Finally, some of the objects returned by the client support methods of their own. This is most pronounced for torrents themselves.

```
import qbittorrentapi
qbt_client = qbittorrentapi.Client(host='localhost:8080', username='admin', password=
    'adminadmin')

for torrent in qbt_client.torrents.info.active():
    torrent.set_location(location='/home/user/torrents/')
    torrent.reannounce()
    torrent.upload_limit = -1
```

## 1.4.2 Behavior & Configuration

### Untrusted WebUI Certificate

- qBittorrent allows you to configure HTTPS with an untrusted certificate; this commonly includes self-signed certificates.

- When using such a certificate, instantiate Client with `VERIFY_WEBUI_CERTIFICATE=False` or set environment variable `PYTHON_QBITTORRENTAPI_DO_NOT_VERIFY_WEBUI_CERTIFICATE` to a non-null value.
- Failure to do this will cause connections to qBittorrent to fail.
- As a word of caution, doing this actually does turn off certificate verification. Therefore, for instance, potential man-in-the-middle attacks will not be detected and reported (since the error is suppressed). However, the connection will remain encrypted.

## Host, Username and Password

- These can be provided when instantiating Client or calling `qbt_client.auth_log_in(username='...', password='...')`.
- Alternatively, set environment variables `PYTHON_QBITTORRENTAPI_HOST`, `PYTHON_QBITTORRENTAPI_USERNAME` and `PYTHON_QBITTORRENTAPI_PASSWORD`.

## Unimplemented API Endpoints

- Since the qBittorrent Web API has evolved over time, some endpoints may not be available from the qBittorrent host.
- By default, if a call is made to endpoint that doesn't exist for the version of the qBittorrent host (e.g., the Search endpoints were introduced in Web API v2.1.1), there's a debug logger output and None is returned.
- To raise `NotImplementedError` instead, instantiate Client with `RAISE_NOTIMPLEMENTEDERROR_FOR_UNIMPLEMENTED_ENDPOINTS=True`.

## Disable Logging Debug Output

- Instantiate Client with `DISABLE_LOGGING_DEBUG_OUTPUT=True` or manually disable logging for the relevant packages:

```
- logging.getLogger('qbittorrentapi').setLevel(logging.INFO)
- logging.getLogger('requests').setLevel(logging.INFO)
- logging.getLogger('urllib3').setLevel(logging.INFO)
```

### 1.4.3 Performance

By default, complex objects are returned from some endpoints. These objects allow for accessing the response's items as attributes and include methods for contextually relevant actions (such as `start()` and `stop()` for a torrent, for example).

This comes at the cost of performance, though. Generally, this cost isn't large; however, some endpoints, such as `torrents_files()`, may need to convert a large payload and the cost can be significant.

This client can be configured to always return only the simple JSON if desired. Simply set `SIMPLE_RESPONSES=True` when instantiating the client.

```
qb_client = qbittorrentapi.Client(host='localhost:8080', username='admin', password='admin', SIMPLE_RESPONSES=True)
```

Alternatively, `SIMPLE_RESPONSES` can be set to True to return the simple JSON only for an individual method call.

```
qbt_client.torrents.files(torrent_hash='...', SIMPLE_RESPONSES=True)
```

## 1.4.4 Exceptions

**exception** qbittorrentapi.exceptions.**APIError**

Bases: Exception

Base error for all exceptions from this Client.

**exception** qbittorrentapi.exceptions.**FileError**

Bases: OSError, qbittorrentapi.exceptions.APIError

Base class for all exceptions for file handling.

**exception** qbittorrentapi.exceptions.**TorrentFileError**

Bases: qbittorrentapi.exceptions.FileError

Base class for all exceptions for torrent files.

**exception** qbittorrentapi.exceptions.**TorrentFileNotFoundException**

Bases: qbittorrentapi.exceptions.TorrentFileError

Specified torrent file does not appear to exist.

**exception** qbittorrentapi.exceptions.**TorrentFilePermissionError**

Bases: qbittorrentapi.exceptions.TorrentFileError

Permission was denied to read the specified torrent file.

**exception** qbittorrentapi.exceptions.**APIConnectionError**(\*args, \*\*kwargs)

Bases: requests.exceptions.RequestException, qbittorrentapi.exceptions.APIError

Base class for all communications errors including HTTP errors.

**exception** qbittorrentapi.exceptions.**LoginFailed**(\*args, \*\*kwargs)

Bases: qbittorrentapi.exceptions.APIConnectionError

This can technically be raised with any request since log in may be attempted for any request and could fail.

**exception** qbittorrentapi.exceptions.**HTTPSError**(\*args, \*\*kwargs)

Bases: requests.exceptions.HTTPError, qbittorrentapi.exceptions.APIConnectionError

Base error for all HTTP errors. All errors following a successful connection to qBittorrent are returned as HTTP statuses.

**exception** qbittorrentapi.exceptions.**HTTP4XXError**(\*args, \*\*kwargs)

Bases: qbittorrentapi.exceptions.HTTPSError

Base error for all HTTP 4XX statuses.

**exception** qbittorrentapi.exceptions.**HTTP5XXError**(\*args, \*\*kwargs)

Bases: qbittorrentapi.exceptions.HTTPSError

Base error for all HTTP 5XX statuses.

**exception** qbittorrentapi.exceptions.**HTTP400Error**(\*args, \*\*kwargs)

Bases: qbittorrentapi.exceptions.HTTP4XXError

HTTP 400 Status

```
exception qbittorrentapi.exceptions.HTTP401Error (*args, **kwargs)
Bases: qbittorrentapi.exceptions.HTTP4XXError

HTTP 401 Status

exception qbittorrentapi.exceptions.HTTP403Error (*args, **kwargs)
Bases: qbittorrentapi.exceptions.HTTP4XXError

HTTP 403 Status

exception qbittorrentapi.exceptions.HTTP404Error (*args, **kwargs)
Bases: qbittorrentapi.exceptions.HTTP4XXError

HTTP 404 Status

exception qbittorrentapi.exceptions.HTTP409Error (*args, **kwargs)
Bases: qbittorrentapi.exceptions.HTTP4XXError

HTTP 409 Status

exception qbittorrentapi.exceptions.HTTP415Error (*args, **kwargs)
Bases: qbittorrentapi.exceptions.HTTP4XXError

HTTP 415 Status

exception qbittorrentapi.exceptions.HTTP500Error (*args, **kwargs)
Bases: qbittorrentapi.exceptions.HTTP5XXError

HTTP 500 Status

exception qbittorrentapi.exceptions.MissingRequiredParameters400Error (*args,
**kwargs)
Bases: qbittorrentapi.exceptions.HTTP400Error

Endpoint call is missing one or more required parameters.

exception qbittorrentapi.exceptions.InvalidRequest400Error (*args, **kwargs)
Bases: qbittorrentapi.exceptions.HTTP400Error

One or more endpoint arguments are malformed.

exception qbittorrentapi.exceptions.Unauthorized401Error (*args, **kwargs)
Bases: qbittorrentapi.exceptions.HTTP401Error

Primarily reserved for XSS and host header issues.

exception qbittorrentapi.exceptions.Forbidden403Error (*args, **kwargs)
Bases: qbittorrentapi.exceptions.HTTP403Error

Not logged in, IP has been banned, or calling an API method that isn't public.

exception qbittorrentapi.exceptions.NotFound404Error (*args, **kwargs)
Bases: qbittorrentapi.exceptions.HTTP404Error

This should mean qBittorrent couldn't find a torrent for the torrent hash.

exception qbittorrentapi.exceptions.Conflict409Error (*args, **kwargs)
Bases: qbittorrentapi.exceptions.HTTP409Error

Returned if arguments don't make sense specific to the endpoint.

exception qbittorrentapi.exceptions.UnsupportedMediaType415Error (*args,
**kwargs)
Bases: qbittorrentapi.exceptions.HTTP415Error

torrents/add endpoint will return this for invalid URL(s) or files.
```

```
exception qbittorrentapi.exceptions.InternalServerError500Error(*args,
                                                               **kwargs)
Bases: qbittorrentapi.exceptions.HTTP500Error
Returned if qBittorrent craps on itself while processing the request...
```

## 1.4.5 API Reference

### Application

```
class qbittorrentapi.AppAPIMixin(host='', port=None, username=None, password=None,
                                  **kwargs)
```

Implementation of all Application API methods

```
app_buildInfo(**kwargs)
```

Retrieve build info. (alias: app\_buildInfo)

**Returns** Dictionary of build info. Each piece of info is an attribute. Properties: [https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-\(qBittorrent-4.1\)#get-build-info](https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-(qBittorrent-4.1)#get-build-info)

```
app_build_info(**kwargs)
```

Retrieve build info. (alias: app\_buildInfo)

**Returns** Dictionary of build info. Each piece of info is an attribute. Properties: [https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-\(qBittorrent-4.1\)#get-build-info](https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-(qBittorrent-4.1)#get-build-info)

```
app_defaultSavePath(**kwargs)
```

Retrieves the default path for where torrents are saved. (alias: app\_defaultSavePath)

**Returns** string

```
app_default_save_path(**kwargs)
```

Retrieves the default path for where torrents are saved. (alias: app\_defaultSavePath)

**Returns** string

```
app_preferences(**kwargs)
```

Retrieve qBittorrent application preferences.

**Returns** Dictionary of preferences. Each preference is an attribute. Properties: [https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-\(qBittorrent-4.1\)#get-application-preferences](https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-(qBittorrent-4.1)#get-application-preferences)

```
app_setPreferences(pref=None, **kwargs)
```

Set one or more preferences in qBittorrent application. (alias: app\_setPreferences)

**Parameters** **prefs** – dictionary of preferences to set

**Returns** None

```
app_set_preferences(pref=None, **kwargs)
```

Set one or more preferences in qBittorrent application. (alias: app\_setPreferences)

**Parameters** **prefs** – dictionary of preferences to set

**Returns** None

```
app_shutdown(**kwargs)
```

Shutdown qBittorrent.

```
app_version(**kwargs)
```

Retrieve application version

**Returns** string

**app\_web\_api\_version(\*\*kwargs)**  
Retrieve web API version. (alias: app\_webapiVersion)

**Returns** string

**app\_webapiVersion(\*\*kwargs)**  
Retrieve web API version. (alias: app\_webapiVersion)

**Returns** string

**application**

Allows for transparent interaction with Application endpoints. (alias: app)

See Application class for usage. :return: Application object

**class qbittorrentapi.Application(\*args, \*\*kwargs)**

Allows interaction with “Application” API endpoints.

**Usage**

```
>>> from qbittorrentapi import Client
>>> client = Client(host='localhost:8080', username='admin', password=
...>'adminadmin')
>>> # this are all the same attributes that are available as named in
...>the
>>> # endpoints or the more pythonic names in Client (with or
...>without 'app_' prepended)
>>> webapiVersion = client.application.webapiVersion
>>> web_api_version = client.application.web_api_version
>>> app_web_api_version = client.application.app_web_api_version
>>> # access and set preferences as attributes
>>> is_dht_enabled = client.application.preferences.dht
>>> # supports sending a just subset of preferences to update
>>> client.application.preferences = dict(dht=(not is_dht_enabled))
>>> prefs = client.application.preferences
>>> prefs['web_ui_clickjacking_protection_enabled'] = True
>>> client.app.preferences = prefs
>>>
>>> client.application.shutdown()
```

**buildInfo**

**build\_info**

**defaultSavePath**

**default\_save\_path**

**preferences**

**setPreferences(pref=None, \*\*kwargs)**

**set\_preferences(pref=None, \*\*kwargs)**

**shutdown()**

**version**

**web\_api\_version**

**webapiVersion**

## Authentication

```
class qbittorrentapi.Request(host='', port=None, username=None, password=None, **kwargs)
    Facilitates HTTP requests to qBittorrent.
```

```
auth_log_in(username=None, password=None)
    Log in to qBittorrent host.
```

### Raises

- *LoginFailed* – if credentials failed to log in
- *Forbidden403Error* – if user user is banned... or not logged in

### Parameters

- **username** – user name for qBittorrent client
- **password** – password for qBittorrent client

### Returns

```
auth_log_out(**kwargs)
    End session with qBittorrent.
```

## Client

```
class qbittorrentapi.Client(host='', port=None, username=None, password=None, **kwargs)
    Initialize API for qBittorrent client.
```

Host must be specified. Username and password can be specified at login. A call to auth\_log\_in is not explicitly required if username and password are provided during Client construction.

### Parameters

- **host** – hostname for qBittorrent Web API (e.g. [http[s]://]localhost[:8080])
- **port** – port number for qBittorrent Web API (note: only used if host does not contain a port)
- **username** – user name for qBittorrent client
- **password** – password for qBittorrent client
- **SIMPLE\_RESPONSES** – By default, complex objects are returned from some endpoints. These objects will allow for accessing responses' items as attributes and include methods for contextually relevant actions. This comes at the cost of performance. Generally, this cost isn't large; however, some endpoints, such as torrents\_files() method, may need to convert a large payload. Set this to True to return the simple JSON back. Alternatively, set this to True only for an individual method call. For instance, when requesting the files for a torrent: client.torrents\_files(hash='...', SIMPLE\_RESPONSES=True).
- **VERIFY\_WEBUI\_CERTIFICATE** – Set to False to skip verify certificate for HTTPS connections; for instance, if the connection is using a self-signed certificate. Not setting this to False for self-signed certs will cause a APIConnectionError exception to be raised.
- **RAISE\_UNIMPLEMENTEDERROR\_FOR\_UNIMPLEMENTED\_API\_ENDPOINTS** – Some Endpoints may not be implemented in older versions of qBittorrent. Setting this to True will raise a UnimplementedError instead of just returning None.
- **DISABLE\_LOGGING\_DEBUG\_OUTPUT** – Turn off debug output from logging for this package as well as Requests & urllib3.

## Log

```
class qbittorrentapi.LogAPIMixIn(host='', port=None, username=None, password=None,  
                                  **kwargs)
```

Implementation of all Log API methods.

```
log_main(normal=None, info=None, warning=None, critical=None, last_known_id=None,  
          **kwargs)
```

Retrieve the qBittorrent log entries. Iterate over returned object.

### Parameters

- **normal** – False to exclude ‘normal’ entries
- **info** – False to exclude ‘info’ entries
- **warning** – False to exclude ‘warning’ entries
- **critical** – False to exclude ‘critical’ entries
- **last\_known\_id** – only entries with an ID greater than this value will be returned

**Returns** List of log entries.

```
log_peers(last_known_id=None, **kwargs)
```

Retrieve qBittorrent peer log.

**Parameters** **last\_known\_id** – only entries with an ID greater than this value will be returned

**Returns** list of log entries in a List

```
class qbittorrentapi.Log(client)
```

Allows interaction with “Log” API endpoints.

### Usage

```
>>> from qbittorrentapi import Client  
>>> client = Client(host='localhost:8080', username='admin', password=  
    ↪'adminadmin')  
>>> # this is all the same attributes that are available as named in  
    ↪the  
>>> # endpoints or the more pythonic names in Client (with or  
    ↪without 'log_' prepended)  
>>> log_list = client.log.main()  
>>> peers_list = client.log.peers(hash='...')  
>>> # can also filter log down with additional attributes  
>>> log_info = client.log.main.info(last_known_id='...')  
>>> log_warning = client.log.main.warning(last_known_id='...')
```

```
peers(last_known_id=None, **kwargs)
```

## RSS

```
class qbittorrentapi.RSSAPIMixIn(host='', port=None, username=None, password=None,  
                                  **kwargs)
```

Implementation of all RSS API methods.

```
rss_addFeed(url=None, item_path=None, **kwargs)
```

Add new RSS feed. Folders in path must already exist. (alias: rss\_addFeed)

**Raises** *Conflict409Error* –

### Parameters

- **url** – URL of RSS feed (e.g <http://thepiratebay.org/rss/top100/200>)
- **item\_path** – Name and/or path for new feed (e.g. FolderSubfolderFeedName)

**Returns** None

**rss\_addFolder** (*folder\_path=None, \*\*kwargs*)

Add a RSS folder. Any intermediate folders in path must already exist. (alias: rss\_addFolder)

**Raises** *Conflict409Error* –

**Parameters** **folder\_path** – path to new folder (e.g. LinuxISOs)

**Returns** None

**rss\_add\_feed** (*url=None, item\_path=None, \*\*kwargs*)

Add new RSS feed. Folders in path must already exist. (alias: rss\_addFeed)

**Raises** *Conflict409Error* –

**Parameters**

- **url** – URL of RSS feed (e.g <http://thepiratebay.org/rss/top100/200>)
- **item\_path** – Name and/or path for new feed (e.g. FolderSubfolderFeedName)

**Returns** None

**rss\_add\_folder** (*folder\_path=None, \*\*kwargs*)

Add a RSS folder. Any intermediate folders in path must already exist. (alias: rss\_addFolder)

**Raises** *Conflict409Error* –

**Parameters** **folder\_path** – path to new folder (e.g. LinuxISOs)

**Returns** None

**rss\_items** (*include\_feed\_data=None, \*\*kwargs*)

Retrieve RSS items and optionally feed data.

**Parameters** **include\_feed\_data** – True or false to include feed data

**Returns** dictionary of RSS items

**rss\_markAsRead** (*item\_path=None, article\_id=None, \*\*kwargs*)

Mark RSS article as read. If article ID is not provider, the entire feed is marked as read. (alias: rss\_markAsRead)

**Raises** *NotFound404Error* –

**Parameters**

- **item\_path** – path to item to be refreshed (e.g. FolderSubfolderItemName)
- **article\_id** – article ID from rss\_items()

**Returns** None

**rss\_mark\_as\_read** (*item\_path=None, article\_id=None, \*\*kwargs*)

Mark RSS article as read. If article ID is not provider, the entire feed is marked as read. (alias: rss\_markAsRead)

**Raises** *NotFound404Error* –

**Parameters**

- **item\_path** – path to item to be refreshed (e.g. FolderSubfolderItemName)
- **article\_id** – article ID from rss\_items()

**Returns** None

**rss\_matchingArticles**(rule\_name=None, \*\*kwargs)  
Fetch all articles matching a rule. (alias: rss\_matchingArticles)

**Parameters** `rule_name` – Name of rule to return matching articles

**Returns** RSSItemsDictionary of articles

**rss\_matching\_articles**(rule\_name=None, \*\*kwargs)  
Fetch all articles matching a rule. (alias: rss\_matchingArticles)

**Parameters** `rule_name` – Name of rule to return matching articles

**Returns** RSSItemsDictionary of articles

**rss\_moveItem**(orig\_item\_path=None, new\_item\_path=None, \*\*kwargs)  
Move/rename a RSS item (folder, feed, etc). (alias: rss\_moveItem)

**Raises** `Conflict409Error` –

**Parameters**

- `orig_item_path` – path to item to be removed (e.g. FolderSubfolderItemName)
- `new_item_path` – path to item to be removed (e.g. FolderSubfolderItemName)

**Returns** None

**rss\_move\_item**(orig\_item\_path=None, new\_item\_path=None, \*\*kwargs)  
Move/rename a RSS item (folder, feed, etc). (alias: rss\_moveItem)

**Raises** `Conflict409Error` –

**Parameters**

- `orig_item_path` – path to item to be removed (e.g. FolderSubfolderItemName)
- `new_item_path` – path to item to be removed (e.g. FolderSubfolderItemName)

**Returns** None

**rss\_refreshItem**(item\_path=None, \*\*kwargs)  
Trigger a refresh for a RSS item (alias: rss\_refreshItem)

**Parameters** `item_path` – path to item to be refreshed (e.g. FolderSubfolderItemName)

**Returns** None

**rss\_refresh\_item**(item\_path=None, \*\*kwargs)  
Trigger a refresh for a RSS item (alias: rss\_refreshItem)

**Parameters** `item_path` – path to item to be refreshed (e.g. FolderSubfolderItemName)

**Returns** None

**rss\_removeItem**(item\_path=None, \*\*kwargs)  
Remove a RSS item (folder, feed, etc). (alias: rss\_removeItem)

NOTE: Removing a folder also removes everything in it.

**Raises** `Conflict409Error` –

**Parameters** `item_path` – path to item to be removed (e.g. FolderSubfolderItemName)

**Returns** None

**rss\_removeRule**(rule\_name=None, \*\*kwargs)  
Delete a RSS auto-downloading rule. (alias: rss\_removeRule)

**Parameters** `rule_name` – Name of rule to delete

**Returns** None

**`rss_remove_item`**(`item_path=None, **kwargs`)

Remove a RSS item (folder, feed, etc). (alias: `rss_removeItem`)

NOTE: Removing a folder also removes everything in it.

**Raises** `Conflict409Error` –

**Parameters** `item_path` – path to item to be removed (e.g. `FolderSubfolderItemName`)

**Returns** None

**`rss_remove_rule`**(`rule_name=None, **kwargs`)

Delete a RSS auto-downloading rule. (alias: `rss_removeRule`)

**Parameters** `rule_name` – Name of rule to delete

**Returns** None

**`rss_renameRule`**(`orig_rule_name=None, new_rule_name=None, **kwargs`)

Rename a RSS auto-download rule. (alias: `rss_renameRule`)

**Parameters**

- `orig_rule_name` – current name of rule
- `new_rule_name` – new name for rule

**Returns** None

**`rss_rename_rule`**(`orig_rule_name=None, new_rule_name=None, **kwargs`)

Rename a RSS auto-download rule. (alias: `rss_renameRule`)

**Parameters**

- `orig_rule_name` – current name of rule
- `new_rule_name` – new name for rule

**Returns** None

**`rss_rules`**(`**kwargs`)

Retrieve RSS auto-download rule definitions.

**Returns** None

**`rss_setRule`**(`rule_name=None, rule_def=None, **kwargs`)

Create a new RSS auto-downloading rule. (alias: `rss_setRule`)

**Parameters**

- `rule_name` – name for new rule
- `rule_def` – dictionary with rule fields Properties: [https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-\(qBittorrent-4.1\)#set-auto-downloading-rule](https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-(qBittorrent-4.1)#set-auto-downloading-rule)

**Returns** None

**`rss_set_rule`**(`rule_name=None, rule_def=None, **kwargs`)

Create a new RSS auto-downloading rule. (alias: `rss_setRule`)

**Parameters**

- `rule_name` – name for new rule

- **rule\_def** – dictionary with rule fields Properties: [https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-\(qBittorrent-4.1\)#set-auto-downloading-rule](https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-(qBittorrent-4.1)#set-auto-downloading-rule)

**Returns** None

**class** qbittorrentapi.RSS(*client*)

Allows interaction with “RSS” API endpoints.

#### Usage

```
>>> from qbittorrentapi import Client
>>> client = Client(host='localhost:8080', username='admin', password=
    ↪'adminadmin')
>>> # this is all the same attributes that are available as named in
    ↪the
>>> # endpoints or the more pythonic names in Client (with or
    ↪without 'log_' prepended)
>>> rss_rules = client.rss.rules
>>> client.rss.addFolder(folder_path="TPB")
>>> client.rss.addFeed(url='...', item_path="TPB\Top100")
>>> client.rss.remove_item(item_path="TPB") # deletes TPB and Top100
>>> client.rss.set_rule(rule_name="...", rule_def={...})
>>> client.rss.items.with_data
>>> client.rss.items.without_data
```

```
addFeed(url=None, item_path=None, **kwargs)
addFolder(folder_path=None, **kwargs)
add_feed(url=None, item_path=None, **kwargs)
add_folder(folder_path=None, **kwargs)
markAsRead(item_path=None, article_id=None, **kwargs)
mark_as_read(item_path=None, article_id=None, **kwargs)
matchingArticles(rule_name=None, **kwargs)
matching_articles(rule_name=None, **kwargs)
moveItem(orig_item_path=None, new_item_path=None, **kwargs)
move_item(orig_item_path=None, new_item_path=None, **kwargs)
refreshItem(item_path=None)
refresh_item(item_path=None)
removeItem(item_path=None, **kwargs)
removeRule(rule_name=None, **kwargs)
remove_item(item_path=None, **kwargs)
remove_rule(rule_name=None, **kwargs)
renameRule(orig_rule_name=None, new_rule_name=None, **kwargs)
rename_rule(orig_rule_name=None, new_rule_name=None, **kwargs)
rules
setRule(rule_name=None, rule_def=None, **kwargs)
set_rule(rule_name=None, rule_def=None, **kwargs)
```

## Search

```
class qbittorrentapi.SearchAPIMixin(host=None, port=None, username=None, password=None,  
                                     **kwargs)
```

Implementation for all Search API methods.

```
search_categories(plugin_name=None, **kwargs)
```

Retrieve categories for search.

**Parameters** `plugin_name` – Limit categories returned by plugin(s) (supports ‘all’ and ‘enabled’)

**Returns** list of categories

```
search_delete(search_id=None, **kwargs)
```

Delete a search job.

**Raises** `NotFound404Error` –

**Parameters** `search_id` – ID of search to delete

**Returns** None

```
search_enablePlugin(plugins=None, enable=None, **kwargs)
```

Enable or disable search plugin(s). (alias: `search_enablePlugin`)

**Parameters**

- `plugins` – list of plugin names
- `enable` – True or False

**Returns** None

```
search_enable_plugin(plugins=None, enable=None, **kwargs)
```

Enable or disable search plugin(s). (alias: `search_enablePlugin`)

**Parameters**

- `plugins` – list of plugin names
- `enable` – True or False

**Returns** None

```
search_installPlugin(sources=None, **kwargs)
```

Install search plugins from either URL or file. (alias: `search_installPlugin`)

**Parameters** `sources` – list of URLs or filepaths

**Returns** None

```
search_install_plugin(sources=None, **kwargs)
```

Install search plugins from either URL or file. (alias: `search_installPlugin`)

**Parameters** `sources` – list of URLs or filepaths

**Returns** None

```
search_plugins(**kwargs)
```

Retrieve details of search plugins.

**Returns** List of plugins. Properties: [https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-\(qBittorrent-4.1\)#get-search-plugins](https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-(qBittorrent-4.1)#get-search-plugins)

```
search_results(search_id=None, limit=None, offset=None, **kwargs)
```

Retrieve the results for the search.

### Raises

- *NotFound404Error* –
- *Conflict409Error* –

### Parameters

- **search\_id** – ID of search job
- **limit** – number of results to return
- **offset** – where to start returning results

**Returns** Dictionary of results Properties: [https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-\(qBittorrent-4.1\)#get-search-results](https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-(qBittorrent-4.1)#get-search-results)

**search\_start** (*pattern=None, plugins=None, category=None, \*\*kwargs*)

Start a search. Python must be installed. Host may limit number of concurrent searches.

**Raises** *Conflict409Error* –

### Parameters

- **pattern** – term to search for
- **plugins** – list of plugins to use for searching (supports ‘all’ and ‘enabled’)
- **category** – categories to limit search; dependent on plugins. (supports ‘all’)

**Returns** search job

**search\_status** (*search\_id=None, \*\*kwargs*)

Retrieve status of one or all searches.

**Raises** *NotFound404Error* –

**Parameters** **search\_id** – ID of search to get status; leave empty for status of all jobs

**Returns** dictionary of searches Properties: [https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-\(qBittorrent-4.1\)#get-search-status](https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-(qBittorrent-4.1)#get-search-status)

**search\_stop** (*search\_id=None, \*\*kwargs*)

Stop a running search.

**Raises** *NotFound404Error* –

**Parameters** **search\_id** – ID of search job to stop

**Returns** None

**search\_uninstallPlugin** (*names=None, \*\*kwargs*)

Uninstall search plugins. (alias: search\_uninstallPlugin)

**Parameters** **names** – names of plugins to uninstall

**Returns** None

**search\_uninstall\_plugin** (*names=None, \*\*kwargs*)

Uninstall search plugins. (alias: search\_uninstallPlugin)

**Parameters** **names** – names of plugins to uninstall

**Returns** None

**search\_updatePlugins** (*\*\*kwargs*)

Auto update search plugins. (alias: search\_updatePlugins)

**Returns** None

**search\_update\_plugins** (\*\*kwargs)  
Auto update search plugins. (alias: search\_updatePlugins)

**Returns** None

**class qbittorrentapi.Search(\*args, \*\*kwargs)**  
Allows interaction with “Search” API endpoints.

#### Usage

```
>>> from qbittorrentapi import Client
>>> client = Client(host='localhost:8080', username='admin', password=
    ↪'adminadmin')
>>> # this is all the same attributes that are available as named in
    ↪the
>>> # endpoints or the more pythonic names in Client (with or
    ↪without 'search_' prepended)
>>> # initiate searches and retrieve results
>>> search_job = client.search.start(pattern='Ubuntu', plugins='all',_
    ↪category='all')
>>> status = search_job.status()
>>> results = search_job.result()
>>> search_job.delete()
>>> # inspect and manage plugins
>>> plugins = client.search.plugins
>>> cats = client.search.categories(plugin_name='...')
>>> client.search.install_plugin(sources='...')
>>> client.search.update_plugins()
```

**categories** (plugin\_name=None, \*\*kwargs)  
**delete** (search\_id=None, \*\*kwargs)  
**enablePlugin** (plugins=None, enable=None, \*\*kwargs)  
**enable\_plugin** (plugins=None, enable=None, \*\*kwargs)  
**installPlugin** (sources=None, \*\*kwargs)  
**install\_plugin** (sources=None, \*\*kwargs)  
**plugins**  
**results** (search\_id=None, limit=None, offset=None, \*\*kwargs)  
**start** (pattern=None, plugins=None, category=None, \*\*kwargs)  
**status** (search\_id=None, \*\*kwargs)  
**stop** (search\_id=None, \*\*kwargs)  
**uninstallPlugin** (sources=None, \*\*kwargs)  
**uninstall\_plugin** (sources=None, \*\*kwargs)  
**updatePlugins** (\*\*kwargs)  
**update\_plugins** (\*\*kwargs)

#### Sync

**class qbittorrentapi.SyncAPIMixin** (host='', port=None, username=None, password=None,  
\*\*kwargs)  
Implementation of all Sync API Methods.

**sync\_maindata**(*rid*=0, \*\**kwargs*)

Retrieves sync data.

**Parameters** **rid** – response ID

**Returns** dictionary response Properties: [https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-\(qBittorrent-4.1\)#get-main-data](https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-(qBittorrent-4.1)#get-main-data)

**sync\_torrentPeers**(*torrent\_hash*=None, *rid*=0, \*\**kwargs*)

Retrieves torrent sync data. (alias: sync\_torrentPeers)

**Raises** *NotFound404Error* –

**Parameters**

- **torrent\_hash** – hash for torrent
- **rid** – response ID

**Returns** Dictionary of torrent sync data. Properties: [https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-\(qBittorrent-4.1\)#get-torrent-peers-data](https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-(qBittorrent-4.1)#get-torrent-peers-data)

**sync\_torrent\_peers**(*torrent\_hash*=None, *rid*=0, \*\**kwargs*)

Retrieves torrent sync data. (alias: sync\_torrentPeers)

**Raises** *NotFound404Error* –

**Parameters**

- **torrent\_hash** – hash for torrent
- **rid** – response ID

**Returns** Dictionary of torrent sync data. Properties: [https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-\(qBittorrent-4.1\)#get-torrent-peers-data](https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-(qBittorrent-4.1)#get-torrent-peers-data)

**class qbittorrentapi.Sync**(*client*)

Allows interaction with the “Sync” API endpoints.

**Usage:**

```
>>> from qbittorrentapi import Client
>>> client = Client(host='localhost:8080', username='admin', password=
    +'adminadmin')
>>> # this are all the same attributes that are available as named in the
>>> # endpoints or the more pythonic names in Client (with or without 'sync_
    +' prepended)
>>> maindata = client.sync.maindata(rid="...")
>>> # for use when continuously calling maindata for changes in torrents
>>> # this will automatically request the changes since the last call
>>> md = client.sync.maindata.delta()
>>> #
>>> torrentPeers= client.sync.torrentPeers(hash="...", rid='...')
>>> torrent_peers = client.sync.torrent_peers(hash="...", rid='...')
```

## Torrent States

**class qbittorrentapi.TorrentStates**

Torrent States as defined by qBittorrent.

**Definitions:**

- wiki: [https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-\(qBittorrent-4.1\)#get-torrent-list](https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-(qBittorrent-4.1)#get-torrent-list)

- code: <https://github.com/qbittorrent/qBittorrent/blob/master/src/base/bittorrent/torrenthandle.h#L52>

### Usage

```
>>> from qbittorrentapi import Client
>>> from qbittorrentapi import TorrentStates
>>> client = Client()
>>> # print torrent hashes for torrents that are downloading
>>> for torrent in client.torrents_info():
>>>     # check if torrent is downloading
>>>     if torrent.state_enum.is_downloading:
>>>         print(f'{torrent.hash} is downloading...')
>>>     # the appropriate enum member can be directly derived
>>>     state_enum = TorrentStates(torrent.state)
>>>     print(f'{torrent.hash}: {state_enum.value}')
```

```
ALLOCATING = 'allocating'
CHECKING_DOWNLOAD = 'checkingDL'
CHECKING_RESUME_DATA = 'checkingResumeData'
CHECKING_UPLOAD = 'checkingUP'
DOWNLOADING = 'downloading'
ERROR = 'error'
FORCED_UPLOAD = 'forcedUP'
FORCE_DOWNLOAD = 'forceDL'
METADATA_DOWNLOAD = 'metaDL'
MISSING_FILES = 'missingFiles'
MOVING = 'moving'
PAUSED_DOWNLOAD = 'pausedDL'
PAUSED_UPLOAD = 'pausedUP'
QUEUED_DOWNLOAD = 'queuedDL'
QUEUED_UPLOAD = 'queuedUP'
STALLED_DOWNLOAD = 'stalledDL'
STALLED_UPLOAD = 'stalledUP'
UNKNOWN = 'unknown'
UPLOADING = 'uploading'

is_checking
    Returns True if the State is categorized as Checking.

is_complete
    Returns True if the State is categorized as Complete.

is_downloading
    Returns True if the State is categorized as Downloading.

is_errored
    Returns True if the State is categorized as Errored.
```

#### **is\_paused**

Returns True if the State is categorized as Paused.

#### **is\_uploading**

Returns True if the State is categorized as Uploading.

## Torrents

```
class qbittorrentapi.TorrentsAPIMixIn(host='', port=None, username=None, password=None, **kwargs)
```

Implementation of all Torrents API methods.

```
torrents_add(urls=None, torrent_files=None, save_path=None, cookie=None, category=None, is_skip_checking=None, is_paused=None, is_root_folder=None, rename=None, upload_limit=None, download_limit=None, use_auto_torrent_management=None, is_sequential_download=None, is_first_last_piece_priority=None, **kwargs)
```

Add one or more torrents by URLs and/or torrent files.

#### Raises

- *UnsupportedMediaType415Error* – if file is not a valid torrent file
- *TorrentFileNotFoundError* – if a torrent file doesn't exist
- *TorrentFilePermissionError* – if read permission is denied to torrent file

#### Parameters

- **urls** – single instance or an iterable of URLs (<http://>, <https://>, magnet: and bc://bt/)
- **torrent\_files** – several options are available to send torrent files to qBittorrent:  
1) single instance of bytes: useful if torrent file already read from disk or downloaded from internet. 2) single instance of file handle to torrent file: use open(<filepath>, 'rb') to open the torrent file. 3) single instance of a filepath to torrent file: e.g. '/home/user/torrent\_filename.torrent' 4) an iterable of the single instances above to send more than one torrent file 5) dictionary with key/value pairs of torrent name and single instance of above object Note: The torrent name in a dictionary is useful to identify which torrent file errored. qBittorrent provides back that name in the error text. If a torrent name is not provided, then the name of the file will be used. And in the case of bytes (or if filename cannot be determined), the value 'torrent\_n' will be used
- **save\_path** – location to save the torrent data
- **cookie** – cookie to retrieve torrents by URL
- **category** – category to assign to torrent(s)
- **is\_skip\_checking** – skip hash checking
- **is\_paused** – True to start torrent(s) paused
- **is\_root\_folder** – True or False to create root folder
- **rename** – new name for torrent(s)
- **upload\_limit** – upload limit in bytes/second
- **download\_limit** – download limit in bytes/second
- **use\_auto\_torrent\_management** – True or False to use automatic torrent management
- **is\_sequential\_download** – True or False for sequential download

- **is\_first\_last\_piece\_priority** – True or False for first and last piece download priority

**Returns** “Ok.” for success and “Fails.” for failure

**torrents\_addPeers** (*peers=None, torrent\_hashes=None, \*\*kwargs*)  
Add one or more peers to one or more torrents. (alias: torrents\_addPeers)

**Raises** *InvalidRequest400Error* – for invalid peers

#### Parameters

- **peers** – one or more peers to add. each peer should take the form ‘host:port’
- **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.

**Returns** dictionary - {<hash>: {'added': #, 'failed': #}}

**torrents\_addTags** (*tags=None, torrent\_hashes=None, \*\*kwargs*)  
Add one or more tags to one or more torrents. (alias: torrents\_addTags) Note: Tags that do not exist will be created on-the-fly.

#### Parameters

- **tags** – tag name or list of tags
- **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.

**Returns** None

**torrents\_addTrackers** (*torrent\_hash=None, urls=None, \*\*kwargs*)  
Add trackers to a torrent. (alias: torrents\_addTrackers)

**Raises** *NotFound404Error* –

#### Parameters

- **torrent\_hash** – hash for torrent
- **urls** – tracker urls to add to torrent

**Returns** None

**torrents\_add\_peers** (*peers=None, torrent\_hashes=None, \*\*kwargs*)  
Add one or more peers to one or more torrents. (alias: torrents\_addPeers)

**Raises** *InvalidRequest400Error* – for invalid peers

#### Parameters

- **peers** – one or more peers to add. each peer should take the form ‘host:port’
- **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.

**Returns** dictionary - {<hash>: {'added': #, 'failed': #}}

**torrents\_add\_tags** (*tags=None, torrent\_hashes=None, \*\*kwargs*)  
Add one or more tags to one or more torrents. (alias: torrents\_addTags) Note: Tags that do not exist will be created on-the-fly.

#### Parameters

- **tags** – tag name or list of tags
- **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.

**Returns** None

**torrents\_add\_trackers** (*torrent\_hash=None, urls=None, \*\*kwargs*)

Add trackers to a torrent. (alias: torrents\_addTrackers)

**Raises** *NotFound404Error* –

**Parameters**

- **torrent\_hash** – hash for torrent
- **urls** – tracker urls to add to torrent

**Returns** None

**torrents\_bottomPrio** (*torrent\_hashes=None, \*\*kwargs*)

Set torrent as highest priority. Torrent Queuing must be enabled. (alias: torrents\_bottomPrio)

**Raises** *Conflict409* –

**Parameters** **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.

**Returns** None

**torrents\_bottom\_priority** (*torrent\_hashes=None, \*\*kwargs*)

Set torrent as highest priority. Torrent Queuing must be enabled. (alias: torrents\_bottomPrio)

**Raises** *Conflict409* –

**Parameters** **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.

**Returns** None

**torrents\_categories** (\*\*kwargs)

Retrieve all category definitions

Note: torrents/categories is not available until v2.1.0 :return: dictionary of categories

**torrents\_createCategory** (*name=None, save\_path=None, \*\*kwargs*)

Create a new torrent category. (alias: torrents\_createCategory)

Note: save\_path is not available until web API version 2.1.0

**Raises** *Conflict409* – if category name is not valid or unable to create

**Parameters**

- **name** – name for new category
- **save\_path** – location to save torrents for this category

**Returns** None

**torrents\_createTags** (*tags=None, \*\*kwargs*)

Create one or more tags. (alias: torrents\_createTags)

**Parameters** **tags** – tag name or list of tags

**Returns** None

**torrents\_create\_category** (*name=None, save\_path=None, \*\*kwargs*)

Create a new torrent category. (alias: torrents\_createCategory)

Note: save\_path is not available until web API version 2.1.0

**Raises** *Conflict409* – if category name is not valid or unable to create

**Parameters**

- **name** – name for new category
- **save\_path** – location to save torrents for this category

**Returns** None

**torrents\_create\_tags** (*tags=None, \*\*kwargs*)  
Create one or more tags. (alias: torrents\_createTags)

**Parameters** **tags** – tag name or list of tags

**Returns** None

**torrents\_decreasePrio** (*torrent\_hashes=None, \*\*kwargs*)  
Decrease the priority of a torrent. Torrent Queuing must be enabled. (alias: torrents\_decreasePrio)  
**Raises** **Conflict409** –  
**Parameters** **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.

**Returns** None

**torrents\_decrease\_priority** (*torrent\_hashes=None, \*\*kwargs*)  
Decrease the priority of a torrent. Torrent Queuing must be enabled. (alias: torrents\_decreasePrio)  
**Raises** **Conflict409** –  
**Parameters** **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.

**Returns** None

**torrents\_delete** (*delete\_files=None, torrent\_hashes=None, \*\*kwargs*)  
Remove a torrent from qBittorrent and optionally delete its files.

**Parameters**

- **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.
- **delete\_files** – True to delete the torrent’s files

**Returns** None

**torrents\_deleteTags** (*tags=None, \*\*kwargs*)  
Delete one or more tags. (alias: torrents\_deleteTags)

**Parameters** **tags** – tag name or list of tags

**Returns** None

**torrents\_delete\_tags** (*tags=None, \*\*kwargs*)  
Delete one or more tags. (alias: torrents\_deleteTags)

**Parameters** **tags** – tag name or list of tags

**Returns** None

**torrents\_downloadLimit** (*torrent\_hashes=None, \*\*kwargs*)  
Retrieve the download limit for one or more torrents. (alias: torrents\_downloadLimit)

**Returns** dictioanry {hash: limit} (-1 represents no limit)

**torrents\_download\_limit** (*torrent\_hashes=None, \*\*kwargs*)  
Retrieve the download limit for one or more torrents. (alias: torrents\_downloadLimit)

**Returns** dictioanry {hash: limit} (-1 represents no limit)

**torrents\_editCategory** (*name=None, save\_path=None, \*\*kwargs*)

Edit an existing category. (alias: torrents\_editCategory)

Note: torrents/editCategory not available until web API version 2.1.0

**Raises** `Conflict409` –

**Parameters**

- **name** – category to edit
- **save\_path** – new location to save files for this category

**Returns** None

**torrents\_editTracker** (*torrent\_hash=None, original\_url=None, new\_url=None, \*\*kwargs*)

Replace a torrent's tracker with a different one. (alias: torrents\_editTrackers)

**Raises**

- `InvalidRequest400` –
- `NotFound404Error` –
- `Conflict409Error` –

**Parameters**

- **torrent\_hash** – hash for torrent
- **original\_url** – URL for existing tracker
- **new\_url** – new URL to replace

**Returns** None

**torrents\_edit\_category** (*name=None, save\_path=None, \*\*kwargs*)

Edit an existing category. (alias: torrents\_editCategory)

Note: torrents/editCategory not available until web API version 2.1.0

**Raises** `Conflict409` –

**Parameters**

- **name** – category to edit
- **save\_path** – new location to save files for this category

**Returns** None

**torrents\_edit\_tracker** (*torrent\_hash=None, original\_url=None, new\_url=None, \*\*kwargs*)

Replace a torrent's tracker with a different one. (alias: torrents\_editTrackers)

**Raises**

- `InvalidRequest400` –
- `NotFound404Error` –
- `Conflict409Error` –

**Parameters**

- **torrent\_hash** – hash for torrent
- **original\_url** – URL for existing tracker
- **new\_url** – new URL to replace

**Returns** None

**torrents\_filePrio** (*torrent\_hash=None, file\_ids=None, priority=None, \*\*kwargs*)

Set priority for one or more files. (alias: torrents\_filePrio)

**Raises**

- **InvalidRequest400** – if priority is invalid or at least one file ID is not an integer
- **NotFound404Error** –
- **Conflict409** – if torrent metadata has not finished downloading or at least one file was not found

**Parameters**

- **torrent\_hash** – hash for torrent
- **file\_ids** – single file ID or a list.
- **priority** – priority for file(s) Properties: [https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-\(qBittorrent-4.1\)#set-file-priority](https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-(qBittorrent-4.1)#set-file-priority)

**Returns** None

**torrents\_file\_priority** (*torrent\_hash=None, file\_ids=None, priority=None, \*\*kwargs*)

Set priority for one or more files. (alias: torrents\_filePrio)

**Raises**

- **InvalidRequest400** – if priority is invalid or at least one file ID is not an integer
- **NotFound404Error** –
- **Conflict409** – if torrent metadata has not finished downloading or at least one file was not found

**Parameters**

- **torrent\_hash** – hash for torrent
- **file\_ids** – single file ID or a list.
- **priority** – priority for file(s) Properties: [https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-\(qBittorrent-4.1\)#set-file-priority](https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-(qBittorrent-4.1)#set-file-priority)

**Returns** None

**torrents\_files** (*torrent\_hash=None, \*\*kwargs*)

Retrieve individual torrent's files.

**Raises** **NotFound404Error** –

**Parameters** **torrent\_hash** – hash for torrent

**Returns** List of torrent's files Properties: [https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-\(qBittorrent-4.1\)#get-torrent-contents](https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-(qBittorrent-4.1)#get-torrent-contents)

**torrents\_increasePrio** (*torrent\_hashes=None, \*\*kwargs*)

Increase the priority of a torrent. Torrent Queueing must be enabled. (alias: torrents\_increasePrio)

**Raises** **Conflict409** –

**Parameters** **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.

**Returns** None

**torrents\_increase\_priority** (*torrent\_hashes=None, \*\*kwargs*)

Increase the priority of a torrent. Torrent Queuing must be enabled. (alias: torrents\_increasePrio)

**Raises Conflict409 –**

**Parameters torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.

**Returns** None

**torrents\_info** (*status\_filter=None, category=None, sort=None, reverse=None, limit=None, offset=None, torrent\_hashes=None, \*\*kwargs*)

Retrieves list of info for torrents. Note: hashes is available starting web API version 2.0.1

**Parameters**

- **status\_filter** – Filter list by all, downloading, completed, paused, active, inactive, resumed stalled, stalled\_uploading and stalled\_downloading added in Web API v2.4.1
- **category** – Filter list by category
- **sort** – Sort list by any property returned
- **reverse** – Reverse sorting
- **limit** – Limit length of list
- **offset** – Start of list (if < 0, offset from end of list)
- **torrent\_hashes** – Filter list by hash (separate multiple hashes with a ‘|’)

**Returns** List of torrents Properties: [https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-\(qBittorrent-4.1\)#get-torrent-list](https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-(qBittorrent-4.1)#get-torrent-list)

**torrents\_pause** (*torrent\_hashes=None, \*\*kwargs*)

Pause one or more torrents in qBittorrent.

**Parameters torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.

**Returns** None

**torrents\_pieceHashes** (*torrent\_hash=None, \*\*kwargs*)

Retrieve individual torrent’s pieces’ hashes. (alias: torrents\_pieceHashes)

**Raises NotFound404Error –**

**Parameters torrent\_hash** – hash for torrent

**Returns** List of torrent’s pieces’ hashes

**torrents\_pieceStates** (*torrent\_hash=None, \*\*kwargs*)

Retrieve individual torrent’s pieces’ states. (alias: torrents\_pieceStates)

**Raises NotFound404Error –**

**Parameters torrent\_hash** – hash for torrent

**Returns** list of torrent’s pieces’ states

**torrents\_piece\_hashes** (*torrent\_hash=None, \*\*kwargs*)

Retrieve individual torrent’s pieces’ hashes. (alias: torrents\_pieceHashes)

**Raises NotFound404Error –**

**Parameters torrent\_hash** – hash for torrent

**Returns** List of torrent’s pieces’ hashes

**torrents\_piece\_states** (*torrent\_hash=None, \*\*kwargs*)

Retrieve individual torrent's pieces' states. (alias: torrents\_pieceStates)

**Raises** *NotFound404Error* –

**Parameters** **torrent\_hash** – hash for torrent

**Returns** list of torrent's pieces' states

**torrents\_properties** (*torrent\_hash=None, \*\*kwargs*)

Retrieve individual torrent's properties.

**Raises** *NotFound404Error* –

**Parameters** **torrent\_hash** – hash for torrent

**Returns** Dictionary of torrent properties Properties: [https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-\(qBittorrent-4.1\)#get-torrent-generic-properties](https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-(qBittorrent-4.1)#get-torrent-generic-properties)

**torrents\_reannounce** (*torrent\_hashes=None, \*\*kwargs*)

Reannounce a torrent.

Note: torrents/reannounce not available web API version 2.0.2

**Parameters** **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.

**Returns** None

**torrents\_recheck** (*torrent\_hashes=None, \*\*kwargs*)

Recheck a torrent in qBittorrent.

**Parameters** **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.

**Returns** None

**torrents\_removeCategories** (*categories=None, \*\*kwargs*)

Delete one or more categories. (alias: torrents\_removeCategories)

**Parameters** **categories** – categories to delete

**Returns** None

**torrents\_removeTags** (*tags=None, torrent\_hashes=None, \*\*kwargs*)

Add one or more tags to one or more torrents. (alias: torrents\_removeTags)

**Parameters**

- **tags** – tag name or list of tags
- **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.

**Returns** None

**torrents\_removeTrackers** (*torrent\_hash=None, urls=None, \*\*kwargs*)

Remove trackers from a torrent. (alias: torrents\_removeTrackers)

**Raises**

- *NotFound404Error* –
- *Conflict409Error* –

**Parameters**

- **torrent\_hash** – hash for torrent

- **urls** – tracker urls to removed from torrent

**Returns** None

**torrents\_remove\_categories** (*categories=None, \*\*kwargs*)

Delete one or more categories. (alias: torrents\_removeCategories)

**Parameters** **categories** – categories to delete

**Returns** None

**torrents\_remove\_tags** (*tags=None, torrent\_hashes=None, \*\*kwargs*)

Add one or more tags to one or more torrents. (alias: torrents\_removeTags)

**Parameters**

- **tags** – tag name or list of tags
- **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.

**Returns** None

**torrents\_remove\_trackers** (*torrent\_hash=None, urls=None, \*\*kwargs*)

Remove trackers from a torrent. (alias: torrents\_removeTrackers)

**Raises**

- *NotFound404Error* –
- *Conflict409Error* –

**Parameters**

- **torrent\_hash** – hash for torrent
- **urls** – tracker urls to removed from torrent

**Returns** None

**torrents\_rename** (*torrent\_hash=None, new\_torrent\_name=None, \*\*kwargs*)

Rename a torrent.

**Raises** *NotFound404Error* –

**Parameters**

- **torrent\_hash** – hash for torrent
- **new\_torrent\_name** – new name for torrent

**Returns** None

**torrents\_renameFile** (*torrent\_hash=None, file\_id=None, new\_file\_name=None, \*\*kwargs*)

Rename a torrent file.

**Raises**

- *MissingRequiredParameters400Error* –
- *NotFound404Error* –
- *Conflict409Error* –

**Parameters**

- **torrent\_hash** – hash for torrent
- **file\_id** – id for file
- **new\_file\_name** – new name for file

**Returns** None

**torrents\_rename\_file** (*torrent\_hash=None, file\_id=None, new\_file\_name=None, \*\*kwargs*)  
Rename a torrent file.

**Raises**

- *MissingRequiredParameters400Error* –
- *NotFound404Error* –
- *Conflict409Error* –

**Parameters**

- **torrent\_hash** – hash for torrent
- **file\_id** – id for file
- **new\_file\_name** – new name for file

**Returns** None

**torrents\_resume** (*torrent\_hashes=None, \*\*kwargs*)  
Resume one or more torrents in qBittorrent.

**Parameters** **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.

**Returns** None

**torrents\_setAutoManagement** (*enable=None, torrent\_hashes=None, \*\*kwargs*)  
Enable or disable automatic torrent management for one or more torrents. (alias: torrents\_setAutoManagement)

**Parameters**

- **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.
- **enable** – True or False

**Returns** None

**torrents\_setCategory** (*category=None, torrent\_hashes=None, \*\*kwargs*)  
Set a category for one or more torrents. (alias: torrents\_setCategory)

**Raises** *Conflict409* – for bad category

**Parameters**

- **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.
- **category** – category to assign to torrent

**Returns** None

**torrents\_setDownloadLimit** (*limit=None, torrent\_hashes=None, \*\*kwargs*)  
Set the download limit for one or more torrents. (alias: torrents\_setDownloadLimit)

**Parameters**

- **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.
- **limit** – bytes/second (-1 sets the limit to infinity)

**Returns** None

**torrents\_setForceStart** (*enable=None, torrent\_hashes=None, \*\*kwargs*)  
Force start one or more torrents. (alias: torrents\_setForceStart)

### Parameters

- **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.
- **enable** – True or False (False makes this equivalent to torrents\_resume())

### Returns None

**torrents\_setLocation** (*location=None, torrent\_hashes=None, \*\*kwargs*)

Set location for torrents’s files. (alias: torrents\_setLocation)

### Raises

- **Forbidden403Error** – if the user doesn’t have permissions to write to the location
- **Conflict409** – if the directory cannot be created at the location

### Parameters

- **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.
- **location** – disk location to move torrent’s files

### Returns None

**torrents\_setShareLimits** (*ratio\_limit=None, seeding\_time\_limit=None, torrent\_hashes=None, \*\*kwargs*)

Set share limits for one or more torrents.

### Parameters

- **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.
- **ratio\_limit** – max ratio to seed a torrent. (-2 means use the global value and -1 is no limit)
- **seeding\_time\_limit** – minutes (-2 means use the global value and -1 is no limit)

### Returns None

**torrents\_setSuperSeeding** (*enable=None, torrent\_hashes=None, \*\*kwargs*)

Set one or more torrents as super seeding. (alias: torrents\_setSuperSeeding)

### Parameters

- **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.
- **enable** – True or False

### Returns

**torrents\_setUploadLimit** (*limit=None, torrent\_hashes=None, \*\*kwargs*)

Set the upload limit for one or more torrents. (alias: torrents\_setUploadLimit)

### Parameters

- **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.
- **limit** – bytes/second (-1 sets the limit to infinity)

### Returns None

**torrents\_set\_auto\_management** (*enable=None, torrent\_hashes=None, \*\*kwargs*)

Enable or disable automatic torrent management for one or more torrents. (alias: torrents\_setAutoManagement)

### Parameters

- **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.

- **enable** – True or False

**Returns** None

**torrents\_set\_category** (*category=None, torrent\_hashes=None, \*\*kwargs*)

Set a category for one or more torrents. (alias: torrents\_setCategory)

**Raises** **Conflict409** – for bad category

**Parameters**

- **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.
- **category** – category to assign to torrent

**Returns** None

**torrents\_set\_download\_limit** (*limit=None, torrent\_hashes=None, \*\*kwargs*)

Set the download limit for one or more torrents. (alias: torrents\_setDownloadLimit)

**Parameters**

- **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.
- **limit** – bytes/second (-1 sets the limit to infinity)

**Returns** None

**torrents\_set\_force\_start** (*enable=None, torrent\_hashes=None, \*\*kwargs*)

Force start one or more torrents. (alias: torrents\_setForceStart)

**Parameters**

- **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.
- **enable** – True or False (False makes this equivalent to torrents\_resume())

**Returns** None

**torrents\_set\_location** (*location=None, torrent\_hashes=None, \*\*kwargs*)

Set location for torrents’s files. (alias: torrents\_setLocation)

**Raises**

- **Forbidden403Error** – if the user doesn’t have permissions to write to the location
- **Conflict409** – if the directory cannot be created at the location

**Parameters**

- **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.
- **location** – disk location to move torrent’s files

**Returns** None

**torrents\_set\_share\_limits** (*ratio\_limit=None, seeding\_time\_limit=None, torrent\_hashes=None, \*\*kwargs*)

Set share limits for one or more torrents.

**Parameters**

- **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.
- **ratio\_limit** – max ratio to seed a torrent. (-2 means use the global value and -1 is no limit)
- **seeding\_time\_limit** – minutes (-2 means use the global value and -1 is no limit)

**Returns** None

**torrents\_set\_super\_seeding** (*enable=None, torrent\_hashes=None, \*\*kwargs*)

Set one or more torrents as super seeding. (alias: torrents\_setSuperSeeding)

**Parameters**

- **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.
- **enable** – True or False

**Returns**

**torrents\_set\_upload\_limit** (*limit=None, torrent\_hashes=None, \*\*kwargs*)

Set the upload limit for one or more torrents. (alias: torrents\_setUploadLimit)

**Parameters**

- **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.
- **limit** – bytes/second (-1 sets the limit to infinity)

**Returns** None

**torrents\_tags** (*\*\*kwargs*)

Retrieve all tag definitions.

**Returns** list of tags

**torrents\_toggleFirstLastPiecePrio** (*torrent\_hashes=None, \*\*kwargs*)

Toggle priority of first/last piece downloading. (alias: torrents\_toggleFirstLastPiecePrio)

**Parameters** **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.

**Returns** None

**torrents\_toggleSequentialDownload** (*torrent\_hashes=None, \*\*kwargs*)

Toggle sequential download for one or more torrents. (alias: torrents\_toggleSequentialDownload)

**Parameters** **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.

**Returns** None

**torrents\_toggle\_first\_last\_piece\_priority** (*torrent\_hashes=None, \*\*kwargs*)

Toggle priority of first/last piece downloading. (alias: torrents\_toggleFirstLastPiecePrio)

**Parameters** **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.

**Returns** None

**torrents\_toggle\_sequential\_download** (*torrent\_hashes=None, \*\*kwargs*)

Toggle sequential download for one or more torrents. (alias: torrents\_toggleSequentialDownload)

**Parameters** **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.

**Returns** None

**torrents\_topPrio** (*torrent\_hashes=None, \*\*kwargs*)

Set torrent as highest priority. Torrent Queueing must be enabled. (alias: torrents\_topPrio)

**Raises** **Conflict409** –

**Parameters** **torrent\_hashes** – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.

**Returns** None

**torrents\_top\_priority** (*torrent\_hashes=None, \*\*kwargs*)

Set torrent as highest priority. Torrent Queuing must be enabled. (alias: torrents\_topPrio)

**Raises** `Conflict409` –

**Parameters** `torrent_hashes` – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.

**Returns** None

**torrents\_trackers** (*torrent\_hash=None, \*\*kwargs*)

Retrieve individual torrent’s trackers.

**Raises** `NotFound404Error` –

**Parameters** `torrent_hash` – hash for torrent

**Returns** List of torrent’s trackers Properties: [https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-\(qBittorrent-4.1\)#get-torrent-trackers](https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-(qBittorrent-4.1)#get-torrent-trackers)

**torrents\_uploadLimit** (*torrent\_hashes=None, \*\*kwargs*)

Retrieve the upload limit for one or more torrents. (alias: torrents\_uploadLimit)

**Parameters** `torrent_hashes` – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.

**Returns** dictionary of limits

**torrents\_upload\_limit** (*torrent\_hashes=None, \*\*kwargs*)

Retrieve the upload limit for one or more torrents. (alias: torrents\_uploadLimit)

**Parameters** `torrent_hashes` – single torrent hash or list of torrent hashes. Or ‘all’ for all torrents.

**Returns** dictionary of limits

**torrents\_webseeds** (*torrent\_hash=None, \*\*kwargs*)

Retrieve individual torrent’s web seeds.

**Raises** `NotFound404Error` –

**Parameters** `torrent_hash` – hash for torrent

**Returns** List of torrent’s web seeds Properties: [https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-\(qBittorrent-4.1\)#get-torrent-web-seeds](https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-(qBittorrent-4.1)#get-torrent-web-seeds)

**class** qbittorrentapi.Torrents (*client*)

Allows interaction with the “Torrents” API endpoints.

### Usage

```
>>> from qbittorrentapi import Client
>>> client = Client(host='localhost:8080', username='admin', password='adminadmin')
>>> # this are all the same attributes that are available as named in the
>>> # endpoints or the more pythonic names in Client (with or without 'torrents_' prepended)
>>> torrent_list = client.torrents.info()
>>> torrent_list_active = client.torrents.info.active()
>>> torrent_list_active_partial = client.torrents.info.active(limit=100, offset=200)
```

(continues on next page)

(continued from previous page)

```
>>> torrent_list_downloading = client.torrents.info.download()
>>> # torrent looping
>>> for torrent in client.torrents.info.completed()
>>> # all torrents endpoints with a 'hashes' parameters support all
>>> # method to apply action to all torrents
>>> client.torrents.pause.all()
>>> client.torrents.resume.all()
>>> # or specify the individual hashes
>>> client.torrents.downloadLimit(torrent_hashes=['...', '...'])
```

**add**(*urls=None*, *torrent\_files=None*, *save\_path=None*, *cookie=None*, *category=None*,  
*is\_skip\_checking=None*, *is\_paused=None*, *is\_root\_folder=None*, *rename=None*, *up-  
load\_limit=None*, *download\_limit=None*, *use\_auto\_torrent\_management=None*,  
*is\_sequential\_download=None*, *is\_first\_last\_piece\_priority=None*, \*\**kwargs*)

**class qbittorrentapi.TorrentDictionary**(*data, client*)

Allows interaction with individual torrents via the “Torrents” API endpoints.

### Usage

```
>>> from qbittorrentapi import Client
>>> client = Client(host='localhost:8080', username='admin', password=
>>> # this are all the same attributes that are available as named in
>>> # the
>>> # endpoints or the more pythonic names in Client (with or
>>> # without 'transfer_' prepended)
>>> torrent = client.torrents.info()[0]
>>> torrent_hash = torrent.info.hash
>>> # Attributes without inputs and a return value are properties
>>> properties = torrent.properties
>>> trackers = torrent.trackers
>>> files = torrent.files
>>> # Action methods
>>> torrent.edit_tracker(original_url='...', new_url='...')
>>> torrent.remove_trackers(urls='http://127.0.0.2/')
>>> torrent.rename(new_torrent_name='...')
>>> torrent.resume()
>>> torrent.pause()
>>> torrent.recheck()
>>> torrent.torrents_top_priority()
>>> torrent.setLocation(location='/home/user/torrents/')
>>> torrent.setCategory(category='video')
```

**addTags**(*tags=None*, \*\**kwargs*)

**addTrackers**(*urls=None*, \*\**kwargs*)

**add\_tags**(*tags=None*, \*\**kwargs*)

**add\_trackers**(*urls=None*, \*\**kwargs*)

**bottomPrio**(\*\**kwargs*)

**bottom\_priority**(\*\**kwargs*)

**decreasePrio**(\*\**kwargs*)

**decrease\_priority**(\*\**kwargs*)

**delete**(*delete\_files=None*, \*\**kwargs*)

```
downloadLimit
download_limit
editTracker (orig_url=None, new_url=None, **kwargs)
edit_tracker (orig_url=None, new_url=None, **kwargs)
filePriority (file_ids=None, priority=None, **kwargs)
file_priority (file_ids=None, priority=None, **kwargs)
files
increasePrio (**kwargs)
increase_priority (**kwargs)
info
pause (**kwargs)
pieceHashes
pieceStates
piece_hashes
piece_states
properties
reannounce (**kwargs)
recheck (**kwargs)
removeTags (tags=None, **kwargs)
removeTrackers (urls=None, **kwargs)
remove_tags (tags=None, **kwargs)
remove_trackers (urls=None, **kwargs)
rename (new_name=None, **kwargs)
renameFile (file_id=None, new_file_name=None, **kwargs)
rename_file (file_id=None, new_file_name=None, **kwargs)
resume (**kwargs)
setAutoManagement (enable=None, **kwargs)
setCategory (category=None, **kwargs)
setDownloadLimit (limit=None, **kwargs)
setForceStart (enable=None, **kwargs)
setLocation (location=None, **kwargs)
setShareLimits (ratio_limit=None, seeding_time_limit=None, **kwargs)
setSuperSeeding (enable=None, **kwargs)
setUploadLimit (limit=None, **kwargs)
set_auto_management (enable=None, **kwargs)
set_category (category=None, **kwargs)
```

```
set_download_limit (limit=None, **kwargs)
set_force_start (enable=None, **kwargs)
set_location (location=None, **kwargs)
set_share_limits (ratio_limit=None, seeding_time_limit=None, **kwargs)
set_super_seeding (enable=None, **kwargs)
set_upload_limit (limit=None, **kwargs)
state_enum
    Returns the formalized Enumeration for Torrent State instead of the raw string.

sync_local ()
    Update local cache of torrent info.

toggleFirstLastPiecePrio (**kwargs)
toggleSequentialDownload (**kwargs)
toggle_first_last_piece_priority (**kwargs)
toggle_sequential_download (**kwargs)
topPrio (**kwargs)
top_priority (**kwargs)
trackers
uploadLimit
upload_limit
webseeds
```

## Transfer

```
class qbittorrentapi.TransferAPIMixIn (host='', port=None, username=None, password=None, **kwargs)
Implementation of all Transfer API methods

transfer_banPeers (peers=None, **kwargs)
    Ban one or more peers. (alias: transfer_banPeers)

    Parameters peers – one or more peers to ban. each peer should take the form ‘host:port’

    Returns None

transfer_ban_peers (peers=None, **kwargs)
    Ban one or more peers. (alias: transfer_banPeers)

    Parameters peers – one or more peers to ban. each peer should take the form ‘host:port’

    Returns None

transfer_downloadLimit (**kwargs)
    Retrieves download limit. 0 is unlimited. (alias: transfer_downloadLimit)

    Returns integer

transfer_download_limit (**kwargs)
    Retrieves download limit. 0 is unlimited. (alias: transfer_downloadLimit)

    Returns integer
```

**transfer\_info** (\*\*kwargs)

Retrieves the global transfer info usually found in qBittorrent status bar.

**Returns** dictionary of status items Properties: [https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-\(qBittorrent-4.1\)#get-global-transfer-info](https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-(qBittorrent-4.1)#get-global-transfer-info)

**transfer\_setDownloadLimit** (limit=None, \*\*kwargs)

Set the global download limit in bytes/second. (alias: transfer\_setDownloadLimit)

**Parameters** **limit** – download limit in bytes/second (0 or -1 for no limit)

**Returns** None

**transfer\_setUploadLimit** (limit=None, \*\*kwargs)

Set the global download limit in bytes/second. (alias: transfer\_setUploadLimit)

**Parameters** **limit** – upload limit in bytes/second (0 or -1 for no limit)

**Returns** None

**transfer\_set\_download\_limit** (limit=None, \*\*kwargs)

Set the global download limit in bytes/second. (alias: transfer\_setDownloadLimit)

**Parameters** **limit** – download limit in bytes/second (0 or -1 for no limit)

**Returns** None

**transfer\_set\_upload\_limit** (limit=None, \*\*kwargs)

Set the global download limit in bytes/second. (alias: transfer\_setUploadLimit)

**Parameters** **limit** – upload limit in bytes/second (0 or -1 for no limit)

**Returns** None

**transfer\_speedLimitsMode** (\*\*kwargs)

Retrieves whether alternative speed limits are enabled. (alias: transfer\_speedLimitMode)

**Returns** ‘1’ if alternative speed limits are currently enabled, ‘0’ otherwise

**transfer\_speed\_limits\_mode** (\*\*kwargs)

Retrieves whether alternative speed limits are enabled. (alias: transfer\_speedLimitMode)

**Returns** ‘1’ if alternative speed limits are currently enabled, ‘0’ otherwise

**transfer\_toggleSpeedLimitsMode** (intended\_state=None, \*\*kwargs)

Sets whether alternative speed limits are enabled. (alias: transfer\_toggleSpeedLimitsMode)

**Parameters** **intended\_state** – True to enable alt speed and False to disable. Leaving None will toggle the current state.

**Returns** None

**transfer\_toggle\_speed\_limits\_mode** (intended\_state=None, \*\*kwargs)

Sets whether alternative speed limits are enabled. (alias: transfer\_toggleSpeedLimitsMode)

**Parameters** **intended\_state** – True to enable alt speed and False to disable. Leaving None will toggle the current state.

**Returns** None

**transfer\_uploadLimit** (\*\*kwargs)

Retrieves upload limit. 0 is unlimited. (alias: transfer\_uploadLimit)

**Returns** integer

**transfer\_upload\_limit** (\*\*kwargs)

Retrieves upload limit. 0 is unlimited. (alias: transfer\_uploadLimit)

**Returns** integer

**class qbittorrentapi.Transfer(\*args, \*\*kwargs)**

Allows interaction with the “Transfer” API endpoints.

**Usage**

```
>>> from qbittorrentapi import Client
>>> client = Client(host='localhost:8080', username='admin', password=
    'adminadmin')
>>> # this are all the same attributes that are available as named in
    the
>>> # endpoints or the more pythonic names in Client (with or
    without 'transfer_' prepended)
>>> transfer_info = client.transfer.info
>>> # access and set download/upload limits as attributes
>>> dl_limit = client.transfer.download_limit
>>> # this updates qBittorrent in real-time
>>> client.transfer.download_limit = 1024000
>>> # update speed limits mode to alternate or not
>>> client.transfer.speedLimitsMode = True
```

**banPeers (peers=None, \*\*kwargs)**

**ban\_peers (peers=None, \*\*kwargs)**

**downloadLimit**

**download\_limit**

**info**

**setDownloadLimit (limit=None, \*\*kwargs)**

**setUpLoadLimit (limit=None, \*\*kwargs)**

**set\_download\_limit (limit=None, \*\*kwargs)**

**set\_upload\_limit (limit=None, \*\*kwargs)**

**speedLimitsMode**

**speed\_limits\_mode**

**toggleSpeedLimitsMode (intended\_state=None, \*\*kwargs)**

**toggle\_speed\_limits\_mode (intended\_state=None, \*\*kwargs)**

**uploadLimit**

**upload\_limit**

---

## Python Module Index

---

### q

`qbittorrentapi`, 38  
`qbittorrentapi.exceptions`, 7



---

## Index

---

### A

add() (*qbittorrentapi.Torrents method*), 36  
add\_feed() (*qbittorrentapi.RSS method*), 16  
add\_folder() (*qbittorrentapi.RSS method*), 16  
add\_tags() (*qbittorrentapi.TorrentDictionary method*), 36  
add\_trackers() (*qbittorrentapi.TorrentDictionary method*), 36  
addFeed() (*qbittorrentapi.RSS method*), 16  
addFolder() (*qbittorrentapi.RSS method*), 16  
addTags() (*qbittorrentapi.TorrentDictionary method*), 36  
addTrackers() (*qbittorrentapi.TorrentDictionary method*), 36  
ALLOCATING (*qbittorrentapi.TorrentStates attribute*), 21  
APIConnectionError, 7  
APIError, 7  
app\_build\_info() (*qbittorrentapi.AppAPIMixIn method*), 9  
app\_buildInfo() (*qbittorrentapi.AppAPIMixIn method*), 9  
app\_default\_save\_path() (*qbittorrentapi.AppAPIMixIn method*), 9  
app\_defaultSavePath() (*qbittorrentapi.AppAPIMixIn method*), 9  
app\_preferences() (*qbittorrentapi.AppAPIMixIn method*), 9  
app\_set\_preferences() (*qbittorrentapi.AppAPIMixIn method*), 9  
app\_setPreferences() (*qbittorrentapi.AppAPIMixIn method*), 9  
app\_shutdown() (*qbittorrentapi.AppAPIMixIn method*), 9  
app\_version() (*qbittorrentapi.AppAPIMixIn method*), 9  
app\_web\_api\_version() (*qbittorrentapi.AppAPIMixIn method*), 9  
app\_webapiVersion() (*qbittorrentapi.AppAPIMixIn method*), 9

*rentapi.AppAPIMixIn method*), 10  
AppAPIMixIn (*class in qbittorrentapi*), 9  
Application (*class in qbittorrentapi*), 10  
application (*qbittorrentapi.AppAPIMixIn attribute*), 10  
auth\_log\_in() (*qbittorrentapi.Request method*), 11  
auth\_log\_out() (*qbittorrentapi.Request method*), 11

### B

ban\_peers() (*qbittorrentapi.Transfer method*), 40  
banPeers() (*qbittorrentapi.Transfer method*), 40  
bottom\_priority() (*qbittorrentapi.TorrentDictionary method*), 36  
bottomPrio() (*qbittorrentapi.TorrentDictionary method*), 36  
build\_info (*qbittorrentapi.Application attribute*), 10  
buildInfo (*qbittorrentapi.Application attribute*), 10

### C

categories() (*qbittorrentapi.Search method*), 19  
CHECKING\_DOWNLOAD (*qbittorrentapi.TorrentStates attribute*), 21  
CHECKING\_RESUME\_DATA (*qbittorrentapi.TorrentStates attribute*), 21  
CHECKING\_UPLOAD (*qbittorrentapi.TorrentStates attribute*), 21  
Client (*class in qbittorrentapi*), 11  
Conflict409Error, 8

### D

decrease\_priority() (*qbittorrentapi.TorrentDictionary method*), 36  
decreasePrio() (*qbittorrentapi.TorrentDictionary method*), 36  
default\_save\_path (*qbittorrentapi.Application attribute*), 10  
defaultSavePath (*qbittorrentapi.Application attribute*), 10  
delete() (*qbittorrentapi.Search method*), 19

```
delete() (qbittorrentapi.TorrentDictionary method), 36
download_limit (qbittorrentapi.TorrentDictionary attribute), 37
download_limit (qbittorrentapi.Transfer attribute), 40
DOWNLOADING (qbittorrentapi.TorrentStates attribute), 21
downloadLimit (qbittorrentapi.TorrentDictionary attribute), 37
downloadLimit (qbittorrentapi.Transfer attribute), 40

E
edit_tracker() (qbittorrentapi.TorrentDictionary method), 37
editTracker() (qbittorrentapi.TorrentDictionary method), 37
enable_plugin() (qbittorrentapi.Search method), 19
enablePlugin() (qbittorrentapi.Search method), 19
ERROR (qbittorrentapi.TorrentStates attribute), 21

F
file_priority() (qbittorrentapi.TorrentDictionary method), 37
FileError, 7
filePriority() (qbittorrentapi.TorrentDictionary method), 37
files (qbittorrentapi.TorrentDictionary attribute), 37
Forbidden403Error, 8
FORCE_DOWNLOAD (qbittorrentapi.TorrentStates attribute), 21
FORCED_UPLOAD (qbittorrentapi.TorrentStates attribute), 21

H
HTTP400Error, 7
HTTP401Error, 7
HTTP403Error, 8
HTTP404Error, 8
HTTP409Error, 8
HTTP415Error, 8
HTTP4XXError, 7
HTTP500Error, 8
HTTP5XXError, 7
HTTPError, 7

I
increase_priority() (qbittorrentapi.TorrentDictionary method), 37
increasePrio() (qbittorrentapi.TorrentDictionary method), 37
info (qbittorrentapi.TorrentDictionary attribute), 37
info (qbittorrentapi.Transfer attribute), 40

L
install_plugin() (qbittorrentapi.Search method), 19
installPlugin() (qbittorrentapi.Search method), 19
InternalServerError500Error, 8
InvalidRequest400Error, 8
is_checking (qbittorrentapi.TorrentStates attribute), 21
is_complete (qbittorrentapi.TorrentStates attribute), 21
is_downloading (qbittorrentapi.TorrentStates attribute), 21
is_errorred (qbittorrentapi.TorrentStates attribute), 21
is_paused (qbittorrentapi.TorrentStates attribute), 21
is_uploading (qbittorrentapi.TorrentStates attribute), 22

M
Log (class in qbittorrentapi), 12
log_main() (qbittorrentapi.LogAPIMixIn method), 12
log_peers() (qbittorrentapi.LogAPIMixIn method), 12
LogAPIMixIn (class in qbittorrentapi), 12
LoginFailed, 7

N
NotFound404Error, 8

P
pause () (qbittorrentapi.TorrentDictionary method), 37
PAUSED_DOWNLOAD (qbittorrentapi.TorrentStates attribute), 21
PAUSED_UPLOAD (qbittorrentapi.TorrentStates attribute), 21
peers () (qbittorrentapi.Log method), 12
piece_hashes (qbittorrentapi.TorrentDictionary attribute), 37
```

piece_states ( <i>qbittorrentapi.TorrentDictionary attribute</i> ), 37	<i>rss_add_feed()</i> <i>method</i> ), 13	<i>(qbittorrentapi.RSSAPIMixIn</i>
pieceHashes ( <i>qbittorrentapi.TorrentDictionary attribute</i> ), 37	<i>rss_add_folder()</i> <i>method</i> ), 13	<i>(qbittorrentapi.RSSAPIMixIn</i>
pieceStates ( <i>qbittorrentapi.TorrentDictionary attribute</i> ), 37	<i>rss_addFeed()</i> <i>method</i> ), 12	<i>(qbittorrentapi.RSSAPIMixIn</i>
plugins ( <i>qbittorrentapi.Search attribute</i> ), 19	<i>rss_addFolder()</i> <i>method</i> ), 13	<i>(qbittorrentapi.RSSAPIMixIn</i>
preferences ( <i>qbittorrentapi.Application attribute</i> ), 10	<i>rss_items()</i> ( <i>qbittorrentapi.RSSAPIMixIn method</i> ), 13	
properties ( <i>qbittorrentapi.TorrentDictionary attribute</i> ), 37	<i>rss_mark_as_read()</i> ( <i>qbittorrentapi.RSSAPIMixIn method</i> ), 13	
<b>Q</b>	<i>rss_markAsRead()</i> ( <i>qbittorrentapi.RSSAPIMixIn method</i> ), 13	
qbittorrentapi ( <i>module</i> ), 9, 11, 12, 17, 19, 20, 22, 38	<i>rss_matching_articles()</i> ( <i>qbittorrentapi.RSSAPIMixIn method</i> ), 14	
qbittorrentapi.exceptions ( <i>module</i> ), 7	<i>rss_matchingArticles()</i> ( <i>qbittorrentapi.RSSAPIMixIn method</i> ), 14	
QUEUED_DOWNLOAD ( <i>qbittorrentapi.TorrentStates attribute</i> ), 21	<i>rss_move_item()</i> ( <i>qbittorrentapi.RSSAPIMixIn method</i> ), 14	
QUEUED_UPLOAD ( <i>qbittorrentapi.TorrentStates attribute</i> ), 21	<i>rss_moveItem()</i> ( <i>qbittorrentapi.RSSAPIMixIn method</i> ), 14	
<b>R</b>	<i>rss_refresh_item()</i> ( <i>qbittorrentapi.RSSAPIMixIn method</i> ), 14	
reannounce () ( <i>qbittorrentapi.TorrentDictionary method</i> ), 37	<i>rss_refreshItem()</i> ( <i>qbittorrentapi.RSSAPIMixIn method</i> ), 14	
recheck () ( <i>qbittorrentapi.TorrentDictionary method</i> ), 37	<i>rss_remove_item()</i> ( <i>qbittorrentapi.RSSAPIMixIn method</i> ), 15	
refresh_item () ( <i>qbittorrentapi.RSS method</i> ), 16	<i>rss_remove_rule()</i> ( <i>qbittorrentapi.RSSAPIMixIn method</i> ), 15	
refreshItem () ( <i>qbittorrentapi.RSS method</i> ), 16	<i>rss_removeItem()</i> ( <i>qbittorrentapi.RSSAPIMixIn method</i> ), 14	
remove_item () ( <i>qbittorrentapi.RSS method</i> ), 16	<i>rss_removeRule()</i> ( <i>qbittorrentapi.RSSAPIMixIn method</i> ), 14	
remove_rule () ( <i>qbittorrentapi.RSS method</i> ), 16	<i>rss_rename_rule()</i> ( <i>qbittorrentapi.RSSAPIMixIn method</i> ), 15	
remove_tags () ( <i>qbittorrentapi.TorrentDictionary method</i> ), 37	<i>rss_renameRule()</i> ( <i>qbittorrentapi.RSSAPIMixIn method</i> ), 15	
remove_trackers () ( <i>qbittorrentapi.TorrentDictionary method</i> ), 37	<i>rss_rules()</i> ( <i>qbittorrentapi.RSSAPIMixIn method</i> ), 15	
removeItem () ( <i>qbittorrentapi.RSS method</i> ), 16	<i>rss_set_rule()</i> ( <i>qbittorrentapi.RSSAPIMixIn method</i> ), 15	
removeRule () ( <i>qbittorrentapi.RSS method</i> ), 16	<i>rss_setRule()</i> ( <i>qbittorrentapi.RSSAPIMixIn method</i> ), 15	
removeTags () ( <i>qbittorrentapi.TorrentDictionary method</i> ), 37	<i>RSSAPIMixIn</i> ( <i>class in qbittorrentapi</i> ), 12	
removeTrackers () ( <i>qbittorrentapi.TorrentDictionary method</i> ), 37	<i>rules</i> ( <i>qbittorrentapi.RSS attribute</i> ), 16	
rename () ( <i>qbittorrentapi.TorrentDictionary method</i> ), 37		
rename_file () ( <i>qbittorrentapi.TorrentDictionary method</i> ), 37		
rename_rule () ( <i>qbittorrentapi.RSS method</i> ), 16		
renameFile () ( <i>qbittorrentapi.TorrentDictionary method</i> ), 37		
renameRule () ( <i>qbittorrentapi.RSS method</i> ), 16		
Request ( <i>class in qbittorrentapi</i> ), 11	<b>S</b>	
results () ( <i>qbittorrentapi.Search method</i> ), 19	Search ( <i>class in qbittorrentapi</i> ), 19	
resume () ( <i>qbittorrentapi.TorrentDictionary method</i> ), 37	search_categories () ( <i>qbittorrentapi.SearchAPIMixIn method</i> ), 17	
RSS ( <i>class in qbittorrentapi</i> ), 16	search_delete () ( <i>qbittorrentapi.SearchAPIMixIn method</i> ), 17	

search_enable_plugin() ( <i>qbittor-rentapi.SearchAPIMixIn method</i> ), 17	( <i>qbittor-rentapi.TorrentDictionary method</i> ), 37
search_enablePlugin() ( <i>qbittor-rentapi.SearchAPIMixIn method</i> ), 17	( <i>qbittor-rentapi.TorrentDictionary method</i> ), 40
search_install_plugin() ( <i>qbittor-rentapi.SearchAPIMixIn method</i> ), 17	( <i>qbittor-rentapi.TorrentDictionary method</i> ), 37
search_installPlugin() ( <i>qbittor-rentapi.SearchAPIMixIn method</i> ), 17	( <i>qbittor-rentapi.TorrentDictionary method</i> ), 37
search_plugins() ( <i>qbittorrentapi.SearchAPIMixIn method</i> ), 17	( <i>qbittorrentapi.Application method</i> ), 10
search_results() ( <i>qbittorrentapi.SearchAPIMixIn method</i> ), 17	( <i>qbittorrentapi.RSS method</i> ), 16
search_start() ( <i>qbittorrentapi.SearchAPIMixIn method</i> ), 18	( <i>qbittorrentapi.TorrentDictionary method</i> ), 37
search_status() ( <i>qbittorrentapi.SearchAPIMixIn method</i> ), 18	( <i>qbittorrentapi.TorrentDictionary method</i> ), 37
search_stop() ( <i>qbittorrentapi.SearchAPIMixIn method</i> ), 18	( <i>qbittorrentapi.TorrentDictionary method</i> ), 37
search_uninstall_plugin() ( <i>qbittor-rentapi.SearchAPIMixIn method</i> ), 18	( <i>qbittorrentapi.TorrentDictionary method</i> ), 40
search_uninstallPlugin() ( <i>qbittor-rentapi.SearchAPIMixIn method</i> ), 18	( <i>qbittorrentapi.TorrentDictionary method</i> ), 40
search_update_plugins() ( <i>qbittor-rentapi.SearchAPIMixIn method</i> ), 18	( <i>qbittorrentapi.TorrentDictionary method</i> ), 40
search_updatePlugins() ( <i>qbittor-rentapi.SearchAPIMixIn method</i> ), 18	( <i>qbittorrentapi.TorrentDictionary method</i> ), 40
SearchAPIMixIn ( <i>class in qbittorrentapi</i> ), 17	
set_auto_management() ( <i>qbittor-rentapi.TorrentDictionary method</i> ), 37	
set_category() ( <i>qbittorrentapi.TorrentDictionary method</i> ), 37	
set_download_limit() ( <i>qbittor-rentapi.TorrentDictionary method</i> ), 37	
set_download_limit() ( <i>qbittorrentapi.Transfer method</i> ), 40	
set_force_start() ( <i>qbittor-rentapi.TorrentDictionary method</i> ), 38	
set_location() ( <i>qbittorrentapi.TorrentDictionary method</i> ), 38	
set_preferences() ( <i>qbittorrentapi.Application method</i> ), 10	
set_rule() ( <i>qbittorrentapi.RSS method</i> ), 16	
set_share_limits() ( <i>qbittor-rentapi.TorrentDictionary method</i> ), 38	
set_super_seeding() ( <i>qbittor-rentapi.TorrentDictionary method</i> ), 38	
set_upload_limit() ( <i>qbittor-rentapi.TorrentDictionary method</i> ), 38	
set_upload_limit() ( <i>qbittorrentapi.Transfer method</i> ), 40	
setAutoManagement() ( <i>qbittor-rentapi.TorrentDictionary method</i> ), 37	
setCategory() ( <i>qbittorrentapi.TorrentDictionary method</i> ), 37	
setDownloadLimit() ( <i>qbittor-rentapi.TorrentDictionary method</i> ), 37	
setDownloadLimit() ( <i>qbittorrentapi.Transfer method</i> ), 40	
setForceStart() ( <i>qbittorrentapi.TorrentDictionary method</i> ), 37	
setLocation() ( <i>qbittorrentapi.TorrentDictionary method</i> ), 37	
setPreferences() ( <i>qbittorrentapi.Application method</i> ), 10	
setRule() ( <i>qbittorrentapi.RSS method</i> ), 16	
setShareLimits() ( <i>qbittor-rentapi.TorrentDictionary method</i> ), 37	
setSuperSeeding() ( <i>qbittor-rentapi.TorrentDictionary method</i> ), 37	
setUploadLimit() ( <i>qbittorrentapi.Transfer method</i> ), 37	
setUploadLimit() ( <i>qbittorrentapi.Transfer method</i> ), 40	
shutdown() ( <i>qbittorrentapi.Application method</i> ), 10	
speed_limits_mode() ( <i>qbittorrentapi.Transfer attribute</i> ), 40	
speedLimitsMode() ( <i>qbittorrentapi.Transfer attribute</i> ), 40	
STALLED_DOWNLOAD ( <i>qbittorrentapi.TorrentStates attribute</i> ), 21	
STALLED_UPLOAD ( <i>qbittorrentapi.TorrentStates attribute</i> ), 21	
start() ( <i>qbittorrentapi.Search method</i> ), 19	
state_enum() ( <i>qbittorrentapi.TorrentDictionary attribute</i> ), 38	
status() ( <i>qbittorrentapi.Search method</i> ), 19	
stop() ( <i>qbittorrentapi.Search method</i> ), 19	
Sync ( <i>class in qbittorrentapi</i> ), 20	
sync_local() ( <i>qbittorrentapi.TorrentDictionary method</i> ), 38	
sync_maindata() ( <i>qbittorrentapi.SyncAPIMixIn method</i> ), 19	
sync_torrent_peers() ( <i>qbittor-rentapi.SyncAPIMixIn method</i> ), 20	
sync_torrentPeers() ( <i>qbittor-rentapi.SyncAPIMixIn method</i> ), 20	
SyncAPIMixIn ( <i>class in qbittorrentapi</i> ), 19	

## T

toggle_first_last_piece_priority() ( <i>qbittorrentapi.TorrentDictionary method</i> ), 38
toggle_sequential_download() ( <i>qbittor-rentapi.TorrentDictionary method</i> ), 38
toggle_speed_limits_mode() ( <i>qbittor-rentapi.Transfer method</i> ), 40
toggleFirstLastPiecePrio() ( <i>qbittor-rentapi.TorrentDictionary method</i> ), 38

```

toggleSequentialDownload()           (qbittor-
    rentapi.TorrentDictionary method), 38
toggleSpeedLimitsMode()            (qbittor-
    rentapi.Transfer method), 40
top_priority()   (qbittorrentapi.TorrentDictionary
    method), 38
topPrio()        (qbittorrentapi.TorrentDictionary method),
    38
TorrentDictionary (class in qbittorrentapi), 36
TorrentFileError, 7
TorrentFileNotFoundException, 7
TorrentFilePermissionError, 7
Torrents (class in qbittorrentapi), 35
torrents_add()     (qbittorrentapi.TorrentsAPIMixIn
    method), 22
torrents_add_peers()          (qbittor-
    rentapi.TorrentsAPIMixIn method), 23
torrents_add_tags()           (qbittor-
    rentapi.TorrentsAPIMixIn method), 23
torrents_add_trackers()        (qbittor-
    rentapi.TorrentsAPIMixIn method), 23
torrents_addPeers()           (qbittor-
    rentapi.TorrentsAPIMixIn method), 23
torrents_addTags()            (qbittor-
    rentapi.TorrentsAPIMixIn method), 23
torrents_addTrackers()         (qbittor-
    rentapi.TorrentsAPIMixIn method), 23
torrents_bottom_priority()      (qbittor-
    rentapi.TorrentsAPIMixIn method), 24
torrents_bottomPrio()          (qbittor-
    rentapi.TorrentsAPIMixIn method), 24
torrents_categories()          (qbittor-
    rentapi.TorrentsAPIMixIn method), 24
torrents_create_category()     (qbittor-
    rentapi.TorrentsAPIMixIn method), 24
torrents_create_tags()         (qbittor-
    rentapi.TorrentsAPIMixIn method), 25
torrents_createCategory()      (qbittor-
    rentapi.TorrentsAPIMixIn method), 24
torrents_createTags()          (qbittor-
    rentapi.TorrentsAPIMixIn method), 24
torrents_decrease_priority()    (qbittor-
    rentapi.TorrentsAPIMixIn method), 25
torrents_decreasePrio()         (qbittor-
    rentapi.TorrentsAPIMixIn method), 25
torrents_delete()               (qbittor-
    rentapi.TorrentsAPIMixIn method), 25
torrents_delete_tags()          (qbittor-
    rentapi.TorrentsAPIMixIn method), 25
torrents_deleteTags()           (qbittor-
    rentapi.TorrentsAPIMixIn method), 25
torrents_download_limit()       (qbittor-
    rentapi.TorrentsAPIMixIn method), 25
torrents_downloadLimit()        (qbittor-
    rentapi.TorrentsAPIMixIn method), 25
rentapi.TorrentsAPIMixIn method), 25
torrents_edit_category()        (qbittor-
    rentapi.TorrentsAPIMixIn method), 26
torrents_edit_tracker()         (qbittor-
    rentapi.TorrentsAPIMixIn method), 26
torrents_editCategory()         (qbittor-
    rentapi.TorrentsAPIMixIn method), 25
torrents_editTracker()          (qbittor-
    rentapi.TorrentsAPIMixIn method), 26
torrents_file_priority()        (qbittor-
    rentapi.TorrentsAPIMixIn method), 27
torrents_filePrio()             (qbittor-
    rentapi.TorrentsAPIMixIn method), 27
torrents_files()                (qbittor-
    rentapi.TorrentsAPIMixIn method), 27
torrents_increase_priority()    (qbittor-
    rentapi.TorrentsAPIMixIn method), 27
torrents_increasePrio()          (qbittor-
    rentapi.TorrentsAPIMixIn method), 27
torrents_info()                 (qbittorrentapi.TorrentsAPIMixIn
    method), 28
torrents_pause()                (qbittor-
    rentapi.TorrentsAPIMixIn method), 28
torrents_piece_hashes()         (qbittor-
    rentapi.TorrentsAPIMixIn method), 28
torrents_piece_states()         (qbittor-
    rentapi.TorrentsAPIMixIn method), 28
torrents_pieceHashes()          (qbittor-
    rentapi.TorrentsAPIMixIn method), 28
torrents_pieceStates()          (qbittor-
    rentapi.TorrentsAPIMixIn method), 28
torrents_properties()           (qbittor-
    rentapi.TorrentsAPIMixIn method), 29
torrents_reannounce()           (qbittor-
    rentapi.TorrentsAPIMixIn method), 29
torrents_recheck()               (qbittor-
    rentapi.TorrentsAPIMixIn method), 29
torrents_remove_categories()    (qbittor-
    rentapi.TorrentsAPIMixIn method), 30
torrents_remove_tags()          (qbittor-
    rentapi.TorrentsAPIMixIn method), 30
torrents_remove_trackers()      (qbittor-
    rentapi.TorrentsAPIMixIn method), 30
torrents_removeCategories()     (qbittor-
    rentapi.TorrentsAPIMixIn method), 29
torrents_removeTags()            (qbittor-
    rentapi.TorrentsAPIMixIn method), 29
torrents_removeTrackers()        (qbittor-
    rentapi.TorrentsAPIMixIn method), 29
torrents_rename()                (qbittor-
    rentapi.TorrentsAPIMixIn method), 30
torrents_rename_file()           (qbittor-
    rentapi.TorrentsAPIMixIn method), 31
torrents_renameFile()            (qbittor-
    rentapi.TorrentsAPIMixIn method), 31

```

```

rentapi.TorrentsAPIMixIn method), 30
torrents_resume() (qbittor- rentapi.TorrentsAPIMixIn method), 35
rentapi.TorrentsAPIMixIn method), 31
torrents_set_auto_management() (qbittor- rentapi.TorrentsAPIMixIn method), 22
rentapi.TorrentsAPIMixIn method), 32
torrents_set_category() (qbittor- TorrentStates (class in qbittorrentapi), 20
rentapi.TorrentsAPIMixIn method), 33
torrents_set_download_limit() (qbittor- trackers (qbittorrentapi.TorrentDictionary attribute),
rentapi.TorrentsAPIMixIn method), 33 38
torrents_set_force_start() (qbittor- Transfer (class in qbittorrentapi), 40
rentapi.TorrentsAPIMixIn method), 33
torrents_set_share_limits() (qbittor- transfer_ban_peers() (qbittor-
rentapi.TorrentsAPIMixIn method), 33 rentapi.TransferAPIMixIn method), 38
torrents_set_super_seeding() (qbittor- transfer_banPeers() (qbittor-
rentapi.TorrentsAPIMixIn method), 33 rentapi.TransferAPIMixIn method), 38
torrents_set_upload_limit() (qbittor- transfer_download_limit() (qbittor-
rentapi.TorrentsAPIMixIn method), 34 rentapi.TransferAPIMixIn method), 38
torrents_setAutoManagement() (qbittor- transfer_downloadLimit() (qbittor-
rentapi.TorrentsAPIMixIn method), 31 rentapi.TransferAPIMixIn method), 38
torrents_setCategory() (qbittor- transfer_info() (qbittorrentapi.TransferAPIMixIn
rentapi.TorrentsAPIMixIn method), 31 method), 38
torrents_setDownloadLimit() (qbittor- transfer_set_download_limit() (qbittor-
rentapi.TorrentsAPIMixIn method), 31 rentapi.TransferAPIMixIn method), 39
torrents_setForceStart() (qbittor- transfer_set_upload_limit() (qbittor-
rentapi.TorrentsAPIMixIn method), 31 rentapi.TransferAPIMixIn method), 39
torrents_setLocation() (qbittor- transfer_setDownloadLimit() (qbittor-
rentapi.TorrentsAPIMixIn method), 32 rentapi.TransferAPIMixIn method), 39
torrents_setShareLimits() (qbittor- transfer_setUploadLimit() (qbittor-
rentapi.TorrentsAPIMixIn method), 32 rentapi.TransferAPIMixIn method), 39
torrents_setSuperSeeding() (qbittor- transfer_speed_limits_mode() (qbittor-
rentapi.TorrentsAPIMixIn method), 32 rentapi.TransferAPIMixIn method), 39
torrents_setUploadLimit() (qbittor- transfer_toggle_speed_limits_mode()
rentapi.TorrentsAPIMixIn method), 32 (qbittorrentapi.TransferAPIMixIn method), 39
torrents_tags() (qbittorrentapi.TorrentsAPIMixIn transfer_toggleSpeedLimitsMode() (qbittor-
method), 34 rentapi.TransferAPIMixIn method), 39
torrents_toggle_first_last_piece_priority() TransferAPIMixIn (class in qbittorrentapi), 38
(qbittorrentapi.TorrentsAPIMixIn method), 34
torrents_toggle_sequential_download() U
(qbittorrentapi.TorrentsAPIMixIn method), 34
torrents_toggleFirstLastPiecePrio() Unauthorized401Error, 8
(qbittorrentapi.TorrentsAPIMixIn method), 34
torrents_toggleSequentialDownload() uninstall_plugin() (qbittorrentapi.Search
(qbittorrentapi.TorrentsAPIMixIn method), 34 method), 19
torrents_top_priority() (qbittor- uninstallPlugin() (qbittorrentapi.Search
rentapi.TorrentsAPIMixIn method), 35 method), 19
torrents_topPrio() (qbittor- UNKNOWN (qbittorrentapi.TorrentStates attribute), 21
rentapi.TorrentsAPIMixIn method), 34 UnsupportedMediaType415Error, 8
torrents_trackers() (qbittor- update_plugins() (qbittorrentapi.Search method),
rentapi.TorrentsAPIMixIn method), 35 19
torrents_upload_limit() (qbittor- updatePlugins() (qbittorrentapi.Search method),
rentapi.TorrentsAPIMixIn method), 35 19
torrents_uploadLimit() (qbittor- upload_limit (qbittorrentapi.TorrentDictionary at-
tribut), 38

```

upload\_limit (*qbittorrentapi.Transfer attribute*), 40  
UPLOADING (*qbittorrentapi.TorrentStates attribute*), 21  
uploadLimit (*qbittorrentapi.TorrentDictionary attribute*), 38  
uploadLimit (*qbittorrentapi.Transfer attribute*), 40

## V

version (*qbittorrentapi.Application attribute*), 10

## W

web\_api\_version (*qbittorrentapi.Application attribute*), 10  
webapiVersion (*qbittorrentapi.Application attribute*), 10  
webseeds (*qbittorrentapi.TorrentDictionary attribute*), 38