
qbittorrent-api

Release v2023.7.51

Russell Martin

Jul 13, 2023

CONTENTS

1	Introduction	1
	Python Module Index	57
	Index	59

INTRODUCTION

Python client implementation for qBittorrent Web API.

Currently supports qBittorrent [v4.5.4](#) (Web API v2.8.19) released on June 17, 2023.

1.1 Features

- The entire qBittorrent [Web API](#) is implemented.
- qBittorrent version checking for an endpoint's existence/features is automatically handled.
- All Python versions are supported.
- If the authentication cookie expires, a new one is automatically requested in line with any API call.

1.2 Installation

- Install via pip from [PyPI](#):

```
python -m pip install qbittorrent-api
```

- Install a specific release (e.g. [v2022.8.34](#)):

```
python -m pip install qbittorrent-api==2022.8.34
```

- Install direct from [main](#):

```
pip install git+https://github.com/rmartin16/qbittorrent-api.git@main#egg=qbittorrent-api
```

- Enable WebUI in qBittorrent: Tools -> Preferences -> Web UI
- If the Web API will be exposed to the Internet, follow the [recommendations](#).

1.3 Getting Started

```
import qbittorrentapi

# instantiate a Client using the appropriate WebUI configuration
conn_info = dict(
    host="localhost",
    port=8080,
    username="admin",
    password="adminadmin",
)
qbt_client = qbittorrentapi.Client(**conn_info)

# the Client will automatically acquire/maintain a logged-in state
# in line with any request. therefore, this is not strictly necessary;
# however, you may want to test the provided login credentials.
try:
    qbt_client.auth_log_in()
except qbittorrentapi.LoginFailed as e:
    print(e)

# if the Client will not be long-lived or many Clients may be created
# in a relatively short amount of time, be sure to log out:
qbt_client.auth_log_out()

# or use a context manager:
with qbittorrentapi.Client(**conn_info) as qbt_client:
    if qbt_client.torrents_add(urls="...") != "Ok.":
        raise Exception("Failed to add torrent.")

# display qBittorrent info
print(f"qBittorrent: {qbt_client.app.version}")
print(f"qBittorrent Web API: {qbt_client.app.web_api_version}")
for k, v in qbt_client.app.build_info.items():
    print(f"{k}: {v}")

# retrieve and show all torrents
for torrent in qbt_client.torrents_info():
    print(f"{torrent.hash[-6:]}: {torrent.name} ({torrent.state})")

# pause all torrents
qbt_client.torrents.pause.all()
```

1.4 Usage

First, the Web API endpoints are organized in to eight namespaces.

- Authentication (auth)
- Application (app)
- Log (log)
- Sync (sync)
- Transfer (transfer)
- Torrent Management (torrents)
- RSS (rss)
- Search (search)

Second, this client has two modes of interaction with the qBittorrent Web API.

Each Web API endpoint is implemented one-to-one as a method of the instantiated client.

```
import qbittorrentapi
qbt_client = qbittorrentapi.Client(host='localhost:8080', username='admin', password=
↳ 'adminadmin')
qbt_client.app_version()
qbt_client.rss_rules()
qbt_client.torrents_info()
qbt_client.torrents_resume(torrent_hashes='...')
# and so on
```

However, a more robust interface to the endpoints is available via each namespace. This is intended to provide a more seamless and intuitive interface to the Web API.

```
import qbittorrentapi
qbt_client = qbittorrentapi.Client(host='localhost:8080', username='admin', password=
↳ 'adminadmin')
# changing a preference
is_dht_enabled = qbt_client.app.preferences.dht
qbt_client.app.preferences = dict(dht=not is_dht_enabled)
# stopping all torrents
qbt_client.torrents.pause.all()
# retrieve different views of the log
qbt_client.log.main.warning()
qbt_client.log.main.normal()
```

Finally, some of the objects returned by the client support methods of their own. This is most pronounced for torrents themselves.

```
import qbittorrentapi
qbt_client = qbittorrentapi.Client(host='localhost:8080', username='admin', password=
↳ 'adminadmin')

for torrent in qbt_client.torrents.info.active():
    torrent.set_location(location='/home/user/torrents/')

```

(continues on next page)

(continued from previous page)

```
torrent.reannounce()  
torrent.upload_limit = -1
```

1.4.1 Introduction

Python client implementation for qBittorrent Web API.

Currently supports qBittorrent [v4.5.4](#) (Web API v2.8.19) released on June 17, 2023.

Features

- The entire qBittorrent [Web API](#) is implemented.
- qBittorrent version checking for an endpoint's existence/features is automatically handled.
- All Python versions are supported.
- If the authentication cookie expires, a new one is automatically requested in line with any API call.

Installation

- Install via pip from [PyPI](#):

```
python -m pip install qbittorrent-api
```

- Install a specific release (e.g. [v2022.8.34](#)):

```
python -m pip install qbittorrent-api==2022.8.34
```

- Install direct from main:

```
pip install git+https://github.com/rmartin16/qbittorrent-api.git@main#egg=qbittorrent-api
```

- Enable WebUI in qBittorrent: Tools -> Preferences -> Web UI
- If the Web API will be exposed to the Internet, follow the [recommendations](#).

Getting Started

```
import qbittorrentapi  
  
# instantiate a Client using the appropriate WebUI configuration  
conn_info = dict(  
    host="localhost",  
    port=8080,  
    username="admin",  
    password="adminadmin",  
)
```

(continues on next page)

(continued from previous page)

```

qbt_client = qbittorrentapi.Client(**conn_info)

# the Client will automatically acquire/maintain a logged-in state
# in line with any request. therefore, this is not strictly necessary;
# however, you may want to test the provided login credentials.
try:
    qbt_client.auth_log_in()
except qbittorrentapi.LoginFailed as e:
    print(e)

# if the Client will not be long-lived or many Clients may be created
# in a relatively short amount of time, be sure to log out:
qbt_client.auth_log_out()

# or use a context manager:
with qbittorrentapi.Client(**conn_info) as qbt_client:
    if qbt_client.torrents_add(urls="...") != "Ok.":
        raise Exception("Failed to add torrent.")

# display qBittorrent info
print(f"qBittorrent: {qbt_client.app.version}")
print(f"qBittorrent Web API: {qbt_client.app.web_api_version}")
for k, v in qbt_client.app.build_info.items():
    print(f"{k}: {v}")

# retrieve and show all torrents
for torrent in qbt_client.torrents_info():
    print(f"{torrent.hash[-6:]}: {torrent.name} ({torrent.state})")

# pause all torrents
qbt_client.torrents.pause.all()

```

Usage

First, the Web API endpoints are organized in to eight namespaces.

- Authentication (auth)
- Application (app)
- Log (log)
- Sync (sync)
- Transfer (transfer)
- Torrent Management (torrents)
- RSS (rss)
- Search (search)

Second, this client has two modes of interaction with the qBittorrent Web API.

Each Web API endpoint is implemented one-to-one as a method of the instantiated client.

```
import qbittorrentapi
qbt_client = qbittorrentapi.Client(host='localhost:8080', username='admin', password=
↳ 'adminadmin')
qbt_client.app_version()
qbt_client.rss_rules()
qbt_client.torrents_info()
qbt_client.torrents_resume(torrent_hashes='...')
# and so on
```

However, a more robust interface to the endpoints is available via each namespace. This is intended to provide a more seamless and intuitive interface to the Web API.

```
import qbittorrentapi
qbt_client = qbittorrentapi.Client(host='localhost:8080', username='admin', password=
↳ 'adminadmin')
# changing a preference
is_dht_enabled = qbt_client.app.preferences.dht
qbt_client.app.preferences = dict(dht=not is_dht_enabled)
# stopping all torrents
qbt_client.torrents.pause.all()
# retrieve different views of the log
qbt_client.log.main.warning()
qbt_client.log.main.normal()
```

Finally, some of the objects returned by the client support methods of their own. This is most pronounced for torrents themselves.

```
import qbittorrentapi
qbt_client = qbittorrentapi.Client(host='localhost:8080', username='admin', password=
↳ 'adminadmin')

for torrent in qbt_client.torrents.info.active():
    torrent.set_location(location='/home/user/torrents/')
    torrent.reannounce()
    torrent.upload_limit = -1
```

1.4.2 Behavior & Configuration

Host, Username and Password

- The authentication credentials can be provided when instantiating *Client*:

```
qbt_client = Client(host="localhost:8080", username='...', password='...')
```

- The credentials can also be specified after *Client* is created but calling *auth_log_in()* is not strictly necessary to authenticate the client; this will happen automatically for any API request.

```
qbt_client.auth_log_in(username='...', password='...')
```

- Alternatively, the credentials can be specified in environment variables:
 - QBITTORRENTAPI_HOST
 - QBITTORRENTAPI_USERNAME

– QBITTORRENTAPI_PASSWORD

qBittorrent Session Management

- Any time a connection is established with qBittorrent, it instantiates a session to manage authentication for all subsequent API requests.
- This client will transparently manage sessions by ensuring the client is always logged in in-line with any API request including requesting a new session upon expiration of an existing session.
- However, each new *Client* instantiation will create a new session in qBittorrent.
- Therefore, if many *Client* instances will be created be sure to call *auth_log_out* for each instance or use a context manager.
- Otherwise, qBittorrent may experience abnormally high memory usage.

```
with qbittorrentapi.Client(**conn_info) as qbt_client:
    if qbt_client.torrents_add(urls="...") != "Ok.":
        raise Exception("Failed to add torrent.")
```

Untrusted WebUI Certificate

- qBittorrent allows you to configure HTTPS with an untrusted certificate; this commonly includes self-signed certificates.
- When using such a certificate, instantiate *Client* with `VERIFY_WEBUI_CERTIFICATE=False` or set environment variable `QBITTORRENTAPI_DO_NOT_VERIFY_WEBUI_CERTIFICATE` to a non-null value.
- Failure to do this for will cause connections to qBittorrent to fail.
- As a word of caution, doing this actually does turn off certificate verification. Therefore, for instance, potential man-in-the-middle attacks will not be detected and reported (since the error is suppressed). However, the connection will remain encrypted.

```
qbt_client = Client(..., VERIFY_WEBUI_CERTIFICATE=False)
```

Requests Configuration

- The *Requests* package is used to issue HTTP requests to qBittorrent to facilitate this API.
- Much of *Requests* configuration for making HTTP requests can be controlled with parameters passed along with the request payload.
- For instance, HTTP Basic Authorization credentials can be provided via *auth*, timeouts via *timeout*, or Cookies via *cookies*. See *Requests documentation* for full details.
- These parameters are exposed here in two ways; the examples below tell *Requests* to use a connect timeout of 3.1 seconds and a read timeout of 30 seconds.
- When you instantiate *Client*, you can specify the parameters to use in all HTTP requests to qBittorrent:

```
qbt_client = Client(..., REQUESTS_ARGS={'timeout': (3.1, 30)})
```

- Alternatively, parameters can be specified for individual requests:

```
qbt_client.torrents_info(..., requests_args={'timeout': (3.1, 30)})
```

Additional HTTP Headers

- For consistency, HTTP Headers can be specified using the method above; for backwards compatibility, the methods below are supported as well.
- Either way, these additional headers will be incorporated (using clobbering) into the rest of the headers to be sent.
- To send a custom HTTP header in all requests made from an instantiated client, declare them during instantiation:

```
qbt_client = Client(..., EXTRA_HEADERS={'X-My-Fav-Header': 'header value'})
```

- Alternatively, you can send custom headers in individual requests:

```
qbt_client.torrents.add(..., headers={'X-My-Fav-Header': 'header value'})
```

Unimplemented API Endpoints

- Since the qBittorrent Web API has evolved over time, some endpoints may not be available from the qBittorrent host.
- By default, if a request is made to endpoint that doesn't exist for the version of the qBittorrent host (e.g., the Search endpoints were introduced in Web API v2.1.1), there's a debug logger output and None is returned.
- To raise `NotImplementedError` instead, instantiate `Client` with:

```
qbt_client = Client(..., RAISE_NOTIMPLEMENTEDERROR_FOR_UNIMPLEMENTED_API_ENDPOINTS=True)
```

qBittorrent Version Checking

- It is also possible to either raise an Exception for qBittorrent hosts that are not “fully” supported or manually check for support.
- The most likely situation for this to occur is if the qBittorrent team publishes a new release but its changes have not been incorporated in to this client yet.
- Instantiate `Client` like below to raise `UnsupportedQbittorrentVersion` exception for versions not fully supported:

```
qbt_client = Client(..., RAISE_ERROR_FOR_UNSUPPORTED_QBITTORRENT_VERSIONS=True)
```

- Additionally, the `qbittorrentapi.Version` class can be used for manual introspection of the versions.

```
Version.is_app_version_supported(qbt_client.app.version)
```

Disable Logging Debug Output

- Instantiate Client with `DISABLE_LOGGING_DEBUG_OUTPUT=True` or manually disable logging for the relevant packages:

```
logging.getLogger('qbittorrentapi').setLevel(logging.INFO)
logging.getLogger('requests').setLevel(logging.INFO)
logging.getLogger('urllib3').setLevel(logging.INFO)
```

1.4.3 Performance

By default, complex objects are returned from some endpoints. These objects allow for accessing the response's items as attributes and include methods for contextually relevant actions (such as `start()` and `stop()` for a torrent, for example).

This comes at the cost of performance, though. Generally, this cost isn't large; however, some endpoints, such as `torrents_files()`, may need to convert a large payload and the cost can be significant.

This client can be configured to always return only the simple JSON if desired. Simply set `SIMPLE_RESPONSES=True` when instantiating the client.

```
qbt_client = qbittorrentapi.Client(
    host='localhost:8080',
    username='admin',
    password='adminadmin',
    SIMPLE_RESPONSES=True,
)
```

Alternatively, `SIMPLE_RESPONSES` can be set to `True` to return the simple JSON only for an individual method call.

```
qbt_client.torrents.files(torrent_hash='...', SIMPLE_RESPONSES=True)
```

1.4.4 Exceptions

exception `qbittorrentapi.exceptions.APIError`

Bases: `Exception`

Base error for all exceptions from this Client.

exception `qbittorrentapi.exceptions.UnsupportedQbittorrentVersion`

Bases: `APIError`

Connected qBittorrent is not fully supported by this Client.

exception `qbittorrentapi.exceptions.FileError`

Bases: `OSError`, `APIError`

Base class for all exceptions for file handling.

exception `qbittorrentapi.exceptions.TorrentFileError`

Bases: `FileError`

Base class for all exceptions for torrent files.

exception qbittorrentapi.exceptions.**TorrentFileNotFoundError**

Bases: [TorrentFileError](#)

Specified torrent file does not appear to exist.

exception qbittorrentapi.exceptions.**TorrentFilePermissionError**

Bases: [TorrentFileError](#)

Permission was denied to read the specified torrent file.

exception qbittorrentapi.exceptions.**APIConnectionError**(*args, **kwargs)

Bases: [RequestException](#), [APIError](#)

Base class for all communications errors including HTTP errors.

exception qbittorrentapi.exceptions.**LoginFailed**(*args, **kwargs)

Bases: [APIConnectionError](#)

This can technically be raised with any request since log in may be attempted for any request and could fail.

exception qbittorrentapi.exceptions.**HTTPError**(*args, **kwargs)

Bases: [HTTPError](#), [APIConnectionError](#)

Base error for all HTTP errors.

All errors following a successful connection to qBittorrent are returned as HTTP statuses.

http_status_code = None

exception qbittorrentapi.exceptions.**HTTP4XXError**(*args, **kwargs)

Bases: [HTTPError](#)

Base error for all HTTP 4XX statuses.

exception qbittorrentapi.exceptions.**HTTP5XXError**(*args, **kwargs)

Bases: [HTTPError](#)

Base error for all HTTP 5XX statuses.

exception qbittorrentapi.exceptions.**HTTP400Error**(*args, **kwargs)

Bases: [HTTP4XXError](#)

HTTP 400 Status.

http_status_code = 400

exception qbittorrentapi.exceptions.**HTTP401Error**(*args, **kwargs)

Bases: [HTTP4XXError](#)

HTTP 401 Status.

http_status_code = 401

exception qbittorrentapi.exceptions.**HTTP403Error**(*args, **kwargs)

Bases: [HTTP4XXError](#)

HTTP 403 Status.

http_status_code = 403

exception qbittorrentapi.exceptions.**HTTP404Error**(*args, **kwargs)

Bases: [HTTP4XXError](#)

HTTP 404 Status.

http_status_code = 404

exception qbittorrentapi.exceptions.**HTTP405Error**(*args, **kwargs)

Bases: [HTTP4XXError](#)

HTTP 405 Status.

http_status_code = 405

exception qbittorrentapi.exceptions.**HTTP409Error**(*args, **kwargs)

Bases: [HTTP4XXError](#)

HTTP 409 Status.

http_status_code = 409

exception qbittorrentapi.exceptions.**HTTP415Error**(*args, **kwargs)

Bases: [HTTP4XXError](#)

HTTP 415 Status.

http_status_code = 415

exception qbittorrentapi.exceptions.**HTTP500Error**(*args, **kwargs)

Bases: [HTTP5XXError](#)

HTTP 500 Status.

http_status_code = 500

exception qbittorrentapi.exceptions.**MissingRequiredParameters400Error**(*args, **kwargs)

Bases: [HTTP400Error](#)

Endpoint call is missing one or more required parameters.

exception qbittorrentapi.exceptions.**InvalidRequest400Error**(*args, **kwargs)

Bases: [HTTP400Error](#)

One or more endpoint arguments are malformed.

exception qbittorrentapi.exceptions.**Unauthorized401Error**(*args, **kwargs)

Bases: [HTTP401Error](#)

Primarily reserved for XSS and host header issues.

exception qbittorrentapi.exceptions.**Forbidden403Error**(*args, **kwargs)

Bases: [HTTP403Error](#)

Not logged in, IP has been banned, or calling an API method that isn't public.

exception qbittorrentapi.exceptions.**NotFound404Error**(*args, **kwargs)

Bases: [HTTP404Error](#)

This should mean qBittorrent couldn't find a torrent for the torrent hash.

exception qbittorrentapi.exceptions.**MethodNotAllowed405Error**(*args, **kwargs)

Bases: [HTTP405Error](#)

HTTP method is not supported for the API endpoint.

exception qbittorrentapi.exceptions.**Conflict409Error**(*args, **kwargs)

Bases: [HTTP409Error](#)

Returned if arguments don't make sense specific to the endpoint.

exception qbittorrentapi.exceptions.**UnsupportedMediaType415Error**(*args, **kwargs)

Bases: [HTTP415Error](#)

torrents/add endpoint will return this for invalid URL(s) or files.

exception qbittorrentapi.exceptions.**InternalServerError500Error**(*args, **kwargs)

Bases: [HTTP500Error](#)

Returned if qBittorrent errors internally while processing the request.

1.4.5 API Reference

Application

class qbittorrentapi.app.**AppAPIMixin**(host="", port=None, username=None, password=None, **kwargs)

Bases: [AuthAPIMixin](#)

Implementation of all Application API methods.

Usage

```
>>> from qbittorrentapi import Client
>>> client = Client(host='localhost:8080', username='admin', password=
↳ 'adminadmin')
>>> client.app_version()
>>> client.app_preferences()
```

app_build_info(*kwargs)

Retrieve build info.

Returns

[BuildInfoDictionary](#) - [https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-\(qBittorrent-4.1\)#user-content-get-build-info](https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-(qBittorrent-4.1)#user-content-get-build-info)

app_default_save_path(*kwargs)

Retrieves the default path for where torrents are saved.

Returns

string

app_preferences(*kwargs)

Retrieve qBittorrent application preferences.

Returns

[ApplicationPreferencesDictionary](#) - [https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-\(qBittorrent-4.1\)#user-content-get-application-preferences](https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-(qBittorrent-4.1)#user-content-get-application-preferences)

app_set_preferences(*prefs=None, **kwargs*)

Set one or more preferences in qBittorrent application.

Parameters

prefs – dictionary of preferences to set

Returns

None

app_shutdown(***kwargs*)

Shutdown qBittorrent.

app_version(***kwargs*)

Retrieve application version.

Returns

string

app_web_api_version(***kwargs*)

Retrieve web API version.

Returns

string

class qbittorrentapi.app.**Application**(**args, **kwargs*)

Allows interaction with Application API endpoints.

Usage

```
>>> from qbittorrentapi import Client
>>> client = Client(host='localhost:8080', username='admin', password=
↳ 'adminadmin')
>>> # these are all the same attributes that are available as named in
↳ the
>>> # endpoints or the more pythonic names in Client (with or without
↳ 'app_' prepended)
>>> webapiVersion = client.application.webapiVersion
>>> web_api_version = client.application.web_api_version
>>> app_web_api_version = client.application.web_api_version
>>> # access and set preferences as attributes
>>> is_dht_enabled = client.application.preferences.dht
>>> # supports sending a just subset of preferences to update
>>> client.application.preferences = dict(dht=(not is_dht_enabled))
>>> prefs = client.application.preferences
>>> prefs['web_ui_clickjacking_protection_enabled'] = True
>>> client.app.preferences = prefs
>>>
>>> client.application.shutdown()
```

property build_info

Implements `app_build_info()`

property default_save_path

Implements `app_default_save_path()`

property preferences

Implements `app_preferences()` and `app_set_preferences()`

set_preferences(*prefs=None, **kwargs*)

Implements [app_set_preferences\(\)](#)

shutdown()

Implements [app_shutdown\(\)](#)

property version

Implements [app_version\(\)](#)

property web_api_version

Implements [app_web_api_version\(\)](#)

class qbittorrentapi.app.**ApplicationPreferencesDictionary**(*data=None, client=None*)

Bases: [Dictionary](#)

Response for [app_preferences\(\)](#)

class qbittorrentapi.app.**BuildInfoDictionary**(*data=None, client=None*)

Bases: [Dictionary](#)

Response for [app_build_info\(\)](#)

AttrDict (internal)

Copyright (c) 2013 Brendan Curran-Johnson

class qbittorrentapi._attrdict.**AttrDict**(*args, **kwargs)

Bases: [dict](#), [MutableAttr](#)

A dict that implements MutableAttr.

class qbittorrentapi._attrdict.**MutableAttr**

Bases: [Attr](#), [MutableMapping](#)

A mixin class for a mapping that allows for attribute-style access of values.

class qbittorrentapi._attrdict.**Attr**

Bases: [Mapping](#)

A mixin class for a mapping that allows for attribute-style access of values.

A key may be used as an attribute if:

- It is a string
- It matches `^[A-Za-z][A-Za-z0-9_]*$` (i.e., a public attribute)
- The key doesn't overlap with any class attributes (for `Attr`, those would be `get`, `items`, `keys`, `values`, `mro`, and `register`).

If a value which is accessed as an attribute is a Sequence-type (and is not a string/bytes), it will be converted to a `_sequence_type` with any mappings within it converted to `Attrs`.

NOTE:

This means that if `_sequence_type` is not `None`, then a sequence accessed as an attribute will be a different object than if accessed as an attribute than if it is accessed as an item.

Authentication

class qbittorrentapi.auth.**AuthAPIMixin**(*host=""*, *port=None*, *username=None*, *password=None*, ***kwargs*)

Bases: [Request](#)

Implementation of all Authorization API methods.

Usage

```
>>> from qbittorrentapi import Client
>>> client = Client(host='localhost:8080', username='admin', password=
↳ 'adminadmin')
>>> _ = client.is_logged_in
>>> client.auth_log_in(username='admin', password='adminadmin')
>>> client.auth_log_out()
```

auth_log_in(*username=None*, *password=None*, ***kwargs*)

Log in to qBittorrent host.

Raises

- [LoginFailed](#) – if credentials failed to log in
- [Forbidden403Error](#) – if user is banned...or not logged in

Parameters

- **username** – username for qBittorrent client
- **password** – password for qBittorrent client

Returns

None

auth_log_out(***kwargs*)

End session with qBittorrent.

property is_logged_in

Returns True if low-overhead API call succeeds; False otherwise.

There isn't a reliable way to know if an existing session is still valid without attempting to use it. qBittorrent invalidates cookies when they expire.

Returns

True/False if current authorization cookie is accepted by qBittorrent

class qbittorrentapi.auth.**Authorization**(**args*, ***kwargs*)

Allows interaction with the Authorization API endpoints.

Usage

```
>>> from qbittorrentapi import Client
>>> client = Client(host='localhost:8080', username='admin', password=
↳ 'adminadmin')
>>> is_logged_in = client.auth.is_logged_in
>>> client.auth.log_in(username='admin', password='adminadmin')
>>> client.auth.log_out()
```

property is_logged_inImplements [is_logged_in\(\)](#)**log_in**(username=None, password=None, **kwargs)Implements [auth_log_in\(\)](#)**log_out**(**kwargs)Implements [auth_log_out\(\)](#)**Client**

```
class qbittorrentapi.client.Client(host="", port=None, username=None, password=None,
    EXTRA_HEADERS=None, REQUESTS_ARGS=None,
    VERIFY_WEBUI_CERTIFICATE=True,
    FORCE_SCHEME_FROM_HOST=False,
    RAISE_NOTIMPLEMENTEDERROR_FOR_UNIMPLEMENTED_API_ENDPOINTS=False,
    RAISE_ERROR_FOR_UNSUPPORTED_QBITTORRENT_VERSIONS=False,
    VERBOSE_RESPONSE_LOGGING=False,
    SIMPLE_RESPONSES=False,
    DISABLE_LOGGING_DEBUG_OUTPUT=False, **kwargs)
```

Bases: [LogAPIMixin](#), [SyncAPIMixin](#), [TransferAPIMixin](#), [TorrentsAPIMixin](#), [RSSAPIMixin](#), [SearchAPIMixin](#)

Initialize API for qBittorrent client.

Host must be specified. Username and password can be specified at login. A call to [auth_log_in\(\)](#) is not explicitly required if username and password are provided during Client construction.

Usage

```
>>> from qbittorrentapi import Client
>>> client = Client(host='localhost:8080', username='admin', password=
↳ 'adminadmin')
>>> torrents = client.torrents_info()
```

Parameters

- **host** – hostname for qBittorrent Web API, [http[s]://]localhost[:8080][/path]
- **port** – port number for qBittorrent Web API (ignored if host contains a port)
- **username** – username for qBittorrent Web API
- **password** – password for qBittorrent Web API
- **SIMPLE_RESPONSES** – By default, complex objects are returned from some endpoints. These objects will allow for accessing responses' items as attributes and include methods for contextually relevant actions. This comes at the cost of performance. Generally, this cost isn't large; however, some endpoints, such as `torrents_files()` method, may need to convert a large payload. Set this to True to return the simple JSON back. Alternatively, set this to True only for an individual method call. For instance, when requesting the files for a torrent: `client.torrents_files(hash='...', SIMPLE_RESPONSES=True)`
- **VERIFY_WEBUI_CERTIFICATE** – Set to False to skip verify certificate for HTTPS connections; for instance, if the connection is using a self-signed certificate. Not setting this to False for self-signed certs will cause a [APIConnectionError](#) exception to be raised.
- **EXTRA_HEADERS** – Dictionary of HTTP Headers to include in all requests made to qBittorrent.

- **REQUESTS_ARGS** – Dictionary of configuration for Requests package: <https://requests.readthedocs.io/en/latest/api/#requests.request>
- **FORCE_SCHEME_FROM_HOST** – If a scheme (i.e. http or https) is specified in host, it will be used regardless of whether qBittorrent is configured for HTTP or HTTPS communication. Normally, this client will attempt to determine which scheme qBittorrent is actually listening on... but this can cause problems in rare cases. Defaults `False`.
- **RAISE_NOTIMPLEMENTEDERROR_FOR_UNIMPLEMENTED_API_ENDPOINTS** – Some Endpoints may not be implemented in older versions of qBittorrent. Setting this to `True` will raise a `NotImplementedError` instead of just returning `None`.
- **RAISE_ERROR_FOR_UNSUPPORTED_QBITTORRENT_VERSIONS** – raise the `UnsupportedQbittorrentVersion` exception if the connected version of qBittorrent is not fully supported by this client. Defaults `False`.
- **DISABLE_LOGGING_DEBUG_OUTPUT** – Turn off debug output from logging for this package as well as Requests & urllib3.

Definitions

```
class qbittorrentapi.definitions.APINames(value, names=None, *, module=None, qualname=None,
                                         type=None, start=1, boundary=None)
```

Bases: `str`, `Enum`

API namespaces for API endpoints.

e.g torrents in `http://localhost:8080/api/v2/torrents/addTrackers`

Application = 'app'

Authorization = 'auth'

EMPTY = ''

Log = 'log'

RSS = 'rss'

Search = 'search'

Sync = 'sync'

Torrents = 'torrents'

Transfer = 'transfer'

```
class qbittorrentapi.definitions.ClientCache(*args, **kwargs)
```

Bases: `object`

Caches the client.

Subclass this for any object that needs access to the Client.

```
class qbittorrentapi.definitions.Dictionary(data=None, client=None)
```

Bases: `ClientCache`, `AttrDict`

Base definition of dictionary-like objects returned from qBittorrent.

```
class qbittorrentapi.definitions.List(list_entries=None, entry_class=None, client=None)
```

Bases: `UserList`

Base definition for list-like objects returned from qBittorrent.

```
class qbittorrentapi.definitions.ListEntry(data=None, client=None)
```

Bases: `Dictionary`

Base definition for objects within a list returned from qBittorrent.

```
class qbittorrentapi.definitions.TorrentState(value, names=None, *, module=None, qualname=None,
                                              type=None, start=1, boundary=None)
```

Bases: `str`, `Enum`

Torrent States as defined by qBittorrent.

Definitions:

- wiki: [https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-\(qBittorrent-4.1\)#user-content-get-torrent-list](https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-(qBittorrent-4.1)#user-content-get-torrent-list)
- code: <https://github.com/qbittorrent/qBittorrent/blob/5dcc14153f046209f1067299494a82e5294d883a/src/base/bittorrent/torrent.h#L73>

Usage

```
>>> from qbittorrentapi import Client, TorrentState
>>> client = Client()
>>> # print torrent hashes for torrents that are downloading
>>> for torrent in client.torrents_info():
>>>     # check if torrent is downloading
>>>     if torrent.state_enum.is_downloading:
>>>         print(f'{torrent.hash} is downloading...')
>>>     # the appropriate enum member can be directly derived
>>>     state_enum = TorrentState(torrent.state)
>>>     print(f'{torrent.hash}: {state_enum.value}')
```

```
ALLOCATING = 'allocating'
```

```
CHECKING_DOWNLOAD = 'checkingDL'
```

```
CHECKING_RESUME_DATA = 'checkingResumeData'
```

```
CHECKING_UPLOAD = 'checkingUP'
```

```
DOWNLOADING = 'downloading'
```

```
ERROR = 'error'
```

```
FORCED_DOWNLOAD = 'forcedDL'
```

```
FORCED_METADATA_DOWNLOAD = 'forcedMetaDL'
```

```
FORCED_UPLOAD = 'forcedUP'
```

```
METADATA_DOWNLOAD = 'metaDL'
```

```
MISSING_FILES = 'missingFiles'
```

MOVING = 'moving'

PAUSED_DOWNLOAD = 'pausedDL'

PAUSED_UPLOAD = 'pausedUP'

QUEUED_DOWNLOAD = 'queuedDL'

QUEUED_UPLOAD = 'queuedUP'

STALLED_DOWNLOAD = 'stalledDL'

STALLED_UPLOAD = 'stalledUP'

UNKNOWN = 'unknown'

UPLOADING = 'uploading'

property is_checking

Returns True if the State is categorized as Checking.

property is_complete

Returns True if the State is categorized as Complete.

property is_downloading

Returns True if the State is categorized as Downloading.

property is_errorred

Returns True if the State is categorized as Errorred.

property is_paused

Returns True if the State is categorized as Paused.

property is_uploading

Returns True if the State is categorized as Uploading.

class qbittorrentapi.definitions.TrackerStatus(*value, names=None, *, module=None, qualname=None, type=None, start=1, boundary=None*)

Bases: `int`, `Enum`

Tracker Statuses as defined by qBittorrent.

Definitions:

- wiki: [https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-\(qBittorrent-4.1\)#user-content-get-torrent-trackers](https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-(qBittorrent-4.1)#user-content-get-torrent-trackers)
- code: <https://github.com/qbittorrent/qBittorrent/blob/5dcc14153f046209f1067299494a82e5294d883a/src/base/bittorrent/trackerentry.h#L42>

Usage

```
>>> from qbittorrentapi import Client, TrackerStatus
>>> client = Client()
>>> # print torrent hashes for torrents that are downloading
>>> for torrent in client.torrents_info():
>>>     for tracker in torrent.trackers:
>>>         # display status for each tracker
```

(continues on next page)

(continued from previous page)

```
>>> print(f'{torrent.hash[-6:]}: {TrackerStatus(tracker.status).  
↪display:>13} :{tracker.url}')
```

DISABLED = 0

NOT_CONTACTED = 1

NOT_WORKING = 4

UPDATING = 3

WORKING = 2

property display

Returns a descriptive display value for status.

Log

class qbittorrentapi.log.LogAPIMixin(*host=""*, *port=None*, *username=None*, *password=None*, ***kwargs*)

Bases: [AppAPIMixin](#)

Implementation of all Log API methods.

Usage

```
>>> from qbittorrentapi import Client  
>>> client = Client(host='localhost:8080', username='admin', password=  
↪'adminadmin')  
>>> client.log_main(info=False)  
>>> client.log_peers()
```

log_main(*normal=None*, *info=None*, *warning=None*, *critical=None*, *last_known_id=None*, ***kwargs*)

Retrieve the qBittorrent log entries. Iterate over returned object.

Parameters

- **normal** – False to exclude normal entries
- **info** – False to exclude info entries
- **warning** – False to exclude warning entries
- **critical** – False to exclude critical entries
- **last_known_id** – only entries with an ID greater than this value will be returned

Returns

[LogMainList](#)

log_peers(*last_known_id=None*, ***kwargs*)

Retrieve qBittorrent peer log.

Parameters

- **last_known_id** – only entries with an ID greater than this value will be returned

Returns

[LogPeersList](#)

class qbittorrentapi.log.Log(client)

Allows interaction with Log API endpoints.

Usage

```
>>> from qbittorrentapi import Client
>>> client = Client(host='localhost:8080', username='admin', password=
↳ 'adminadmin')
>>> # this is all the same attributes that are available as named in the
>>> # endpoints or the more pythonic names in Client (with or without
↳ 'log_' prepended)
>>> log_list = client.log.main()
>>> peers_list = client.log.peers(hash='...')
>>> # can also filter log down with additional attributes
>>> log_info = client.log.main.info(last_known_id='...')
>>> log_warning = client.log.main.warning(last_known_id='...')
```

peers(last_known_id=None, **kwargs)

Implements `log_peers()`

class qbittorrentapi.log.LogPeersList(list_entries, client=None)

Bases: `List`

Response for `log_peers()`

class qbittorrentapi.log.LogPeer(data=None, client=None)

Bases: `ListEntry`

Item in `LogPeersList`

class qbittorrentapi.log.LogMainList(list_entries, client=None)

Bases: `List`

Response to `log_main()`

class qbittorrentapi.log.LogEntry(data=None, client=None)

Bases: `ListEntry`

Item in `LogMainList`

Request (internal)

class qbittorrentapi.request.Request(host="", port=None, username=None, password=None, **kwargs)

Bases: `object`

Facilitates HTTP requests to qBittorrent's Web API.

_cast(response, response_class, **response_kwargs)

Returns the API response casted to the requested class.

Parameters

- **response** – requests Response from API
- **response_class** – class to return response as; if none, response is returned
- **response_kwargs** – request-specific configuration for response

Returns

API response as type of `response_class`

_get(*_name=APINames.EMPTY, _method="", requests_args=None, requests_params=None, headers=None, params=None, data=None, files=None, response_class=None, **kwargs*)

Send GET request.

Parameters

- **api_namespace** – the namespace for the API endpoint (e.g. [APINames](#) or `torrents`)
- **api_method** – the name for the API endpoint (e.g. `add`)
- **kwargs** – see [_request\(\)](#)

Returns

Requests [Response](#)

static _get_data(*http_method, params=None, data=None, files=None, **kwargs*)

Determine data, params, and files for the Requests call.

Parameters

- **http_method** – get or post
- **params** – key value pairs to send with GET calls
- **data** – key value pairs to send with POST calls
- **files** – dictionary of files to send with request

Returns

final dictionaries of data to send to qBittorrent

static _get_headers(*headers=None, more_headers=None*)

Determine headers specific to this request. Request headers can be specified explicitly or with the requests kwargs. Headers specified in `self._EXTRA_HEADERS` are merged in Requests itself.

Parameters

- **headers** – headers specified for this specific request
- **more_headers** – headers from requests_kwargs arguments

Returns

final dictionary of headers for this specific request

_get_requests_kwargs(*requests_args=None, requests_params=None*)

Determine the requests_kwargs for the call to Requests. The global configuration in `self._REQUESTS_ARGS` is updated by any arguments provided for a specific call.

Parameters

- **requests_args** – default location to expect Requests requests_kwargs
- **requests_params** – alternative location to expect Requests requests_kwargs

Returns

final dictionary of Requests requests_kwargs

static _get_response_kwargs(*kwargs*)

Determine the kwargs for managing the response to return.

Parameters

kwargs – extra keywords arguments to be passed along in request

Returns

sanitized arguments

static `_handle_error_responses(data, params, response)`

Raise proper exception if qBittorrent returns Error HTTP Status.

_initialize_context()

Initialize and/or reset communications context with qBittorrent.

This is necessary on startup or when the authorization cookie needs to be replaced...perhaps because it expired, qBittorrent was restarted, significant settings changes, etc.

_initialize_lesser(*EXTRA_HEADERS=None, REQUESTS_ARGS=None, VERIFY_WEBUI_CERTIFICATE=True, FORCE_SCHEME_FROM_HOST=False, RAISE_UNIMPLEMENTEDERROR_FOR_UNIMPLEMENTED_API_ENDPOINTS=False, RAISE_NOTIMPLEMENTEDERROR_FOR_UNIMPLEMENTED_API_ENDPOINTS=False, RAISE_ERROR_FOR_UNSUPPORTED_QBITTORRENT_VERSIONS=False, VERBOSE_RESPONSE_LOGGING=False, PRINT_STACK_FOR_EACH_REQUEST=False, SIMPLE_RESPONSES=False, DISABLE_LOGGING_DEBUG_OUTPUT=False, MOCK_WEB_API_VERSION=None*)

Initialize lesser used configuration.

classmethod `_list2string(input_list=None, delimiter='')`

Convert entries in a list to a concatenated string.

Parameters

- **input_list** – list to convert
- **delimiter** – delimiter for concatenation

Returns

if input is a list, concatenated string... else whatever the input was

_post(*_name=APINames.EMPTY, _method="", requests_args=None, requests_params=None, headers=None, params=None, data=None, files=None, response_class=None, **kwargs*)

Send POST request.

Parameters

- **api_namespace** – the namespace for the API endpoint (e.g. [APINames](#) or `torrents`)
- **api_method** – the name for the API endpoint (e.g. `add`)
- **kwargs** – see `_request()`

Returns

Requests [Response](#)

_request(*http_method, api_namespace, api_method, requests_args=None, requests_params=None, headers=None, params=None, data=None, files=None, response_class=None, **kwargs*)

Meat and potatoes of sending requests to qBittorrent.

Parameters

- **http_method** – get or post
- **api_namespace** – the namespace for the API endpoint (e.g. [APINames](#) or `torrents`)
- **api_method** – the name for the API endpoint (e.g. `add`)
- **requests_args** – default location for Requests kwargs
- **requests_params** – alternative location for Requests kwargs

- **headers** – HTTP headers to send with the request
- **params** – key/value pairs to send with a GET request
- **data** – key/value pairs to send with a POST request
- **files** – files to be sent with the request
- **response_class** – class to use to cast the API response
- **kwargs** – arbitrary keyword arguments to send with the request

Returns

Requests [Response](#)

```
_request_manager(http_method, api_namespace, api_method, _retries=1, _retry_backoff_factor=0.3,  
requests_args=None, requests_params=None, headers=None, params=None,  
data=None, files=None, response_class=None, **kwargs)
```

Wrapper to manage request retries and severe exceptions.

This should retry at least once to account for the Web API switching from HTTP to HTTPS. During the second attempt, the URL is rebuilt using HTTP or HTTPS as appropriate.

property _session

Create or return existing HTTP session.

Returns

Requests [Session](#) object

```
_trigger_session_initialization()
```

Effectively resets the HTTP session by removing the reference to it.

During the next request, a new session will be created.

```
_verbose_logging(http_method, url, data, params, requests_kwargs, response)
```

Log verbose information about request.

Can be useful during development.

```
class qbittorrentapi.request.URL(client)
```

Bases: [object](#)

Management for the qBittorrent Web API URL.

```
build_base_url(headers, requests_kwargs=None)
```

Determine the Base URL for the Web API endpoints.

A URL is only actually built here if it's the first time here or the context was re-initialized. Otherwise, the most recently built URL is used.

If the user doesn't provide a scheme for the URL, it will try HTTP first and fall back to HTTPS if that doesn't work. While this is probably backwards, qBittorrent or an intervening proxy can simply redirect to HTTPS and that'll be respected.

Additionally, if users want to augment the path to the API endpoints, any path provided here will be preserved in the returned Base URL and prefixed to all subsequent API calls.

Parameters

- **headers** – HTTP headers for request
- **requests_kwargs** – arguments from user for HTTP HEAD request

Returns

base URL as a string for Web API endpoint

build_url(*api_namespace, api_method, headers, requests_kwargs*)

Create a fully qualified URL for the API endpoint.

Parameters

- **api_namespace** – the namespace for the API endpoint (e.g. torrents)
- **api_method** – the specific method for the API endpoint (e.g. info)
- **headers** – HTTP headers for request
- **requests_kwargs** – kwargs for any calls to Requests

Returns

fully qualified URL string for endpoint

build_url_path(*api_namespace, api_method*)

Determine the full URL path for the API endpoint.

Parameters

- **api_namespace** – the namespace for the API endpoint (e.g. torrents)
- **api_method** – the specific method for the API endpoint (e.g. info)

Returns

entire URL string for API endpoint (e.g. `http://localhost:8080/api/v2/torrents/info` or `http://example.com/qbt/api/v2/torrents/info`)

detect_scheme(*base_url, default_scheme, alt_scheme, headers, requests_kwargs*)

Determine if the URL endpoint is using HTTP or HTTPS.

Parameters

- **base_url** – urllib `ParseResult` URL object
- **default_scheme** – default scheme to use for URL
- **alt_scheme** – alternative scheme to use for URL if default doesn't work
- **headers** – HTTP headers for request
- **requests_kwargs** – kwargs for calls to Requests

Returns

scheme (i.e. HTTP or HTTPS)

RSS

class qbittorrentapi.rss.RSSAPIMixin(*host="", port=None, username=None, password=None, **kwargs*)

Bases: `AppAPIMixin`

Implementation of all RSS API methods.

Usage

```
>>> from qbittorrentapi import Client
>>> client = Client(host='localhost:8080', username='admin', password=
↳ 'adminadmin')
>>> rss_rules = client.rss_rules()
>>> client.rss_set_rule(rule_name="...", rule_def={...})
```

rss_add_feed(url=None, item_path=None, **kwargs)

Add new RSS feed. Folders in path must already exist.

Raises

[*Conflict409Error*](#) –

Parameters

- **url** – URL of RSS feed (e.g. <https://distrowatch.com/news/torrents.xml>)
- **item_path** – Name and/or path for new feed (e.g. Folder\Subfolder\FeedName)

Returns

None

rss_add_folder(folder_path=None, **kwargs)

Add an RSS folder. Any intermediate folders in path must already exist.

Raises

[*Conflict409Error*](#) –

Parameters

folder_path – path to new folder (e.g. Linux\ISOs)

Returns

None

rss_items(include_feed_data=None, **kwargs)

Retrieve RSS items and optionally feed data.

Parameters

include_feed_data – True or false to include feed data

Returns

[*RSSItemsDictionary*](#)

rss_mark_as_read(item_path=None, article_id=None, **kwargs)

Mark RSS article as read. If article ID is not provider, the entire feed is marked as read.

Raises

[*NotFound404Error*](#) –

Parameters

- **item_path** – path to item to be refreshed (e.g. Folder\Subfolder\ItemName)
- **article_id** – article ID from [*rss_items\(\)*](#)

Returns

None

rss_matching_articles(rule_name=None, **kwargs)

Fetch all articles matching a rule.

Parameters

rule_name – Name of rule to return matching articles

Returns

[*RSSItemsDictionary*](#)

rss_move_item(orig_item_path=None, new_item_path=None, **kwargs)

Move/rename an RSS item (folder, feed, etc).

Raises*Conflict409Error* –**Parameters**

- **orig_item_path** – path to item to be removed (e.g. Folder\Subfolder\ItemName)
- **new_item_path** – path to item to be removed (e.g. Folder\Subfolder\ItemName)

Returns

None

rss_refresh_item(*item_path=None, **kwargs*)

Trigger a refresh for an RSS item.

Note: qBittorrent v4.1.5 thru v4.1.8 all use Web API 2.2. However, this endpoint was introduced with v4.1.8; so, behavior may be undefined for these versions.

Parameters**item_path** – path to item to be refreshed (e.g. Folder\Subfolder\ItemName)**Returns**

None

rss_remove_item(*item_path=None, **kwargs*)

Remove an RSS item (folder, feed, etc).

NOTE: Removing a folder also removes everything in it.

Raises*Conflict409Error* –**Parameters****item_path** – path to item to be removed (e.g. Folder\Subfolder\ItemName)**Returns**

None

rss_remove_rule(*rule_name=None, **kwargs*)

Delete a RSS auto-downloading rule.

Parameters**rule_name** – Name of rule to delete**Returns**

None

rss_rename_rule(*orig_rule_name=None, new_rule_name=None, **kwargs*)

Rename an RSS auto-download rule.

Note: this endpoint did not work properly until qBittorrent v4.3.0

Parameters

- **orig_rule_name** – current name of rule
- **new_rule_name** – new name for rule

Returns

None

rss_rules(***kwargs*)

Retrieve RSS auto-download rule definitions.

Returns*RSSRulesDictionary***rss_setFeedURL**(url=None, item_path=None, **kwargs)

Update the URL for an existing RSS feed.

Raises*Conflict409Error* –**Parameters**

- **url** – URL of RSS feed (e.g <https://distrowatch.com/news/torrents.xml>)
- **item_path** – Name and/or path for feed (e.g. Folder\Subfolder\FeedName)

Returns

None

rss_set_feed_url(url=None, item_path=None, **kwargs)

Update the URL for an existing RSS feed.

Raises*Conflict409Error* –**Parameters**

- **url** – URL of RSS feed (e.g <https://distrowatch.com/news/torrents.xml>)
- **item_path** – Name and/or path for feed (e.g. Folder\Subfolder\FeedName)

Returns

None

rss_set_rule(rule_name=None, rule_def=None, **kwargs)

Create a new RSS auto-downloading rule.

Parameters

- **rule_name** – name for new rule
- **rule_def** – dictionary with rule fields - [https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-\(qBittorrent-4.1\)#user-content-set-auto-downloading-rule](https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-(qBittorrent-4.1)#user-content-set-auto-downloading-rule)

Returns

None

class qbittorrentapi.rss.RSS(*client*)

Allows interaction with RSS API endpoints.

Usage

```
>>> from qbittorrentapi import Client
>>> client = Client(host='localhost:8080', username='admin', password=
↳ 'adminadmin')
>>> # this is all the same attributes that are available as named in the
>>> # endpoints or the more pythonic names in Client (with or without
↳ 'log_' prepended)
>>> rss_rules = client.rss.rules
>>> client.rss.addFolder(folder_path="TPB")
>>> client.rss.addFeed(url='...', item_path="TPB\Top100")
>>> client.rss.remove_item(item_path="TPB") # deletes TPB and Top100
>>> client.rss.set_rule(rule_name="...", rule_def={...})
```

(continues on next page)

(continued from previous page)

```
>>> items = client.rss.items.with_data
>>> items_no_data = client.rss.items.without_data
```

add_feed(url=None, item_path=None, **kwargs)

Implements [rss_add_feed\(\)](#)

add_folder(folder_path=None, **kwargs)

Implements [rss_add_folder\(\)](#)

mark_as_read(item_path=None, article_id=None, **kwargs)

Implements [rss_mark_as_read\(\)](#)

matching_articles(rule_name=None, **kwargs)

Implements [rss_matching_articles\(\)](#)

move_item(orig_item_path=None, new_item_path=None, **kwargs)

Implements [rss_move_item\(\)](#)

refresh_item(item_path=None)

Implements [rss_refresh_item\(\)](#)

remove_item(item_path=None, **kwargs)

Implements [rss_remove_item\(\)](#)

remove_rule(rule_name=None, **kwargs)

Implements [rss_remove_rule\(\)](#)

rename_rule(orig_rule_name=None, new_rule_name=None, **kwargs)

Implements [rss_rename_rule\(\)](#)

property rules

Implements [rss_rules\(\)](#)

setFeedURL(url=None, item_path=None, **kwargs)

Implements [rss_set_feed_url\(\)](#)

set_feed_url(url=None, item_path=None, **kwargs)

Implements [rss_set_feed_url\(\)](#)

set_rule(rule_name=None, rule_def=None, **kwargs)

Implements [rss_set_rule\(\)](#)

class qbittorrentapi.rss.RSSItemsDictionary(data=None, client=None)

Bases: [Dictionary](#)

Response for [rss_items\(\)](#)

class qbittorrentapi.rss.RSSRulesDictionary(data=None, client=None)

Bases: [Dictionary](#)

Response for [rss_rules\(\)](#)

Search

class qbittorrentapi.search.**SearchAPIMixin**(*host="", port=None, username=None, password=None, **kwargs*)

Bases: [AppAPIMixin](#)

Implementation for all Search API methods.

Usage

```
>>> from qbittorrentapi import Client
>>> client = Client(host='localhost:8080', username='admin', password=
↳ 'adminadmin')
>>> search_job = client.search_start(pattern='Ubuntu', plugins='all',
↳ category='all')
>>> client.search_stop(search_id=search_job.id)
>>> # or
>>> search_job.stop()
>>>
```

search_categories(*plugin_name=None, **kwargs*)

Retrieve categories for search.

Note: endpoint was removed in qBittorrent v4.3.0

Parameters

plugin_name – Limit categories returned by plugin(s) (supports all and enabled)

Returns

[SearchCategoriesList](#)

search_delete(*search_id=None, **kwargs*)

Delete a search job.

Raises

[NotFound404Error](#) –

Parameters

search_id – ID of search to delete

Returns

None

search_enable_plugin(*plugins=None, enable=None, **kwargs*)

Enable or disable search plugin(s).

Parameters

- **plugins** – list of plugin names
- **enable** – Defaults to True if None or unset; use False to disable

Returns

None

search_install_plugin(*sources=None, **kwargs*)

Install search plugins from either URL or file.

Parameters

sources – list of URLs or filepaths

Returns

None

search_plugins(kwargs)**

Retrieve details of search plugins.

Returns*SearchPluginsList* - [https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-\(qBittorrent-4.1\)#user-content-get-search-plugins](https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-(qBittorrent-4.1)#user-content-get-search-plugins)**search_results(search_id=None, limit=None, offset=None, **kwargs)**

Retrieve the results for the search.

Raises

- *NotFound404Error* –
- *Conflict409Error* –

Parameters

- **search_id** – ID of search job
- **limit** – number of results to return
- **offset** – where to start returning results

Returns*SearchResultsDictionary* - [https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-\(qBittorrent-4.1\)#user-content-get-search-results](https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-(qBittorrent-4.1)#user-content-get-search-results)**search_start(pattern=None, plugins=None, category=None, **kwargs)**

Start a search. Python must be installed. Host may limit number of concurrent searches.

Raises*Conflict409Error* –**Parameters**

- **pattern** – term to search for
- **plugins** – list of plugins to use for searching (supports ‘all’ and ‘enabled’)
- **category** – categories to limit search; dependent on plugins. (supports ‘all’)

Returns*SearchJobDictionary***search_status(search_id=None, **kwargs)**

Retrieve status of one or all searches.

Raises*NotFound404Error* –**Parameters****search_id** – ID of search to get status; leave empty for status of all jobs**Returns***SearchStatusesList* - [https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-\(qBittorrent-4.1\)#user-content-get-search-status](https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-(qBittorrent-4.1)#user-content-get-search-status)**search_stop(search_id=None, **kwargs)**

Stop a running search.

Raises*NotFound404Error* –**Parameters****search_id** – ID of search job to stop**Returns**

None

search_uninstall_plugin(names=None, **kwargs)

Uninstall search plugins.

Parameters**names** – names of plugins to uninstall**Returns**

None

search_update_plugins(**kwargs)

Auto update search plugins.

Returns

None

class qbittorrentapi.search.**Search**(*args, **kwargs)

Allows interaction with Search API endpoints.

Usage

```
>>> from qbittorrentapi import Client
>>> client = Client(host='localhost:8080', username='admin', password=
↳ 'adminadmin')
>>> # this is all the same attributes that are available as named in the
>>> # endpoints or the more pythonic names in Client (with or without
↳ 'search_' prepended)
>>> # initiate searches and retrieve results
>>> search_job = client.search.start(pattern='Ubuntu', plugins='all',
↳ category='all')
>>> status = search_job.status()
>>> results = search_job.result()
>>> search_job.delete()
>>> # inspect and manage plugins
>>> plugins = client.search.plugins
>>> cats = client.search.categories(plugin_name='...')
>>> client.search.install_plugin(sources='...')
>>> client.search.update_plugins()
```

categories(plugin_name=None, **kwargs)Implements *search_categories()***delete**(search_id=None, **kwargs)Implements *search_delete()***enable_plugin**(plugins=None, enable=None, **kwargs)Implements *search_enable_plugin()***install_plugin**(sources=None, **kwargs)Implements *search_install_plugin()*

```

property plugins
    Implements search\_plugins\(\)

results(search_id=None, limit=None, offset=None, **kwargs)
    Implements search\_results\(\)

start(pattern=None, plugins=None, category=None, **kwargs)
    Implements search\_start\(\)

status(search_id=None, **kwargs)
    Implements search\_status\(\)

stop(search_id=None, **kwargs)
    Implements search\_stop\(\)

uninstall_plugin(sources=None, **kwargs)
    Implements search\_uninstall\_plugin\(\)

update_plugins(**kwargs)
    Implements search\_update\_plugins\(\)

class qbittorrentapi.search.SearchJobDictionary(data, client)
    Bases: Dictionary
    Response for search\_start\(\)

    delete(**kwargs)
        Implements search\_delete\(\)

    results(limit=None, offset=None, **kwargs)
        Implements search\_results\(\)

    status(**kwargs)
        Implements search\_status\(\)

    stop(**kwargs)
        Implements search\_stop\(\)

class qbittorrentapi.search.SearchResultsDictionary(data=None, client=None)
    Bases: Dictionary
    Response for search\_results\(\)

class qbittorrentapi.search.SearchStatusesList(list_entries, client=None)
    Bases: List
    Response for search\_status\(\)

class qbittorrentapi.search.SearchStatus(data=None, client=None)
    Bases: ListEntry
    Item in SearchStatusesList

class qbittorrentapi.search.SearchCategoriesList(list_entries, client=None)
    Bases: List
    Response for search\_categories\(\)

```

```
class qbittorrentapi.search.SearchCategory(data=None, client=None)
```

Bases: [ListEntry](#)

Item in [SearchCategoriesList](#)

```
class qbittorrentapi.search.SearchPluginsList(list_entries, client=None)
```

Bases: [List](#)

Response for [search_plugins\(\)](#)

```
class qbittorrentapi.search.SearchPlugin(data=None, client=None)
```

Bases: [ListEntry](#)

Item in [SearchPluginsList](#)

Sync

```
class qbittorrentapi.sync.SyncAPIMixin(host="", port=None, username=None, password=None,
                                       **kwargs)
```

Bases: [AppAPIMixin](#)

Implementation of all Sync API Methods.

Usage

```
>>> from qbittorrentapi import Client
>>> client = Client(host='localhost:8080', username='admin', password=
↳ 'adminadmin')
>>> maindata = client.sync_maindata(rid="...")
>>> torrent_peers = client.sync_torrent_peers(torrent_hash="...", rid=
↳ '...')
```

```
sync_maindata(rid=0, **kwargs)
```

Retrieves sync data.

Parameters

rid – response ID

Returns

[SyncMainDataDictionary](#) - [https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-\(qBittorrent-4.1\)#user-content-get-main-data](https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-(qBittorrent-4.1)#user-content-get-main-data)

```
sync_torrent_peers(torrent_hash=None, rid=0, **kwargs)
```

Retrieves torrent sync data.

Raises

[NotFound404Error](#) –

Parameters

- **torrent_hash** – hash for torrent
- **rid** – response ID

Returns

[SyncTorrentPeersDictionary](#) - [https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-\(qBittorrent-4.1\)#user-content-get-torrent-peers-data](https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-(qBittorrent-4.1)#user-content-get-torrent-peers-data)

class qbittorrentapi.sync.Sync(*client*)

Allows interaction with the Sync API endpoints.

Usage:

```
>>> from qbittorrentapi import Client
>>> client = Client(host='localhost:8080', username='admin', password=
↳ 'adminadmin')
>>> # these are all the same attributes that are available as named in the
>>> # endpoints or the more pythonic names in Client (with or without 'sync_'
↳ prepended)
>>> maindata = client.sync.maindata(rid="...")
>>> # for use when continuously calling maindata for changes in torrents
>>> # this will automatically request the changes since the last call
>>> md = client.sync.maindata.delta()
>>> #
>>> torrentPeers = client.sync.torrentPeers(hash="...", rid='...')
>>> torrent_peers = client.sync.torrent_peers(hash="...", rid='...')
```

class qbittorrentapi.sync.SyncMainDataDictionary(*data=None, client=None*)

Bases: *Dictionary*

Response for *sync_maindata()*

class qbittorrentapi.sync.SyncTorrentPeersDictionary(*data=None, client=None*)

Bases: *Dictionary*

Response for *sync_torrent_peers()*

Torrents

class qbittorrentapi.torrents.TorrentsAPIMixin(*host="", port=None, username=None, password=None, **kwargs*)

Bases: *AppAPIMixin*

Implementation of all Torrents API methods.

Usage

```
>>> from qbittorrentapi import Client
>>> client = Client(host='localhost:8080', username='admin', password=
↳ 'adminadmin')
>>> client.torrents_add(urls='...')
>>> client.torrents_reannounce()
```

torrents_add(*urls=None, torrent_files=None, save_path=None, cookie=None, category=None, is_skip_checking=None, is_paused=None, is_root_folder=None, rename=None, upload_limit=None, download_limit=None, use_auto_torrent_management=None, is_sequential_download=None, is_first_last_piece_priority=None, tags=None, content_layout=None, ratio_limit=None, seeding_time_limit=None, download_path=None, use_download_path=None, stop_condition=None, **kwargs*)

Add one or more torrents by URLs and/or torrent files.

Raises

- **UnsupportedMediaType415Error** – if file is not a valid torrent file

- ***TorrentFileNotFoundError*** – if a torrent file doesn't exist
- ***TorrentFilePermissionError*** – if read permission is denied to torrent file

Parameters

- **urls** – single instance or an iterable of URLs (`http://`, `https://`, `magnet:`, `bc://bt/`)
- **torrent_files** – several options are available to send torrent files to qBittorrent:
 - single instance of bytes: useful if torrent file already read from disk or downloaded from internet.
 - single instance of file handle to torrent file: use `open(<filepath>, 'rb')` to open the torrent file.
 - single instance of a filepath to torrent file: e.g. `/home/user/torrent_filename.torrent`
 - an iterable of the single instances above to send more than one torrent file
 - dictionary with key/value pairs of torrent name and single instance of above object

Note: The torrent name in a dictionary is useful to identify which torrent file errored. qBittorrent provides back that name in the error text. If a torrent name is not provided, then the name of the file will be used. And in the case of bytes (or if filename cannot be determined), the value `'torrent__n'` will be used.

- **save_path** – location to save the torrent data
- **cookie** – cookie to retrieve torrents by URL
- **category** – category to assign to torrent(s)
- **is_skip_checking** – True to skip hash checking
- **is_paused** – True to add the torrent(s) without starting their downloading
- **is_root_folder** – True or False to create root folder (superseded by `content_layout` with v4.3.2)
- **rename** – new name for torrent(s)
- **upload_limit** – upload limit in bytes/second
- **download_limit** – download limit in bytes/second
- **use_auto_torrent_management** – True or False to use automatic torrent management
- **is_sequential_download** – True or False for sequential download
- **is_first_last_piece_priority** – True or False for first and last piece download priority
- **tags** – tag(s) to assign to torrent(s) (added in Web API 2.6.2)
- **content_layout** – Original, Subfolder, or NoSubfolder to control filesystem structure for content (added in Web API 2.7)
- **ratio_limit** – share limit as ratio of upload amt over download amt; e.g. 0.5 or 2.0 (added in Web API 2.8.1)
- **seeding_time_limit** – number of minutes to seed torrent (added in Web API 2.8.1)
- **download_path** – location to download torrent content before moving to `save_path` (added in Web API 2.8.4)

- **use_download_path** – True or False whether download_path should be used...defaults to True if download_path is specified (added in Web API 2.8.4)
- **stop_condition** – MetadataReceived or FilesChecked to stop the torrent when started automatically (added in Web API 2.8.15)

Returns

Ok. for success and Fails. for failure

torrents_add_peers(peers=None, torrent_hashes=None, **kwargs)

Add one or more peers to one or more torrents.

Raises

InvalidRequest400Error – for invalid peers

Parameters

- **peers** – one or more peers to add. each peer should take the form 'host:port'
- **torrent_hashes** – single torrent hash or list of torrent hashes. Or all for all torrents.

Returns

TorrentsAddPeersDictionary - {<hash>: {'added': #, 'failed': #}}

torrents_add_tags(tags=None, torrent_hashes=None, **kwargs)

Add one or more tags to one or more torrents.

Note: Tags that do not exist will be created on-the-fly.

Parameters

- **tags** – tag name or list of tags
- **torrent_hashes** – single torrent hash or list of torrent hashes. Or all for all torrents.

Returns

None

torrents_add_trackers(torrent_hash=None, urls=None, **kwargs)

Add trackers to a torrent.

Raises

NotFound404Error –

Parameters

- **torrent_hash** – hash for torrent
- **urls** – tracker URLs to add to torrent

Returns

None

torrents_bottom_priority(torrent_hashes=None, **kwargs)

Set torrent as lowest priority. Torrent Queuing must be enabled.

Raises

Conflict409Error –

Parameters

torrent_hashes – single torrent hash or list of torrent hashes. Or all for all torrents.

Returns

None

torrents_categories(***kwargs*)

Retrieve all category definitions.

Note: `torrents/categories` is not available until v2.1.0

Returns

TorrentCategoriesDictionary

torrents_create_category(*name=None, save_path=None, download_path=None, enable_download_path=None, **kwargs*)

Create a new torrent category.

Raises

Conflict409Error – if category name is not valid or unable to create

Parameters

- **name** – name for new category
- **save_path** – location to save torrents for this category (added in Web API 2.1.0)
- **download_path** – download location for torrents with this category
- **enable_download_path** – True or False to enable or disable download path

Returns

None

torrents_create_tags(*tags=None, **kwargs*)

Create one or more tags.

Parameters

tags – tag name or list of tags

Returns

None

torrents_decrease_priority(*torrent_hashes=None, **kwargs*)

Decrease the priority of a torrent. Torrent Queuing must be enabled.

Raises

Conflict409Error –

Parameters

torrent_hashes – single torrent hash or list of torrent hashes. Or `all` for all torrents.

Returns

None

torrents_delete(*delete_files=False, torrent_hashes=None, **kwargs*)

Remove a torrent from qBittorrent and optionally delete its files.

Parameters

- **torrent_hashes** – single torrent hash or list of torrent hashes. Or `all` for all torrents.
- **delete_files** – True to delete the torrent's files

Returns

None

torrents_delete_tags(*tags=None, **kwargs*)

Delete one or more tags.

Parameters**tags** – tag name or list of tags**Returns**

None

torrents_download_limit(*torrent_hashes=None, **kwargs*)

Retrieve the download limit for one or more torrents.

Returns*TorrentLimitsDictionary* - {hash: limit} (-1 represents no limit)**torrents_edit_category**(*name=None, save_path=None, download_path=None, enable_download_path=None, **kwargs*)

Edit an existing category.

Note: torrents/editCategory was introduced in Web API 2.1.0

Raises*Conflict409Error* – if category name is not valid or unable to create**Parameters**

- **name** – category to edit
- **save_path** – new location to save files for this category
- **download_path** – download location for torrents with this category
- **enable_download_path** – True or False to enable or disable download path

Returns

None

torrents_edit_tracker(*torrent_hash=None, original_url=None, new_url=None, **kwargs*)

Replace a torrent's tracker with a different one.

Raises

- *InvalidRequest400Error* –
- *NotFound404Error* –
- *Conflict409Error* –

Parameters

- **torrent_hash** – hash for torrent
- **original_url** – URL for existing tracker
- **new_url** – new URL to replace

Returns

None

torrents_export(*torrent_hash=None, **kwargs*)

Export a .torrent file for the torrent.

Raises

- *NotFound404Error* – torrent not found
- *Conflict409Error* – unable to export .torrent file

Parameters

torrent_hash – hash for torrent

Returns

bytes .torrent file

torrents_file_priority(*torrent_hash=None, file_ids=None, priority=None, **kwargs*)

Set priority for one or more files.

Raises

- **InvalidRequest400Error** – if priority is invalid or at least one file ID is not an integer
- **NotFound404Error** –
- **Conflict409Error** – if torrent metadata has not finished downloading or at least one file was not found

Parameters

- **torrent_hash** – hash for torrent
- **file_ids** – single file ID or a list.
- **priority** – priority for file(s) - [https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-\(qBittorrent-4.1\)#user-content-set-file-priority](https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-(qBittorrent-4.1)#user-content-set-file-priority)

Returns

None

torrents_files(*torrent_hash=None, **kwargs*)

Retrieve individual torrent's files.

Raises

NotFound404Error –

Parameters

torrent_hash – hash for torrent

Returns

TorrentFilesList - [https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-\(qBittorrent-4.1\)#user-content-get-torrent-contents](https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-(qBittorrent-4.1)#user-content-get-torrent-contents)

torrents_increase_priority(*torrent_hashes=None, **kwargs*)

Increase the priority of a torrent. Torrent Queuing must be enabled.

Raises

Conflict409Error –

Parameters

torrent_hashes – single torrent hash or list of torrent hashes. Or all for all torrents.

Returns

None

torrents_info(*status_filter=None, category=None, sort=None, reverse=None, limit=None, offset=None, torrent_hashes=None, tag=None, **kwargs*)

Retrieves list of info for torrents.

Parameters

- **status_filter** – Filter list by torrent status. all, downloading, seeding, completed, paused active, inactive, resumed, errored Added in Web API 2.4.1: stalled,

stalled_uploading, and stalled_downloading Added in Web API 2.8.4: checking
Added in Web API 2.8.18: moving

- **category** – Filter list by category
- **sort** – Sort list by any property returned
- **reverse** – Reverse sorting
- **limit** – Limit length of list
- **offset** – Start of list (if < 0, offset from end of list)
- **torrent_hashes** – Filter list by hash (separate multiple hashes with a '|') (added in Web API 2.0.1)
- **tag** – Filter list by tag (empty string means “untagged”; no “tag” parameter means “any tag”; added in Web API 2.8.3)

Returns

TorrentInfoList – [https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-\(qBittorrent-4.1\)#user-content-get-torrent-list](https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-(qBittorrent-4.1)#user-content-get-torrent-list)

torrents_pause(*torrent_hashes=None, **kwargs*)

Pause one or more torrents in qBittorrent.

Parameters

torrent_hashes – single torrent hash or list of torrent hashes. Or `all` for all torrents.

Returns

None

torrents_piece_hashes(*torrent_hash=None, **kwargs*)

Retrieve individual torrent’s pieces’ hashes.

Raises

NotFound404Error –

Parameters

torrent_hash – hash for torrent

Returns

TorrentPieceInfoList

torrents_piece_states(*torrent_hash=None, **kwargs*)

Retrieve individual torrent’s pieces’ states.

Raises

NotFound404Error –

Parameters

torrent_hash – hash for torrent

Returns

TorrentPieceInfoList

torrents_properties(*torrent_hash=None, **kwargs*)

Retrieve individual torrent’s properties.

Raises

NotFound404Error –

Parameters

torrent_hash – hash for torrent

Returns

TorrentPropertiesDictionary - [https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-\(qBittorrent-4.1\)#user-content-get-torrent-generic-properties](https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-(qBittorrent-4.1)#user-content-get-torrent-generic-properties)

torrents_reannounce(*torrent_hashes=None, **kwargs*)

Reannounce a torrent.

Note: torrents/reannounce introduced in Web API 2.0.2

Parameters

torrent_hashes – single torrent hash or list of torrent hashes. Or `all` for all torrents.

Returns

None

torrents_recheck(*torrent_hashes=None, **kwargs*)

Recheck a torrent in qBittorrent.

Parameters

torrent_hashes – single torrent hash or list of torrent hashes. Or `all` for all torrents.

Returns

None

torrents_remove_categories(*categories=None, **kwargs*)

Delete one or more categories.

Parameters

categories – categories to delete

Returns

None

torrents_remove_tags(*tags=None, torrent_hashes=None, **kwargs*)

Add one or more tags to one or more torrents.

Parameters

- **tags** – tag name or list of tags
- **torrent_hashes** – single torrent hash or list of torrent hashes. Or `all` for all torrents.

Returns

None

torrents_remove_trackers(*torrent_hash=None, urls=None, **kwargs*)

Remove trackers from a torrent.

Raises

- *NotFound404Error* –
- *Conflict409Error* –

Parameters

- **torrent_hash** – hash for torrent
- **urls** – tracker URLs to removed from torrent

Returns

None

torrents_rename(*torrent_hash=None, new_torrent_name=None, **kwargs*)

Rename a torrent.

Raises

NotFound404Error –

Parameters

- **torrent_hash** – hash for torrent
- **new_torrent_name** – new name for torrent

Returns

None

torrents_rename_file(*torrent_hash=None, file_id=None, new_file_name=None, old_path=None, new_path=None, **kwargs*)

Rename a torrent file.

Raises

- *MissingRequiredParameters400Error* –
- *NotFound404Error* –
- *Conflict409Error* –

Parameters

- **torrent_hash** – hash for torrent
- **file_id** – id for file (removed in Web API 2.7)
- **new_file_name** – new name for file (removed in Web API 2.7)
- **old_path** – path of file to rename (added in Web API 2.7)
- **new_path** – new path of file to rename (added in Web API 2.7)

Returns

None

torrents_rename_folder(*torrent_hash=None, old_path=None, new_path=None, **kwargs*)

Rename a torrent folder.

Raises

- *MissingRequiredParameters400Error* –
- *NotFound404Error* –
- *Conflict409Error* –

Parameters

- **torrent_hash** – hash for torrent
- **old_path** – path of file to rename (added in Web API 2.7)
- **new_path** – new path of file to rename (added in Web API 2.7)

Returns

None

torrents_resume(*torrent_hashes=None, **kwargs*)

Resume one or more torrents in qBittorrent.

Parameters

torrent_hashes – single torrent hash or list of torrent hashes. Or `all` for all torrents.

Returns

None

torrents_setDownloadPath(*download_path=None, torrent_hashes=None, **kwargs*)

Set the Download Path for one or more torrents.

Raises

- **Forbidden403Error** – cannot write to directory
- **Conflict409Error** – directory cannot be created

Parameters

- **download_path** – file path to save torrent contents before torrent finishes downloading
- **torrent_hashes** – single torrent hash or list of torrent hashes. Or `all` for all torrents.

torrents_setSavePath(*save_path=None, torrent_hashes=None, **kwargs*)

Set the Save Path for one or more torrents.

Raises

- **Forbidden403Error** – cannot write to directory
- **Conflict409Error** – directory cannot be created

Parameters

- **save_path** – file path to save torrent contents
- **torrent_hashes** – single torrent hash or list of torrent hashes. Or `all` for all torrents.

torrents_set_auto_management(*enable=None, torrent_hashes=None, **kwargs*)

Enable or disable automatic torrent management for one or more torrents.

Parameters

- **torrent_hashes** – single torrent hash or list of torrent hashes. Or `all` for all torrents.
- **enable** – Defaults to True if None or unset; use False to disable

Returns

None

torrents_set_category(*category=None, torrent_hashes=None, **kwargs*)

Set a category for one or more torrents.

Raises

Conflict409Error – for bad category

Parameters

- **torrent_hashes** – single torrent hash or list of torrent hashes. Or `all` for all torrents.
- **category** – category to assign to torrent

Returns

None

torrents_set_download_limit(*limit=None, torrent_hashes=None, **kwargs*)

Set the download limit for one or more torrents.

Parameters

- **torrent_hashes** – single torrent hash or list of torrent hashes. Or `all` for all torrents.
- **limit** – bytes/second (-1 sets the limit to infinity)

Returns

None

torrents_set_download_path(*download_path=None, torrent_hashes=None, **kwargs*)

Set the Download Path for one or more torrents.

Raises

- **Forbidden403Error** – cannot write to directory
- **Conflict409Error** – directory cannot be created

Parameters

- **download_path** – file path to save torrent contents before torrent finishes downloading
- **torrent_hashes** – single torrent hash or list of torrent hashes. Or `all` for all torrents.

torrents_set_force_start(*enable=None, torrent_hashes=None, **kwargs*)

Force start one or more torrents.

Parameters

- **torrent_hashes** – single torrent hash or list of torrent hashes. Or `all` for all torrents.
- **enable** – Defaults to `True` if `None` or unset; `False` is equivalent to `torrents_resume()`.

Returns

None

torrents_set_location(*location=None, torrent_hashes=None, **kwargs*)

Set location for torrents' files.

Raises

- **Forbidden403Error** – if the user doesn't have permissions to write to the location (only before v4.5.2 - write check was removed.)
- **Conflict409Error** – if the directory cannot be created at the location

Parameters

- **torrent_hashes** – single torrent hash or list of torrent hashes. Or `all` for all torrents.
- **location** – disk location to move torrent's files

Returns

None

torrents_set_save_path(*save_path=None, torrent_hashes=None, **kwargs*)

Set the Save Path for one or more torrents.

Raises

- **Forbidden403Error** – cannot write to directory
- **Conflict409Error** – directory cannot be created

Parameters

- **save_path** – file path to save torrent contents
- **torrent_hashes** – single torrent hash or list of torrent hashes. Or **all** for all torrents.

torrents_set_share_limits(*ratio_limit=None, seeding_time_limit=None, torrent_hashes=None, **kwargs*)

Set share limits for one or more torrents.

Parameters

- **torrent_hashes** – single torrent hash or list of torrent hashes. Or **all** for all torrents.
- **ratio_limit** – max ratio to seed a torrent. (-2 means use the global value and -1 is no limit)
- **seeding_time_limit** – minutes (-2 means use the global value and -1 is no limit)

Returns

None

torrents_set_super_seeding(*enable=None, torrent_hashes=None, **kwargs*)

Set one or more torrents as super seeding.

Parameters

- **torrent_hashes** – single torrent hash or list of torrent hashes. Or **all** for all torrents.
- **enable** – Defaults to True if None or unset; False to disable

Returns

torrents_set_upload_limit(*limit=None, torrent_hashes=None, **kwargs*)

Set the upload limit for one or more torrents.

Parameters

- **torrent_hashes** – single torrent hash or list of torrent hashes. Or **all** for all torrents.
- **limit** – bytes/second (-1 sets the limit to infinity)

Returns

None

torrents_tags(***kwargs*)

Retrieve all tag definitions.

Returns

TagList

torrents_toggle_first_last_piece_priority(*torrent_hashes=None, **kwargs*)

Toggle priority of first/last piece downloading.

Parameters

torrent_hashes – single torrent hash or list of torrent hashes. Or **all** for all torrents.

Returns

None

torrents_toggle_sequential_download(*torrent_hashes=None, **kwargs*)

Toggle sequential download for one or more torrents.

Parameters

torrent_hashes – single torrent hash or list of torrent hashes. Or **all** for all torrents.

Returns

None

torrents_top_priority(*torrent_hashes=None, **kwargs*)

Set torrent as highest priority. Torrent Queuing must be enabled.

Raises*Conflict409Error* –**Parameters****torrent_hashes** – single torrent hash or list of torrent hashes. Or `all` for all torrents.**Returns**

None

torrents_trackers(*torrent_hash=None, **kwargs*)Retrieve individual torrent's trackers. Tracker status is defined in *TrackerStatus*.**Raises***NotFound404Error* –**Parameters****torrent_hash** – hash for torrent**Returns***TrackersList* – [https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-\(qBittorrent-4.1\)#user-content-get-torrent-trackers](https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-(qBittorrent-4.1)#user-content-get-torrent-trackers)**torrents_upload_limit**(*torrent_hashes=None, **kwargs*)

Retrieve the upload limit for one or more torrents.

Parameters**torrent_hashes** – single torrent hash or list of torrent hashes. Or `all` for all torrents.**Returns***TorrentLimitsDictionary***torrents_webseeds**(*torrent_hash=None, **kwargs*)

Retrieve individual torrent's web seeds.

Raises*NotFound404Error* –**Parameters****torrent_hash** – hash for torrent**Returns***WebSeedsList* – [https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-\(qBittorrent-4.1\)#user-content-get-torrent-web-seeds](https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-(qBittorrent-4.1)#user-content-get-torrent-web-seeds)**class** qbittorrentapi.torrents.Torrents(*client*)

Allows interaction with the Torrents API endpoints.

Usage

```

>>> from qbittorrentapi import Client
>>> client = Client(host='localhost:8080', username='admin', password=
↳ 'adminadmin')
>>> # these are all the same attributes that are available as named in
↳ the
>>> # endpoints or the more pythonic names in Client (with or without

```

(continues on next page)

(continued from previous page)

```

↳ 'torrents_' prepended)
>>> torrent_list = client.torrents.info()
>>> torrent_list_active = client.torrents.info.active()
>>> torrent_list_active_partial = client.torrents.info.active(limit=100,
↳ offset=200)
>>> torrent_list_downloading = client.torrents.info.downloading()
>>> # torrent looping
>>> for torrent in client.torrents.info.completed()
>>> # all torrents endpoints with a 'hashes' parameters support all
↳ method to apply action to all torrents
>>> client.torrents.pause.all()
>>> client.torrents.resume.all()
>>> # or specify the individual hashes
>>> client.torrents.downloadLimit(torrent_hashes=['...', '...'])

```

add(urls=None, torrent_files=None, save_path=None, cookie=None, category=None, is_skip_checking=None, is_paused=None, is_root_folder=None, rename=None, upload_limit=None, download_limit=None, use_auto_torrent_management=None, is_sequential_download=None, is_first_last_piece_priority=None, tags=None, content_layout=None, ratio_limit=None, seeding_time_limit=None, download_path=None, use_download_path=None, stop_condition=None, **kwargs)

class qbittorrentapi.torrents.TorrentDictionary(data, client)

Bases: *Dictionary*

Item in *TorrentInfoList*. Allows interaction with individual torrents via the Torrents API endpoints.

Usage

```

>>> from qbittorrentapi import Client
>>> client = Client(host='localhost:8080', username='admin', password=
↳ 'adminadmin')
>>> # these are all the same attributes that are available as named in
↳ the
>>> # endpoints or the more pythonic names in Client (with or without
↳ 'transfer_' prepended)
>>> torrent = client.torrents.info()[0]
>>> torrent_hash = torrent.info.hash
>>> # Attributes without inputs and a return value are properties
>>> properties = torrent.properties
>>> trackers = torrent.trackers
>>> files = torrent.files
>>> # Action methods
>>> torrent.edit_tracker(original_url="...", new_url="...")
>>> torrent.remove_trackers(urls='http://127.0.0.2/')
>>> torrent.rename(new_torrent_name="...")
>>> torrent.resume()
>>> torrent.pause()
>>> torrent.recheck()
>>> torrent.torrents_top_priority()
>>> torrent.setLocation(location='/home/user/torrents/')
>>> torrent.setCategory(category='video')

```

add_tags(tags=None, **kwargs)

Implements `torrents_add_tags()`
add_trackers(*urls=None, **kwargs*)
 Implements `torrents_add_trackers()`
bottom_priority(***kwargs*)
 Implements `torrents_bottom_priority()`
decrease_priority(***kwargs*)
 Implements `torrents_decrease_priority()`
delete(*delete_files=None, **kwargs*)
 Implements `torrents_delete()`
property download_limit
 Implements `torrents_set_download_limit()`
edit_tracker(*orig_url=None, new_url=None, **kwargs*)
 Implements `torrents_edit_tracker()`
export(***kwargs*)
 Implements `torrents_export()`
file_priority(*file_ids=None, priority=None, **kwargs*)
 Implements `torrents_file_priority()`
property files
 Implements `torrents_files()`
increase_priority(***kwargs*)
 Implements `torrents_increase_priority()`
property info
 Implements `torrents_info()`
pause(***kwargs*)
 Implements `torrents_pause()`
property piece_hashes
 Implements `torrents_piece_hashes()`
property piece_states
 Implements `torrents_piece_states()`
property properties
 Implements `torrents_properties()`
reannounce(***kwargs*)
 Implements `torrents_reannounce()`
recheck(***kwargs*)
 Implements `torrents_recheck()`
remove_tags(*tags=None, **kwargs*)
 Implements `torrents_remove_tags()`
remove_trackers(*urls=None, **kwargs*)
 Implements `torrents_remove_trackers()`

rename(*new_name=None*, ***kwargs*)
Implements `torrents_rename()`

rename_file(*file_id=None*, *new_file_name=None*, *old_path=None*, *new_path=None*, ***kwargs*)
Implements `torrents_rename_file()`

rename_folder(*old_path=None*, *new_path=None*, ***kwargs*)
Implements `torrents_rename_folder()`

resume(***kwargs*)
Implements `torrents_resume()`

setDownloadPath(*download_path=None*, ***kwargs*)
Implements `torrents_set_download_path()`

setSavePath(*save_path=None*, ***kwargs*)
Implements `torrents_set_save_path()`

set_auto_management(*enable=None*, ***kwargs*)
Implements `torrents_set_auto_management()`

set_category(*category=None*, ***kwargs*)
Implements `torrents_set_category()`

set_download_limit(*limit=None*, ***kwargs*)
Implements `torrents_set_download_limit()`

set_download_path(*download_path=None*, ***kwargs*)
Implements `torrents_set_download_path()`

set_force_start(*enable=None*, ***kwargs*)
Implements `torrents_set_force_start()`

set_location(*location=None*, ***kwargs*)
Implements `torrents_set_location()`

set_save_path(*save_path=None*, ***kwargs*)
Implements `torrents_set_save_path()`

set_share_limits(*ratio_limit=None*, *seeding_time_limit=None*, ***kwargs*)
Implements `torrents_set_share_limits()`

set_super_seeding(*enable=None*, ***kwargs*)
Implements `torrents_set_super_seeding()`

set_upload_limit(*limit=None*, ***kwargs*)
Implements `torrents_set_upload_limit()`

property state_enum
Returns the state of a `TorrentState`.

sync_local()
Update local cache of torrent info.

toggle_first_last_piece_priority(***kwargs*)
Implements `torrents_toggle_first_last_piece_priority()`

toggle_sequential_download(**kwargs)

Implements `torrents_toggle_sequential_download()`

top_priority(**kwargs)

Implements `torrents_top_priority()`

property trackers

Implements `torrents_trackers()`

property upload_limit

Implements `torrents_upload_limit()`

property webseeds

Implements `torrents_webseeds()`

class qbittorrentapi.torrents.TorrentCategories(*args, **kwargs)

Bases: `ClientCache`

Allows interaction with torrent categories within the Torrents API endpoints.

Usage

```
>>> from qbittorrentapi import Client
>>> client = Client(host='localhost:8080', username='admin', password=
↳ 'adminadmin')
>>> # these are all the same attributes that are available as named in
↳ the
>>> # endpoints or the more pythonic names in Client (with or without
↳ 'torrents_' prepended)
>>> categories = client.torrent_categories.categories
>>> # create or edit categories
>>> client.torrent_categories.create_category(name='Video', save_path='/
↳ home/user/torrents/Video')
>>> client.torrent_categories.edit_category(name='Video', save_path='/
↳ data/torrents/Video')
>>> # edit or create new by assignment
>>> client.torrent_categories.categories = dict(name='Video', save_path=
↳ '/home/user/')
>>> # delete categories
>>> client.torrent_categories.removeCategories(categories='Video')
>>> client.torrent_categories.removeCategories(categories=['Audio',
↳ "ISOs"])
```

property categories

Implements `torrents_categories()`

create_category(name=None, save_path=None, download_path=None, enable_download_path=None, **kwargs)

Implements `torrents_create_category()`

edit_category(name=None, save_path=None, download_path=None, enable_download_path=None, **kwargs)

Implements `torrents_edit_category()`

remove_categories(categories=None, **kwargs)

Implements `torrents_remove_categories()`

class qbittorrentapi.torrents.TorrentTags(*args, **kwargs)

Bases: [ClientCache](#)

Allows interaction with torrent tags within the “Torrent” API endpoints.

Usage:

```
>>> from qbittorrentapi import Client
>>> client = Client(host='localhost:8080', username='admin', password=
↳ 'adminadmin')
>>> tags = client.torrent_tags.tags
>>> client.torrent_tags.tags = 'tv show' # create category
>>> client.torrent_tags.create_tags(tags=['tv show', 'linux distro'])
>>> client.torrent_tags.delete_tags(tags='tv show')
```

add_tags(tags=None, torrent_hashes=None, **kwargs)

Implements [torrents_add_tags\(\)](#)

create_tags(tags=None, **kwargs)

Implements [torrents_create_tags\(\)](#)

delete_tags(tags=None, **kwargs)

Implements [torrents_delete_tags\(\)](#)

remove_tags(tags=None, torrent_hashes=None, **kwargs)

Implements [torrents_remove_tags\(\)](#)

property tags

Implements [torrents_tags\(\)](#)

class qbittorrentapi.torrents.TorrentPropertiesDictionary(data=None, client=None)

Bases: [Dictionary](#)

Response to [torrents_properties\(\)](#)

class qbittorrentapi.torrents.TorrentLimitsDictionary(data=None, client=None)

Bases: [Dictionary](#)

Response to [torrents_download_limit\(\)](#)

class qbittorrentapi.torrents.TorrentCategoriesDictionary(data=None, client=None)

Bases: [Dictionary](#)

Response to [torrents_categories\(\)](#)

class qbittorrentapi.torrents.TorrentsAddPeersDictionary(data=None, client=None)

Bases: [Dictionary](#)

Response to [torrents_add_peers\(\)](#)

class qbittorrentapi.torrents.TorrentFilesList(list_entries, client=None)

Bases: [List](#)

Response to [torrents_files\(\)](#)

class qbittorrentapi.torrents.TorrentFile(data=None, client=None)

Bases: [ListEntry](#)

Item in [TorrentFilesList](#)


```

class qbittorrentapi.torrents.WebSeedsList(list_entries, client=None)
    Bases: List
    Response to torrents_webseeds()

class qbittorrentapi.torrents.WebSeed(data=None, client=None)
    Bases: ListEntry
    Item in WebSeedsList

class qbittorrentapi.torrents.TrackersList(list_entries, client=None)
    Bases: List
    Response to torrents_trackers()

class qbittorrentapi.torrents.Tracker(data=None, client=None)
    Bases: ListEntry
    Item in TrackersList

class qbittorrentapi.torrents.TorrentInfoList(list_entries, client=None)
    Bases: List
    Response to torrents_info()

class qbittorrentapi.torrents.TorrentPieceInfoList(list_entries, client=None)
    Bases: List
    Response to torrents_piece_states() and torrents_piece_hashes()

class qbittorrentapi.torrents.TorrentPieceData(data=None, client=None)
    Bases: ListEntry
    Item in TorrentPieceInfoList

class qbittorrentapi.torrents.TagList(list_entries, client=None)
    Bases: List
    Response to torrents_tags()

class qbittorrentapi.torrents.Tag(data=None, client=None)
    Bases: ListEntry
    Item in TagList

```

Transfer

```

class qbittorrentapi.transfer.TransferAPIMixin(host="", port=None, username=None, password=None,
                                              **kwargs)

```

Bases: [AppAPIMixin](#)

Implementation of all Transfer API methods.

Usage

```

>>> from qbittorrentapi import Client
>>> client = Client(host='localhost:8080', username='admin', password=
↳ 'adminadmin')
>>> transfer_info = client.transfer_info()
>>> client.transfer_set_download_limit(limit=1024000)

```

transfer_ban_peers(*peers=None, **kwargs*)

Ban one or more peers.

Parameters

peers – one or more peers to ban. each peer should take the form ‘host:port’

Returns

None

transfer_download_limit(***kwargs*)

Retrieves download limit. 0 is unlimited.

Returns

integer

transfer_info(***kwargs*)

Retrieves the global transfer info found in qBittorrent status bar.

Returns

TransferInfoDictionary - [https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-\(qBittorrent-4.1\)#user-content-get-global-transfer-info](https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-(qBittorrent-4.1)#user-content-get-global-transfer-info)

transfer_setSpeedLimitsMode(*intended_state=None, **kwargs*)

Sets whether alternative speed limits are enabled.

Parameters

intended_state – True to enable alt speed and False to disable. Leaving None will toggle the current state.

Returns

None

transfer_set_download_limit(*limit=None, **kwargs*)

Set the global download limit in bytes/second.

Parameters

limit – download limit in bytes/second (0 or -1 for no limit)

Returns

None

transfer_set_speed_limits_mode(*intended_state=None, **kwargs*)

Sets whether alternative speed limits are enabled.

Parameters

intended_state – True to enable alt speed and False to disable. Leaving None will toggle the current state.

Returns

None

transfer_set_upload_limit(*limit=None, **kwargs*)

Set the global download limit in bytes/second.

Parameters

limit – upload limit in bytes/second (0 or -1 for no limit)

Returns

None

transfer_speed_limits_mode(kwargs)**

Retrieves whether alternative speed limits are enabled.

Returns

1 if alternative speed limits are currently enabled, 0 otherwise

transfer_toggle_speed_limits_mode(intended_state=None, **kwargs)

Sets whether alternative speed limits are enabled.

Parameters

intended_state – True to enable alt speed and False to disable. Leaving None will toggle the current state.

Returns

None

transfer_upload_limit(kwargs)**

Retrieves upload limit. 0 is unlimited.

Returns

integer

class qbittorrentapi.transfer.Transfer(*args, **kwargs)

Allows interaction with the Transfer API endpoints.

Usage

```
>>> from qbittorrentapi import Client
>>> client = Client(host='localhost:8080', username='admin', password=
↳ 'adminadmin')
>>> # these are all the same attributes that are available as named in
↳ the
>>> # endpoints or the more pythonic names in Client (with or without
↳ 'transfer_' prepended)
>>> transfer_info = client.transfer.info
>>> # access and set download/upload limits as attributes
>>> dl_limit = client.transfer.download_limit
>>> # this updates qBittorrent in real-time
>>> client.transfer.download_limit = 1024000
>>> # update speed limits mode to alternate or not
>>> client.transfer.speedLimitsMode = True
```

ban_peers(peers=None, **kwargs)

Implements `transfer_ban_peers()`

property download_limit

Implements `transfer_download_limit()`

property info

Implements `transfer_info()`

setSpeedLimitsMode(intended_state=None, **kwargs)

Implements `transfer_set_speed_limits_mode()`

set_download_limit(limit=None, **kwargs)

Implements `transfer_set_download_limit()`

set_speed_limits_mode(*intended_state=None, **kwargs*)

Implements [`transfer_set_speed_limits_mode\(\)`](#)

set_upload_limit(*limit=None, **kwargs*)

Implements [`transfer_set_upload_limit\(\)`](#)

property speed_limits_mode

Implements [`transfer_speed_limits_mode\(\)`](#)

toggle_speed_limits_mode(*intended_state=None, **kwargs*)

Implements [`transfer_set_speed_limits_mode\(\)`](#)

property upload_limit

Implements [`transfer_upload_limit\(\)`](#)

class qbittorrentapi.transfer.**TransferInfoDictionary**(*data=None, client=None*)

Bases: [`Dictionary`](#)

Response to [`transfer_info\(\)`](#)

Version

class qbittorrentapi._version_support.**Version**

Allows introspection for whether this Client supports different versions of the qBittorrent application and its Web API.

Note that if a version is not listed as “supported” here, many (if not all) methods are likely to function properly since the Web API is largely backwards and forward compatible... albeit with some notable exceptions.

classmethod **is_api_version_supported**(*api_version*)

Returns whether a version of the qBittorrent Web API is fully supported by this API client.

Parameters

api_version – version of qBittorrent Web API version such as 2.8.4

Returns

True or False for whether version is supported

classmethod **is_app_version_supported**(*app_version*)

Returns whether a version of the qBittorrent application is fully supported by this API client.

Parameters

app_version – version of qBittorrent application such as v4.4.0

Returns

True or False for whether version is supported

classmethod **latest_supported_api_version**()

Returns the most recent version of qBittorrent Web API that is fully supported.

classmethod **latest_supported_app_version**()

Returns the most recent version of qBittorrent application that is fully supported.

classmethod **supported_api_versions**()

Set of all supported qBittorrent Web API versions.

classmethod **supported_app_versions**()

Set of all supported qBittorrent application versions.

PYTHON MODULE INDEX

q

`qbittorrentapi.definitions`, [17](#)
`qbittorrentapi.exceptions`, [9](#)
`qbittorrentapi.request`, [21](#)

Symbols

[_cast\(\)](#) (*qbittorrentapi.request.Request* method), 21
[_get\(\)](#) (*qbittorrentapi.request.Request* method), 22
[_get_data\(\)](#) (*qbittorrentapi.request.Request* static method), 22
[_get_headers\(\)](#) (*qbittorrentapi.request.Request* static method), 22
[_get_requests_kwargs\(\)](#) (*qbittorrentapi.request.Request* method), 22
[_get_response_kwargs\(\)](#) (*qbittorrentapi.request.Request* static method), 22
[_handle_error_responses\(\)](#) (*qbittorrentapi.request.Request* static method), 22
[_initialize_context\(\)](#) (*qbittorrentapi.request.Request* method), 23
[_initialize_lessor\(\)](#) (*qbittorrentapi.request.Request* method), 23
[_list2string\(\)](#) (*qbittorrentapi.request.Request* class method), 23
[_post\(\)](#) (*qbittorrentapi.request.Request* method), 23
[_request\(\)](#) (*qbittorrentapi.request.Request* method), 23
[_request_manager\(\)](#) (*qbittorrentapi.request.Request* method), 24
[_session](#) (*qbittorrentapi.request.Request* property), 24
[_trigger_session_initialization\(\)](#) (*qbittorrentapi.request.Request* method), 24
[_verbose_logging\(\)](#) (*qbittorrentapi.request.Request* method), 24

A

[add\(\)](#) (*qbittorrentapi.torrents.Torrents* method), 48
[add_feed\(\)](#) (*qbittorrentapi.rss.RSS* method), 29
[add_folder\(\)](#) (*qbittorrentapi.rss.RSS* method), 29
[add_tags\(\)](#) (*qbittorrentapi.torrents.TorrentDictionary* method), 48
[add_tags\(\)](#) (*qbittorrentapi.torrents.TorrentTags* method), 52
[add_trackers\(\)](#) (*qbittorrentapi.torrents.TorrentDictionary* method), 49
[ALLOCATING](#) (*qbittorrentapi.definitions.TorrentState* attribute), 18

[APIConnectionError](#), 10
[APIError](#), 9
[APINames](#) (class in *qbittorrentapi.definitions*), 17
[app_build_info\(\)](#) (*qbittorrentapi.app.AppAPIMixin* method), 12
[app_default_save_path\(\)](#) (*qbittorrentapi.app.AppAPIMixin* method), 12
[app_preferences\(\)](#) (*qbittorrentapi.app.AppAPIMixin* method), 12
[app_set_preferences\(\)](#) (*qbittorrentapi.app.AppAPIMixin* method), 12
[app_shutdown\(\)](#) (*qbittorrentapi.app.AppAPIMixin* method), 13
[app_version\(\)](#) (*qbittorrentapi.app.AppAPIMixin* method), 13
[app_web_api_version\(\)](#) (*qbittorrentapi.app.AppAPIMixin* method), 13
[AppAPIMixin](#) (class in *qbittorrentapi.app*), 12
[Application](#) (class in *qbittorrentapi.app*), 13
[Application](#) (*qbittorrentapi.definitions.APINames* attribute), 17
[ApplicationPreferencesDictionary](#) (class in *qbittorrentapi.app*), 14
[Attr](#) (class in *qbittorrentapi._attrdict*), 14
[AttrDict](#) (class in *qbittorrentapi._attrdict*), 14
[auth_log_in\(\)](#) (*qbittorrentapi.auth.AuthAPIMixin* method), 15
[auth_log_out\(\)](#) (*qbittorrentapi.auth.AuthAPIMixin* method), 15
[AuthAPIMixin](#) (class in *qbittorrentapi.auth*), 15
[Authorization](#) (class in *qbittorrentapi.auth*), 15
[Authorization](#) (*qbittorrentapi.definitions.APINames* attribute), 17

B

[ban_peers\(\)](#) (*qbittorrentapi.transfer.Transfer* method), 55
[bottom_priority\(\)](#) (*qbittorrentapi.torrents.TorrentDictionary* method), 49
[build_base_url\(\)](#) (*qbittorrentapi.request.URL* method), 24

`build_info` (*qbittorrentapi.app.Application* property), 13
`build_url()` (*qbittorrentapi.request.URL* method), 25
`build_url_path()` (*qbittorrentapi.request.URL* method), 25
`BuildInfoDictionary` (class in *qbittorrentapi.app*), 14

C

`categories` (*qbittorrentapi.torrents.TorrentCategories* property), 51
`categories()` (*qbittorrentapi.search.Search* method), 32
`CHECKING_DOWNLOAD` (*qbittorrentapi.definitions.TorrentState* attribute), 18
`CHECKING_RESUME_DATA` (*qbittorrentapi.definitions.TorrentState* attribute), 18
`CHECKING_UPLOAD` (*qbittorrentapi.definitions.TorrentState* attribute), 18
`Client` (class in *qbittorrentapi.client*), 16
`ClientCache` (class in *qbittorrentapi.definitions*), 17
`Conflict409Error`, 12
`create_category()` (*qbittorrentapi.torrents.TorrentCategories* method), 51
`create_tags()` (*qbittorrentapi.torrents.TorrentTags* method), 52

D

`decrease_priority()` (*qbittorrentapi.torrents.TorrentDictionary* method), 49
`default_save_path` (*qbittorrentapi.app.Application* property), 13
`delete()` (*qbittorrentapi.search.Search* method), 32
`delete()` (*qbittorrentapi.search.SearchJobDictionary* method), 33
`delete()` (*qbittorrentapi.torrents.TorrentDictionary* method), 49
`delete_tags()` (*qbittorrentapi.torrents.TorrentTags* method), 52
`detect_scheme()` (*qbittorrentapi.request.URL* method), 25
`Dictionary` (class in *qbittorrentapi.definitions*), 17
`DISABLED` (*qbittorrentapi.definitions.TrackerStatus* attribute), 20
`display` (*qbittorrentapi.definitions.TrackerStatus* property), 20
`download_limit` (*qbittorrentapi.torrents.TorrentDictionary* property), 49

`download_limit` (*qbittorrentapi.transfer.Transfer* property), 55
`DOWNLOADING` (*qbittorrentapi.definitions.TorrentState* attribute), 18

E

`edit_category()` (*qbittorrentapi.torrents.TorrentCategories* method), 51
`edit_tracker()` (*qbittorrentapi.torrents.TorrentDictionary* method), 49
`EMPTY` (*qbittorrentapi.definitions.APINames* attribute), 17
`enable_plugin()` (*qbittorrentapi.search.Search* method), 32
`ERROR` (*qbittorrentapi.definitions.TorrentState* attribute), 18
`export()` (*qbittorrentapi.torrents.TorrentDictionary* method), 49

F

`file_priority()` (*qbittorrentapi.torrents.TorrentDictionary* method), 49
`FileError`, 9
`files` (*qbittorrentapi.torrents.TorrentDictionary* property), 49
`Forbidden403Error`, 11
`FORCED_DOWNLOAD` (*qbittorrentapi.definitions.TorrentState* attribute), 18
`FORCED_METADATA_DOWNLOAD` (*qbittorrentapi.definitions.TorrentState* attribute), 18
`FORCED_UPLOAD` (*qbittorrentapi.definitions.TorrentState* attribute), 18

H

`HTTP400Error`, 10
`HTTP401Error`, 10
`HTTP403Error`, 10
`HTTP404Error`, 10
`HTTP405Error`, 11
`HTTP409Error`, 11
`HTTP415Error`, 11
`HTTP4XXError`, 10
`HTTP500Error`, 11
`HTTP5XXError`, 10
`http_status_code` (*qbittorrentapi.exceptions.HTTP400Error* attribute), 10
`http_status_code` (*qbittorrentapi.exceptions.HTTP401Error* attribute), 10

[http_status_code](#) (*qbittorrentapi.exceptions.HTTP403Error* attribute), [10](#)
[http_status_code](#) (*qbittorrentapi.exceptions.HTTP404Error* attribute), [11](#)
[http_status_code](#) (*qbittorrentapi.exceptions.HTTP405Error* attribute), [11](#)
[http_status_code](#) (*qbittorrentapi.exceptions.HTTP409Error* attribute), [11](#)
[http_status_code](#) (*qbittorrentapi.exceptions.HTTP415Error* attribute), [11](#)
[http_status_code](#) (*qbittorrentapi.exceptions.HTTP500Error* attribute), [11](#)
[http_status_code](#) (*qbittorrentapi.exceptions.HTTPError* attribute), [10](#)
[HTTPError](#), [10](#)
I
[increase_priority\(\)](#) (*qbittorrentapi.torrents.TorrentDictionary* method), [49](#)
[info](#) (*qbittorrentapi.torrents.TorrentDictionary* property), [49](#)
[info](#) (*qbittorrentapi.transfer.Transfer* property), [55](#)
[install_plugin\(\)](#) (*qbittorrentapi.search.Search* method), [32](#)
[InternalServerError500Error](#), [12](#)
[InvalidRequest400Error](#), [11](#)
[is_api_version_supported\(\)](#) (*qbittorrentapi._version_support.Version* class method), [56](#)
[is_app_version_supported\(\)](#) (*qbittorrentapi._version_support.Version* class method), [56](#)
[is_checking](#) (*qbittorrentapi.definitions.TorrentState* property), [19](#)
[is_complete](#) (*qbittorrentapi.definitions.TorrentState* property), [19](#)
[is_downloading](#) (*qbittorrentapi.definitions.TorrentState* property), [19](#)
[is_errored](#) (*qbittorrentapi.definitions.TorrentState* property), [19](#)
[is_logged_in](#) (*qbittorrentapi.auth.AuthAPIMixin* property), [15](#)
[is_logged_in](#) (*qbittorrentapi.auth.Authorization* property), [15](#)
[is_paused](#) (*qbittorrentapi.definitions.TorrentState* property), [19](#)
[is_uploading](#) (*qbittorrentapi.definitions.TorrentState* property), [19](#)
L
[latest_supported_api_version\(\)](#) (*qbittorrentapi._version_support.Version* class method), [56](#)
[latest_supported_app_version\(\)](#) (*qbittorrentapi._version_support.Version* class method), [56](#)
[List](#) (class in *qbittorrentapi.definitions*), [17](#)
[ListEntry](#) (class in *qbittorrentapi.definitions*), [18](#)
[Log](#) (class in *qbittorrentapi.log*), [20](#)
[Log](#) (*qbittorrentapi.definitions.APINames* attribute), [17](#)
[log_in\(\)](#) (*qbittorrentapi.auth.Authorization* method), [16](#)
[log_main\(\)](#) (*qbittorrentapi.log.LogAPIMixin* method), [20](#)
[log_out\(\)](#) (*qbittorrentapi.auth.Authorization* method), [16](#)
[log_peers\(\)](#) (*qbittorrentapi.log.LogAPIMixin* method), [20](#)
[LogAPIMixin](#) (class in *qbittorrentapi.log*), [20](#)
[LogEntry](#) (class in *qbittorrentapi.log*), [21](#)
[LoginFailed](#), [10](#)
[LogMainList](#) (class in *qbittorrentapi.log*), [21](#)
[LogPeer](#) (class in *qbittorrentapi.log*), [21](#)
[LogPeersList](#) (class in *qbittorrentapi.log*), [21](#)
M
[mark_as_read\(\)](#) (*qbittorrentapi.rss.RSS* method), [29](#)
[matching_articles\(\)](#) (*qbittorrentapi.rss.RSS* method), [29](#)
[METADATA_DOWNLOAD](#) (*qbittorrentapi.definitions.TorrentState* attribute), [18](#)
[MethodNotAllowed405Error](#), [11](#)
[MISSING_FILES](#) (*qbittorrentapi.definitions.TorrentState* attribute), [18](#)
[MissingRequiredParameters400Error](#), [11](#)
module
 qbittorrentapi.definitions, [17](#)
 qbittorrentapi.exceptions, [9](#)
 qbittorrentapi.request, [21](#)
[move_item\(\)](#) (*qbittorrentapi.rss.RSS* method), [29](#)
[MOVING](#) (*qbittorrentapi.definitions.TorrentState* attribute), [18](#)
[MutableAttr](#) (class in *qbittorrentapi._attrdict*), [14](#)
N
[NOT_CONTACTED](#) (*qbittorrentapi.definitions.TrackerStatus* attribute), [20](#)

NOT_WORKING (*qbittorrentapi.definitions.TrackerStatus* attribute), 20
 NotFound404Error, 11

P

pause() (*qbittorrentapi.torrents.TorrentDictionary* method), 49
 PAUSED_DOWNLOAD (*qbittorrentapi.definitions.TorrentState* attribute), 19
 PAUSED_UPLOAD (*qbittorrentapi.definitions.TorrentState* attribute), 19
 peers() (*qbittorrentapi.log.Log* method), 21
 piece_hashes (*qbittorrentapi.torrents.TorrentDictionary* property), 49
 piece_states (*qbittorrentapi.torrents.TorrentDictionary* property), 49
 plugins (*qbittorrentapi.search.Search* property), 32
 preferences (*qbittorrentapi.app.Application* property), 13
 properties (*qbittorrentapi.torrents.TorrentDictionary* property), 49

Q

qbittorrentapi.definitions module, 17
 qbittorrentapi.exceptions module, 9
 qbittorrentapi.request module, 21
 QUEUED_DOWNLOAD (*qbittorrentapi.definitions.TorrentState* attribute), 19
 QUEUED_UPLOAD (*qbittorrentapi.definitions.TorrentState* attribute), 19

R

reannounce() (*qbittorrentapi.torrents.TorrentDictionary* method), 49
 recheck() (*qbittorrentapi.torrents.TorrentDictionary* method), 49
 refresh_item() (*qbittorrentapi.rss.RSS* method), 29
 remove_categories() (*qbittorrentapi.torrents.TorrentCategories* method), 51
 remove_item() (*qbittorrentapi.rss.RSS* method), 29
 remove_rule() (*qbittorrentapi.rss.RSS* method), 29
 remove_tags() (*qbittorrentapi.torrents.TorrentDictionary* method), 49

remove_tags() (*qbittorrentapi.torrents.TorrentTags* method), 52
 remove_trackers() (*qbittorrentapi.torrents.TorrentDictionary* method), 49
 rename() (*qbittorrentapi.torrents.TorrentDictionary* method), 49
 rename_file() (*qbittorrentapi.torrents.TorrentDictionary* method), 50
 rename_folder() (*qbittorrentapi.torrents.TorrentDictionary* method), 50
 rename_rule() (*qbittorrentapi.rss.RSS* method), 29
 Request (class in *qbittorrentapi.request*), 21
 results() (*qbittorrentapi.search.Search* method), 33
 results() (*qbittorrentapi.search.SearchJobDictionary* method), 33
 resume() (*qbittorrentapi.torrents.TorrentDictionary* method), 50
 RSS (class in *qbittorrentapi.rss*), 28
 RSS (*qbittorrentapi.definitions.APINames* attribute), 17
 rss_add_feed() (*qbittorrentapi.rss.RSSAPIMixin* method), 25
 rss_add_folder() (*qbittorrentapi.rss.RSSAPIMixin* method), 26
 rss_items() (*qbittorrentapi.rss.RSSAPIMixin* method), 26
 rss_mark_as_read() (*qbittorrentapi.rss.RSSAPIMixin* method), 26
 rss_matching_articles() (*qbittorrentapi.rss.RSSAPIMixin* method), 26
 rss_move_item() (*qbittorrentapi.rss.RSSAPIMixin* method), 26
 rss_refresh_item() (*qbittorrentapi.rss.RSSAPIMixin* method), 27
 rss_remove_item() (*qbittorrentapi.rss.RSSAPIMixin* method), 27
 rss_remove_rule() (*qbittorrentapi.rss.RSSAPIMixin* method), 27
 rss_rename_rule() (*qbittorrentapi.rss.RSSAPIMixin* method), 27
 rss_rules() (*qbittorrentapi.rss.RSSAPIMixin* method), 27
 rss_set_feed_url() (*qbittorrentapi.rss.RSSAPIMixin* method), 28
 rss_set_rule() (*qbittorrentapi.rss.RSSAPIMixin* method), 28
 rss_setFeedURL() (*qbittorrentapi.rss.RSSAPIMixin* method), 28
 RSSAPIMixin (class in *qbittorrentapi.rss*), 25
 RSSitemsDictionary (class in *qbittorrentapi.rss*), 29
 RSSRulesDictionary (class in *qbittorrentapi.rss*), 29
 rules (*qbittorrentapi.rss.RSS* property), 29

S

Search (class in <i>qbittorrentapi.search</i>), 32	
Search (<i>qbittorrentapi.definitions.APINames</i> attribute), 17	
search_categories() (<i>qbittorrentapi.search.SearchAPIMixin</i> method), 30	
search_delete() (<i>qbittorrentapi.search.SearchAPIMixin</i> method), 30	
search_enable_plugin() (<i>qbittorrentapi.search.SearchAPIMixin</i> method), 30	
search_install_plugin() (<i>qbittorrentapi.search.SearchAPIMixin</i> method), 30	
search_plugins() (<i>qbittorrentapi.search.SearchAPIMixin</i> method), 31	
search_results() (<i>qbittorrentapi.search.SearchAPIMixin</i> method), 31	
search_start() (<i>qbittorrentapi.search.SearchAPIMixin</i> method), 31	
search_status() (<i>qbittorrentapi.search.SearchAPIMixin</i> method), 31	
search_stop() (<i>qbittorrentapi.search.SearchAPIMixin</i> method), 31	
search_uninstall_plugin() (<i>qbittorrentapi.search.SearchAPIMixin</i> method), 32	
search_update_plugins() (<i>qbittorrentapi.search.SearchAPIMixin</i> method), 32	
SearchAPIMixin (class in <i>qbittorrentapi.search</i>), 30	
SearchCategoriesList (class in <i>qbittorrentapi.search</i>), 33	
SearchCategory (class in <i>qbittorrentapi.search</i>), 33	
SearchJobDictionary (class in <i>qbittorrentapi.search</i>), 33	
SearchPlugin (class in <i>qbittorrentapi.search</i>), 34	
SearchPluginsList (class in <i>qbittorrentapi.search</i>), 34	
SearchResultsDictionary (class in <i>qbittorrentapi.search</i>), 33	
SearchStatus (class in <i>qbittorrentapi.search</i>), 33	
SearchStatusesList (class in <i>qbittorrentapi.search</i>), 33	
set_auto_management() (<i>qbittorrentapi.torrents.TorrentDictionary</i> method), 50	
set_category() (<i>qbittorrentapi.torrents.TorrentDictionary</i> method), 50	
set_download_limit() (<i>qbittorrentapi.torrents.TorrentDictionary</i> method), 50	
set_download_limit() (<i>qbittorrentapi.transfer.Transfer</i> method), 55	
set_download_path() (<i>qbittorrentapi.torrents.TorrentDictionary</i> method), 50	
set_feed_url() (<i>qbittorrentapi.rss.RSS</i> method), 29	
set_force_start() (<i>qbittorrentapi.torrents.TorrentDictionary</i> method), 50	
set_location() (<i>qbittorrentapi.torrents.TorrentDictionary</i> method), 50	
set_preferences() (<i>qbittorrentapi.app.Application</i> method), 13	
set_rule() (<i>qbittorrentapi.rss.RSS</i> method), 29	
set_save_path() (<i>qbittorrentapi.torrents.TorrentDictionary</i> method), 50	
set_share_limits() (<i>qbittorrentapi.torrents.TorrentDictionary</i> method), 50	
set_speed_limits_mode() (<i>qbittorrentapi.transfer.Transfer</i> method), 55	
set_super_seeding() (<i>qbittorrentapi.torrents.TorrentDictionary</i> method), 50	
set_upload_limit() (<i>qbittorrentapi.torrents.TorrentDictionary</i> method), 50	
set_upload_limit() (<i>qbittorrentapi.transfer.Transfer</i> method), 56	
setDownloadPath() (<i>qbittorrentapi.torrents.TorrentDictionary</i> method), 50	
setFeedURL() (<i>qbittorrentapi.rss.RSS</i> method), 29	
setSavePath() (<i>qbittorrentapi.torrents.TorrentDictionary</i> method), 50	
setSpeedLimitsMode() (<i>qbittorrentapi.transfer.Transfer</i> method), 55	
shutdown() (<i>qbittorrentapi.app.Application</i> method), 14	
speed_limits_mode (<i>qbittorrentapi.transfer.Transfer</i> property), 56	
STALLED_DOWNLOAD (<i>qbittorrentapi.definitions.TorrentState</i> attribute), 19	
STALLED_UPLOAD (<i>qbittorrentapi.definitions.TorrentState</i> attribute), 19	
start() (<i>qbittorrentapi.search.Search</i> method), 33	

state_enum (*qbittorrentapi.torrents.TorrentDictionary* property), 50
 status() (*qbittorrentapi.search.Search* method), 33
 status() (*qbittorrentapi.search.SearchJobDictionary* method), 33
 stop() (*qbittorrentapi.search.Search* method), 33
 stop() (*qbittorrentapi.search.SearchJobDictionary* method), 33
 supported_api_versions() (*qbittorrentapi._version_support.Version* class method), 56
 supported_app_versions() (*qbittorrentapi._version_support.Version* class method), 56
 Sync (class in *qbittorrentapi.sync*), 34
 Sync (*qbittorrentapidefinitions.APINames* attribute), 17
 sync_local() (*qbittorrentapi.torrents.TorrentDictionary* method), 50
 sync_maindata() (*qbittorrentapi.sync.SyncAPIMixin* method), 34
 sync_torrent_peers() (*qbittorrentapi.sync.SyncAPIMixin* method), 34
 SyncAPIMixin (class in *qbittorrentapi.sync*), 34
 SyncMainDataDictionary (class in *qbittorrentapi.sync*), 35
 SyncTorrentPeersDictionary (class in *qbittorrentapi.sync*), 35

T

Tag (class in *qbittorrentapi.torrents*), 53
 TagList (class in *qbittorrentapi.torrents*), 53
 tags (*qbittorrentapi.torrents.TorrentTags* property), 52
 toggle_first_last_piece_priority() (*qbittorrentapi.torrents.TorrentDictionary* method), 50
 toggle_sequential_download() (*qbittorrentapi.torrents.TorrentDictionary* method), 50
 toggle_speed_limits_mode() (*qbittorrentapi.transfer.Transfer* method), 56
 top_priority() (*qbittorrentapi.torrents.TorrentDictionary* method), 51
 TorrentCategories (class in *qbittorrentapi.torrents*), 51
 TorrentCategoriesDictionary (class in *qbittorrentapi.torrents*), 52
 TorrentDictionary (class in *qbittorrentapi.torrents*), 48
 TorrentFile (class in *qbittorrentapi.torrents*), 52
 TorrentFileError, 9
 TorrentFileNotFoundError, 9
 TorrentFilePermissionError, 10
 TorrentFilesList (class in *qbittorrentapi.torrents*), 52
 TorrentInfoList (class in *qbittorrentapi.torrents*), 53
 TorrentLimitsDictionary (class in *qbittorrentapi.torrents*), 52
 TorrentPieceData (class in *qbittorrentapi.torrents*), 53
 TorrentPieceInfoList (class in *qbittorrentapi.torrents*), 53
 TorrentPropertiesDictionary (class in *qbittorrentapi.torrents*), 52
 Torrents (class in *qbittorrentapi.torrents*), 47
 Torrents (*qbittorrentapidefinitions.APINames* attribute), 17
 torrents_add() (*qbittorrentapi.torrents.TorrentsAPIMixin* method), 35
 torrents_add_peers() (*qbittorrentapi.torrents.TorrentsAPIMixin* method), 37
 torrents_add_tags() (*qbittorrentapi.torrents.TorrentsAPIMixin* method), 37
 torrents_add_trackers() (*qbittorrentapi.torrents.TorrentsAPIMixin* method), 37
 torrents_bottom_priority() (*qbittorrentapi.torrents.TorrentsAPIMixin* method), 37
 torrents_categories() (*qbittorrentapi.torrents.TorrentsAPIMixin* method), 37
 torrents_create_category() (*qbittorrentapi.torrents.TorrentsAPIMixin* method), 38
 torrents_create_tags() (*qbittorrentapi.torrents.TorrentsAPIMixin* method), 38
 torrents_decrease_priority() (*qbittorrentapi.torrents.TorrentsAPIMixin* method), 38
 torrents_delete() (*qbittorrentapi.torrents.TorrentsAPIMixin* method), 38
 torrents_delete_tags() (*qbittorrentapi.torrents.TorrentsAPIMixin* method), 38
 torrents_download_limit() (*qbittorrentapi.torrents.TorrentsAPIMixin* method), 39
 torrents_edit_category() (*qbittorrentapi.torrents.TorrentsAPIMixin* method), 39
 torrents_edit_tracker() (*qbittorrentapi.torrents.TorrentsAPIMixin* method), 39

<code>torrents_export()</code> <i>rentapi.torrents.TorrentsAPIMixin</i> 39	(<i>qbittorrent</i> - <i>method</i>),	<code>torrents_set_auto_management()</code> <i>rentapi.torrents.TorrentsAPIMixin</i> 44	(<i>qbittorrent</i> - <i>method</i>),
<code>torrents_file_priority()</code> <i>rentapi.torrents.TorrentsAPIMixin</i> 40	(<i>qbittorrent</i> - <i>method</i>),	<code>torrents_set_category()</code> <i>rentapi.torrents.TorrentsAPIMixin</i> 44	(<i>qbittorrent</i> - <i>method</i>),
<code>torrents_files()</code> <i>rentapi.torrents.TorrentsAPIMixin</i> 40	(<i>qbittorrent</i> - <i>method</i>),	<code>torrents_set_download_limit()</code> <i>rentapi.torrents.TorrentsAPIMixin</i> 44	(<i>qbittorrent</i> - <i>method</i>),
<code>torrents_increase_priority()</code> <i>rentapi.torrents.TorrentsAPIMixin</i> 40	(<i>qbittorrent</i> - <i>method</i>),	<code>torrents_set_download_path()</code> <i>rentapi.torrents.TorrentsAPIMixin</i> 45	(<i>qbittorrent</i> - <i>method</i>),
<code>torrents_info()</code> <i>rentapi.torrents.TorrentsAPIMixin</i> 40	(<i>qbittorrent</i> - <i>method</i>),	<code>torrents_set_force_start()</code> <i>rentapi.torrents.TorrentsAPIMixin</i> 45	(<i>qbittorrent</i> - <i>method</i>),
<code>torrents_pause()</code> <i>rentapi.torrents.TorrentsAPIMixin</i> 41	(<i>qbittorrent</i> - <i>method</i>),	<code>torrents_set_location()</code> <i>rentapi.torrents.TorrentsAPIMixin</i> 45	(<i>qbittorrent</i> - <i>method</i>),
<code>torrents_piece_hashes()</code> <i>rentapi.torrents.TorrentsAPIMixin</i> 41	(<i>qbittorrent</i> - <i>method</i>),	<code>torrents_set_save_path()</code> <i>rentapi.torrents.TorrentsAPIMixin</i> 45	(<i>qbittorrent</i> - <i>method</i>),
<code>torrents_piece_states()</code> <i>rentapi.torrents.TorrentsAPIMixin</i> 41	(<i>qbittorrent</i> - <i>method</i>),	<code>torrents_set_share_limits()</code> <i>rentapi.torrents.TorrentsAPIMixin</i> 46	(<i>qbittorrent</i> - <i>method</i>),
<code>torrents_properties()</code> <i>rentapi.torrents.TorrentsAPIMixin</i> 41	(<i>qbittorrent</i> - <i>method</i>),	<code>torrents_set_super_seeding()</code> <i>rentapi.torrents.TorrentsAPIMixin</i> 46	(<i>qbittorrent</i> - <i>method</i>),
<code>torrents_reannounce()</code> <i>rentapi.torrents.TorrentsAPIMixin</i> 42	(<i>qbittorrent</i> - <i>method</i>),	<code>torrents_set_upload_limit()</code> <i>rentapi.torrents.TorrentsAPIMixin</i> 46	(<i>qbittorrent</i> - <i>method</i>),
<code>torrents_recheck()</code> <i>rentapi.torrents.TorrentsAPIMixin</i> 42	(<i>qbittorrent</i> - <i>method</i>),	<code>torrents_setDownloadPath()</code> <i>rentapi.torrents.TorrentsAPIMixin</i> 44	(<i>qbittorrent</i> - <i>method</i>),
<code>torrents_remove_categories()</code> <i>rentapi.torrents.TorrentsAPIMixin</i> 42	(<i>qbittorrent</i> - <i>method</i>),	<code>torrents_setSavePath()</code> <i>rentapi.torrents.TorrentsAPIMixin</i> 44	(<i>qbittorrent</i> - <i>method</i>),
<code>torrents_remove_tags()</code> <i>rentapi.torrents.TorrentsAPIMixin</i> 42	(<i>qbittorrent</i> - <i>method</i>),	<code>torrents_tags()</code> <i>rentapi.torrents.TorrentsAPIMixin</i> 46	(<i>qbittorrent</i> - <i>method</i>),
<code>torrents_remove_trackers()</code> <i>rentapi.torrents.TorrentsAPIMixin</i> 42	(<i>qbittorrent</i> - <i>method</i>),	<code>torrents_toggle_first_last_piece_priority()</code> (<i>qbittorrent</i> <i>rentapi.torrents.TorrentsAPIMixin</i> <i>method</i>), 46	
<code>torrents_rename()</code> <i>rentapi.torrents.TorrentsAPIMixin</i> 42	(<i>qbittorrent</i> - <i>method</i>),	<code>torrents_toggle_sequential_download()</code> (<i>qbittorrent</i> - <i>rentapi.torrents.TorrentsAPIMixin</i> <i>method</i>), 46	
<code>torrents_rename_file()</code> <i>rentapi.torrents.TorrentsAPIMixin</i> 43	(<i>qbittorrent</i> - <i>method</i>),	<code>torrents_top_priority()</code> <i>rentapi.torrents.TorrentsAPIMixin</i> 47	(<i>qbittorrent</i> - <i>method</i>),
<code>torrents_rename_folder()</code> <i>rentapi.torrents.TorrentsAPIMixin</i> 43	(<i>qbittorrent</i> - <i>method</i>),	<code>torrents_trackers()</code> <i>rentapi.torrents.TorrentsAPIMixin</i> 47	(<i>qbittorrent</i> - <i>method</i>),
<code>torrents_resume()</code> <i>rentapi.torrents.TorrentsAPIMixin</i> 43	(<i>qbittorrent</i> - <i>method</i>),	<code>torrents_upload_limit()</code> <i>rentapi.torrents.TorrentsAPIMixin</i> 47	(<i>qbittorrent</i> - <i>method</i>),
		<code>torrents_webseeds()</code>	(<i>qbittorrent</i> -

`rentapi.torrents.TorrentsAPIMixin` (method), 47

`TorrentsAddPeersDictionary` (class in `qbittorrentapi.torrents`), 52

`TorrentsAPIMixin` (class in `qbittorrentapi.torrents`), 35

`TorrentState` (class in `qbittorrentapi.definitions`), 18

`TorrentTags` (class in `qbittorrentapi.torrents`), 51

`Tracker` (class in `qbittorrentapi.torrents`), 53

`trackers` (`qbittorrentapi.torrents.TorrentDictionary` property), 51

`TrackersList` (class in `qbittorrentapi.torrents`), 53

`TrackerStatus` (class in `qbittorrentapi.definitions`), 19

`Transfer` (class in `qbittorrentapi.transfer`), 55

`Transfer` (`qbittorrentapi.definitions.APINames` attribute), 17

`transfer_ban_peers()` (`qbittorrentapi.transfer.TransferAPIMixin` method), 53

`transfer_download_limit()` (`qbittorrentapi.transfer.TransferAPIMixin` method), 54

`transfer_info()` (`qbittorrentapi.transfer.TransferAPIMixin` method), 54

`transfer_set_download_limit()` (`qbittorrentapi.transfer.TransferAPIMixin` method), 54

`transfer_set_speed_limits_mode()` (`qbittorrentapi.transfer.TransferAPIMixin` method), 54

`transfer_set_upload_limit()` (`qbittorrentapi.transfer.TransferAPIMixin` method), 54

`transfer_setSpeedLimitsMode()` (`qbittorrentapi.transfer.TransferAPIMixin` method), 54

`transfer_speed_limits_mode()` (`qbittorrentapi.transfer.TransferAPIMixin` method), 54

`transfer_toggle_speed_limits_mode()` (`qbittorrentapi.transfer.TransferAPIMixin` method), 55

`transfer_upload_limit()` (`qbittorrentapi.transfer.TransferAPIMixin` method), 55

`TransferAPIMixin` (class in `qbittorrentapi.transfer`), 53

`TransferInfoDictionary` (class in `qbittorrentapi.transfer`), 56

`UNKNOWN` (`qbittorrentapi.definitions.TorrentState` attribute), 19

`UnsupportedMediaType415Error`, 12

`UnsupportedQbittorrentVersion`, 9

`update_plugins()` (`qbittorrentapi.search.Search` method), 33

`UPDATING` (`qbittorrentapi.definitions.TrackerStatus` attribute), 20

`upload_limit` (`qbittorrentapi.torrents.TorrentDictionary` property), 51

`upload_limit` (`qbittorrentapi.transfer.Transfer` property), 56

`UPLOADING` (`qbittorrentapi.definitions.TorrentState` attribute), 19

`URL` (class in `qbittorrentapi.request`), 24

V

`Version` (class in `qbittorrentapi._version_support`), 56

`version` (`qbittorrentapi.app.Application` property), 14

W

`web_api_version` (`qbittorrentapi.app.Application` property), 14

`WebSeed` (class in `qbittorrentapi.torrents`), 53

`webseeds` (`qbittorrentapi.torrents.TorrentDictionary` property), 51

`WebSeedsList` (class in `qbittorrentapi.torrents`), 52

`WORKING` (`qbittorrentapi.definitions.TrackerStatus` attribute), 20

U

`Unauthorized401Error`, 11

`uninstall_plugin()` (`qbittorrentapi.search.Search` method), 33